



Search Results

- Evaluate
 - FAQ's
- Design a Solution
 - Part Drawings
 - PDFIn-Line Cabl ..
- How to Buy
 - Bill of Material
 - Favorite Products List
 - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click to remove) Search Tips Within Results

Text Search: 'IT9115-CUV18'

Your search criteria matched only one product, shown below

IT9115-CUV18



- No protruding head to cause injury since head is inverted
- No protruding tie tip to cause injury since the tip is trapped between the tie and the foam
- Tie will not slip on the foam since the head will indent the foam to remain captive
- Wide tie body .350" (8.9mm) for improved aesthetics
- Cannot over-tension tie causing bulges in the foam
- Install by hand or use *PANDUIT* GTH installation tool
- Flexible and easy to handle
- No need to heat weld the ends closed
- No cut-off scrap pieces to handle or pick up
- Strong: 124 lb. (550N) minimum loop tensile strength
- Locking wedge is protected from unlocking and from ultraviolet light exposure
- Weather Resistant Nylon 6.6 - Available in 13 ultraviolet colors (to match the foam) that will last 2-3 times longer than normal pigmented colors

NOTE: Ties are installed with the teeth on the inside against the foam.

	Part Number	IT9115-CUV18
	RoHS Compliancy Status	Compliant
	Part Description	IN-LINE Cable Tie, 15.3", LightHeavy cross section
	Product Type	Cable Ties
	Material	Ultraviolet (UV) Resistant Nylon 6.6
	Color	UV Tan
	CSA Certified	No
	UL Listed (File #E56854)	No
	UL Recognized (File #E56854)	No
	Length (In.)	15.3
	Length (mm)	389
	Width (In.)	.350
	Width (mm)	8.9
	CE Compliant	Yes
	Cross Section	Light-Heavy
	Head Height (In.)	.300
	Head Height (mm)	7.6
	Head Width (In.)	.556
	Head Width (mm)	14.1
	Locking Style	Locking
	Material Flammability Rating	UL 94V-2
	Max. Bundle Diameter (In.)	4.53
	Max. Bundle Diameter (mm)	115
	Max. Continuous Use Temperature	185°F (85°C)
	Min. Loop Tensile Strength (Lbs.)	124
	Min. Loop Tensile Strength (N)	552
	Pricing Description	Cable Tie, InLine, 15.3"L (389mm) LightHeavy, Weather Resistant, Tan
	Thickness (In.)	.065
	Thickness (mm)	1.7
	Tool	Hand Installation Recommended
	Min. Order UOM	PC
	Min. Order Qty.	100
	BOM Qty. (# of Pkgs.)	0
	Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.