Search Results

Evaluate
- FAQ's
- Selection Guides
- PDF Convenience ..

How to Buy
- Bill of Material
- Favorite Products List
- Locate Distributor

Current refinements (click ☒ to remove) Search Tips

☒ **Text Search: 'PK14-8R-E'**

Your search criteria matched only one product, shown below

PK14-8R-E

- For nuclear containment areas and high temperature to 300°F (150°C) applications
- Color code: natural with appropriate color stripe to identify wire range
- Ring tongue design assures a secure connection in high vibration applications
- UL and CSA rated up to 600 V per UL 486A/B

‡UL approved tooling/product combinations.

Part Number	PK14-8R-E
RoHS Compliancy Status	Compliant
Part Description	Ring terminal, 18– 14 AWG, KYNAR insulated, # 8 stud size.
Product Type	Terminals
Color	Blue Stripe
UL Listed	Yes
Length (In.)	0.87
Length (mm)	22.1
Width (In.)	0.31
Width (mm)	7.9
CE Compliant	No
Clearance	0.29
Clearance (mm)	7.4
Insulation	Kynar
Max. Ins.	0.162
Max. Ins. (mm)	4.12
Panduit Color Code	Blue Stripe
Plating Type	Tinned
Pricing Description	Terminal Convenience Package
Stock	0.03
Stock (mm)	0.8
Stud Size	#8
Temperature Rating	300 Degrees Fahrenheit (150 Degrees Celsius)
Tool	CT-100A, CT-600-A‡, CT-1550‡, CT-1551‡, CT-2500‡
Wire Range	18 – 14 AWG
Wire Range (mm²)	1.0 – 2.0
Min. Order UOM	PC
Min. Order Qty.	20
BOM Qty. (# of Pkgs.)	0
Add to Favorite Product List	

Please register to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.

Copyright © 1995-2011, PANDUIT CORP. All rights reserved. | Legal Information | Privacy Policy