Search Results

Evaluate
- FAQ's
Design a Solution
- Part Drawings
- PDF-Push Barb Mo..
- Specification Sheets
- PDF-Push Barb Mo..
How to Buy
- Bill of Material
- Favorite Products List
- Locate Distributor

Current refinements (click ☒ to remove) Search Tips

☒ **Text Search: 'PMA-065-M0'**

Your search criteria matched only one product, shown below

PMA-065-M0

• Robust barb design provides increased retention and lower insertion force, reducing operator fatigue and improving productivity
• Exclusive contoured anvil head firmly retains a minimum wire gauge of 12 AWG (2mm diameter) within plus or minus 10mm (.394") of the initial installation point, providing a low profile design

Part Number	PMA-065-M0
RoHS Compliancy Status	Compliant
Part Description	Push Barb Arrow Head Mount
Product Type	Cable Tie Mounts- Through Panel Hole
Material	Weather Resistant Nylon 6.6
Color	Black
CE Compliant	No
Environment	Outdoor
Flammability Rating	V-2
Head Diameter (In.)	0.65
Head Diameter (mm)	16.5
Mounting Method	Arrow Head Barb
Nominal Hole Diameter (In.)	0.250
Nominal Hole Diameter (mm)	6.4
Overall Height (In.)	0.60
Overall Height (mm)	15.3
Panel Thickness (In.)	0.08
Panel Thickness (mm)	2.0
Pricing Description	Push Barb Arrow Head Mount, WR BL
Sub Brand	Cable Tie Mount
Temperature Range	-60°C – 85°C (-76°F – 185°F)
Type	Through Hole
Used With Cable Ties	M, I, S
Min. Order UOM	PC
Min. Order Qty.	1
BOM Qty. (# of Pkgs.)	0
Add to Favorite Product List	

Please register to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.

Copyright © 1995-2011, PANDUIT CORP. All rights reserved. | Legal Information | Privacy Policy