

- Evaluate
 - FAQ's
- Design a Solution
 - Catalog Cut Sheet
 - PDFPN186FF-C P
 - Part Drawings
 - PDFFlanged Fork..
- How to Buy
 - Bill of Material
 - Favorite Products List
 - Locate Distributor

Current refinements (click to remove) Search Tips

Text Search: 'PV18-6FF-C'

Your search criteria matched only one product, shown below



- Fork design provides for fast and easy installation, without the need to remove fasteners
 - Flange design provides extra secure connection on a variety of applications
 - Insulation support helps to prevent wire damage in bending applications
 - Brazed seam protects terminal barrel from splitting during the crimp process
 - Internal barrel serrations assure good wire contact and maximum tensile strength
 - UL Flammability UL 94V-0, maximum insulation temperature 221°F (105°C)
 - UL and CSA rated up to 600 V per UL 486A/B
- ‡UL and CSA approved tooling/product combinations.

Part Number	PV18-6FF-CY
RoHS Compliancy Status	Compliant
Note	PV18-6FF-CY replaces PV18-6FF-C
Part Description	Flanged Fork Terminal, vinyl insulated, funnel entry, 22- 16 AWG, #6 stud size.
Product Type	Terminals
CSA Certified	Yes
UL Listed	Yes
Length (In.)	0.87
Length (mm)	22.1
Width (In.)	0.28
Width (mm)	7.1
CE Compliant	No
Clearance	0.19
Clearance (mm)	4.8
Insulation	Vinyl
Max. Ins.	0.150
Max. Ins. (mm)	3.8
Panduit Color Code	Red
Plating Type	Tinned
Pricing Description	Flanged Fork Terminal, vinyl insulated, 22 16 AWG, #6 stud size, funnel entry
Stock	0.03
Stock (mm)	0.8
Stud Size	#6
Temperature Rating	221 Degrees Fahrenheit (105 Degrees Celsius)
Tool	CT-100A‡, CT -600-A‡, CT -1550‡, CT-1551‡, CT-2500‡
Wire Range	22 – 16 AWG
Wire Range (mm²)	0.5 – 1.5
Min. Order UOM	PC
Min. Order Qty.	100
BOM Qty. (# of Pkgs.)	0
Add to Favorite Product List	e

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.