



Search Results

- Evaluate
- FAQ's

- Press Releases

- New Products ..
- How to Buy
- Bill of Material

- Favorite Products List

- Locate Distributor

[Home](#) > [Products Overview](#) > [Search Results](#) >

Current refinements (click to remove) [Search Tips](#) Within Results

Text Search: 'RSCK750-X350-1'

Your search criteria matched only one product, shown below

RSCK750-X350-1



- Includes all components in one package for making a complete electrical connection: *PANDUIT* copper compression RSC in -line reducing splice (see page D2.106 – D2.107) and crystal clear PVC heat shrink sleeves pre -cut to length to insulate reducing splice (See page)
- *PANDUIT* RSC in-line reducing splice is UL Listed and temperature rated to 90°C when crimped with *PANDUIT* crimping tools and dies
- *PANDUIT* crystal clear PVC heat shrink has a UL 224 VW -1 flammability rating and passes Telcordia GR-347-CORE Compression and Cut -Through Penetration Test and Abrasion Resistance Test
- *PANDUIT* crystal clear PVC heat shrink is UL Recognized with a temperature rating of 150°C, high temperature insulating property
- Rated for 600 V applications when *PANDUIT* crystal clear PVC heat shrink is applied

Part Number	RSCK750X350-1
RoHS Compliancy Status	Compliant
Part Description	Kit contains: 1 pc. RSC750X350-6 copper compression in-line reducing splice. 1 pc. HSTTPN150925-X crystal clear PVC heat shrink 1 1/2" dia. x 9.250" long.
Copper Conductor Size	750 kcmil
Reduces to Copper Conductor Size	350 Flex
Pricing Description	Copper Compression InLine Reducing Splice Kits, 750 kcmil- 350 Flex Code/Flex
Min. Order UOM	PC
Min. Order Qty.	1
BOM Qty. (# of Pkgs.)	0
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.