

Search Results

- Evaluate
- FAQ's
 - Press Releases
 - New Products ..
- How to Buy
- Bill of Material
 - Favorite Products List
 - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click  to remove) Search Tips  Within Results

 Text Search: 'RSCX750-4/0-1'

Your search criteria matched only one product, shown below

RSCX750-4/0-1



- Includes all components in one package for making a complete electrical connection: *PANDUIT* copper compression RSC in-line reducing splice (see page D2.106 – D2.107) and crystal clear PVC heat shrink sleeves pre-cut to length to insulate reducing splice (See page)
- *PANDUIT* RSC in-line reducing splice is UL Listed and temperature rated to 90°C when crimped with *PANDUIT* crimping tools and dies
- *PANDUIT* crystal clear PVC heat shrink has a UL 224 VW-1 flammability rating and passes Telcordia GR-347-CORE Compression and Cut-Through Penetration Test and Abrasion Resistance Test
- *PANDUIT* crystal clear PVC heat shrink is UL Recognized with a temperature rating of 150°C, high temperature insulating property
- Rated for 600 V applications when *PANDUIT* crystal clear PVC heat shrink is applied

 Part Number	RSCX750-4/0-1
 RoHS Compliancy Status	Compliant
 Part Description	Kit contains: 1 pc. RSCX750-4/0-3 copper compression in-line reducing splice. 1 pc. HSTTPN200-950-X crystal clear PVC heat shrink 2" dia. x 9.500" long. 1 pc. HSTTPN100-775-Q crystal clear PVC heat shrink 1" dia. x 7.750" long.
 Copper Conductor Size	750 FLEX
 Reduces to Copper Conductor Size	4/0 AWG
 Pricing Description	Copper Compression In-Line Reducing Splice Kits, 750 FLEX – 4/0 AWG Code/Flex
 Min. Order UOM	PC
 Min. Order Qty.	1
 BOM Qty. (# of Pkgs.)	0
 Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.