Search Results

Evaluate
- FAQ's
Design a Solution
- Part Drawings
- PDF Tie Harness ..
How to Buy
- Bill of Material
- Favorite Products List
- Locate Distributor

Current refinements (click ☒ to remove) Search Tips

☒ **Text Search: 'THMSC35FC30'**

Your search criteria matched only one product, shown below

THMSC35FC30

- Designed to be attached to the wire harness during assembly
- Cable ties can be installed by hand or with Panduit automatic cable tie tools
- Used with harness board standoff posts
- Available with or without corrugated tubing location tab
- Natural nylon material for indoor use
- Heat stabilized nylon material (30) for high temperature applications – indoor use

Part Number	THMSC35FC30
RoHS Compliancy Status	Compliant
Part Description	Tie Harness Mount Heat Stabilized
Product Type	Cable Tie Mounts- Through Panel Hole
Material	Heat Stabilized Nylon 6.6
Color	Black
UL Recognized	E136577
Height (In.)	0.46
Height (mm)	11.7
Length (In.)	1.54
Length (mm)	39.1
Width (In.)	0.37
Width (mm)	9.4
CE Compliant	No
Environment	Indoor/High Temp
Flammability Rating	V-2
Max. Panel Thickness (In.)	0.250
Max. Panel Thickness (mm)	6.4
Mounting Method	Fir Tree Hole Mount
Panel Hole Diameter Range (In.)	0.244 – 0.268
Panel Hole Diameter Range (mm)	6.2 – 6.8
Sub Brand	Cable Tie Mount
Type	Tie Harness Mount
Used With Cable Ties	M, I, S
Min. Order UOM	PC
Min. Order Qty.	100
BOM Qty. (# of Pkgs.)	0
Add to Favorite Product List	e

Please register to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.

Copyright © 1995-2011, PANDUIT CORP. All rights reserved. | Legal Information | Privacy Policy