

- visual and mechanical security
 Mechanical keyed configurations prevent unintentional insertion into adjacent ports (6 versions)
- Color-coded for easy identification
- Exceed ANSI/TIA-568-C.2 Category 6 and ISO 11801 Class E standards
- Meet requirements of IEEE 802.3af and IEEE 802.3at for PoE applications
- Each patch cord is 100% performance tested and wired T568B
- Constructed of Category 6, 24 AWG UTP stranded cable and TX6™ PLUS Modular Plugs; plug contacts plated with 50 microinches of gold for superior performance
- Plug meets all applicable ANSI/TIA-968-A requirements and exceeds IEC 60603-7 specifications
- · Slender strain relief boot provides easy access in high density applications
- Plug uses an integral pair manager to optimize performance and consistency by reducing

untwisting of conductors within the plug

- Perform in center of TIA/EIA component range, ensuring interoperability and excellent performance
- Labels on patch cords provide identification of performance level, length, and quality control number
- Patented tangle free latch prevents snags and provides easy release, saving time on frequent moves, adds, and changes
- Optional Patch Cord Color Bands snap on and off individual patch cables offering endless color-coding options
- Optional RJ45 Plug Lock-In Device blocks unauthorized removal of cable, IP phone, other networking equipment or critical connection

Part Number	UTPKSP3YL
 RoHS Compliancy Status 	Compliant
 Part Description 	Keyed, Category 6, UTP patch cord with TX6™ PLUS Keyed Modular Plug on one end and TX6™ PLUS Non-Keyed Modular Plug on the other end.
 Product Type 	Keyed Copper Patch Cord
Color	Yellow
 Length (ft.) 	3

 Length (m) 	0.91
Cable Color	Yellow
 Cable Type 	UTP
CE Compliant	No
 Connector 1 Type 	RJ45 8(8)
 Connector 2 Type 	RJ45 8(8)
 Flammability Rating 	CM
 Performance Level 	Category 6/Class E
 Pricing Description 	Keyed Copper Patch Cord, Cat 6, Yellow UTP Cable, 3 Feet
 Termination End 1 	Keyed Modular Plug
 Termination End 2 	Non-Keyed Modular Plug
 Wiring Scheme 	T568B
 Min. Order UOM 	PC
 Min. Order Qty. 	1
 Min. Order Qty. BOM Qty. (# of Pkgs.) 	1

Please register to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.

Home | Industries | Solutions | Services | Products | Partners | Support | Contact Us | Site Map | Careers Copyright @ 1995-2012, PANDUIT CORP. All rights reserved. | Legal Information | Privacy Policy