

Industries

Solutions

Services

Software

Products

Partners

Support



About Us



-Search-

Entire Site

Search Results

Evaluate

- FAQ's

- How to Buy
- Bill of Material
- Favorite Products List
- Locate Distributor

Home > Product On-Line Catalog > Search Results >

Current refinements (click 🛛 to remove) – Search Tips 🕝

☑ Text Search: 'UTPSP7Y-Q'

Your search criteria matched only one product, shown below

UTPSP7Y-Q



- Exceed ANSI/TIA-568-C.2 Category 6 and ISO 11801 Class E standards
- Meet requirements of IEEE 802.3af and IEEE 802.3at for PoE applications
- Each patch cord is 100% performance tested and wired T568B
- Constructed of Category 6, 24 AWG UTP stranded cable and TX6™ PLUS Modular Plugs; plug. contacts plated with 50 microinches of gold for superior performance
- Plug meets all applicable ANSI/TIA/EIA-968-A requirements and exceeds IEC 60603-7. specifications
- Slender strain relief boot provides easy access in high density applications
- Plug uses an integral pair manager to optimize performance and consistency by reducing untwisting of conductors within the plug
- Perform in center of TIA/EIA component range, ensuring interoperability and excellent performance
- Labels on patch cords provide identification of performance level, length, and quality control. number
- Patented tangle-free latch prevents snags and provides easy release, saving time on frequent moves, adds, and changes
- Optional patch cord color bands snap on and off individual patch cables offering endless color-coding options
- Optional RJ45 plug lock-in device blocks unauthorized removal of cable, IP phone, other networking equipment, or critical connection
- Third party tested for Category 6 component compliance

rima party tootoa for category	o outriportion comprising
Part Number	UTPSP7Y-Q
RoHS Compliancy Status	RoHS Compliant if purchased from Panduit EMEA after June 30, 2008. If not purchased from Panduit EMEA, contact your local Panduit Customer Service Dept.
Part Description	Category 6, UTP patch cord with TX6™ PLUS Modular Plugs on each end.
Product Type	UTP Patch Cord
Color	Off White
Length (ft.)	7
Length (m)	2.13
Boot Color	Clear
Cable Color	Off White
Cable Type	UTP
CE Compliant	No
Connector 1 Type	RJ45 8(8)
Connector 2 Type	RJ45 8(8)
Flammability Rating	CM
No. of Pairs	4
Performance Level	Category 6
Pricing Description	Copper Patch Cord, Cat 6, Off White UTP Cable, 7 Feet, Bulk Packaged
Termination End 1	Modular Plug
Termination End 2	Modular Plug
Wiring Scheme	T568B
Min. Order UOM	PC
Min. Order Gty.	25
BOM Qty. (# of Pkgs.)	0
Add to Favorite Product List	

Please register to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.