


Shrink sleeve - WMS 38,1 (60X60)R YE - 0800406

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)





Product Features

- The conductor to be marked is simply threaded through the sleeve and fixed by shrinking the sleeve
- The sleeves are pre-assembled for optimum use of material
- WMS ... shrink sleeves provide permanent and captive conductor and cable marking
- The shrink sleeves provide additional electrical insulation and mechanical protection for the conductors
- ☑ UL 224 (125°C, 600 V, all tubing)
- ☑ CSA.C22.2 No. 198.1 (125°C, 600 V, all tubing)

Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	1124.2 GRM
Custom tariff number	39173200
Country of origin	China

Technical data

Dimensions

Length (b)	60 mm
Width (a)	60 mm

Ambient conditions

Ambient temperature (operation)	-55 °C 135 °C

General

Color	yellow
Base element material	polyolefine
Components	Halogen-free



Shrink sleeve - WMS 38,1 (60X60)R YE - 0800406

Technical data

General

Material	Polyolefine
Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
Number of individual labels	250
Number of individual labels per row	1
Marking mounting type	slide on

Classifications

eCl@ss

eCl@ss 4.0	24190219
eCl@ss 4.1	24190219
eCl@ss 5.0	27400401
eCl@ss 5.1	27400401
eCl@ss 6.0	27400401
eCl@ss 7.0	27400401
eCl@ss 8.0	27400401

ETIM

ETIM 2.0	EC000761
ETIM 3.0	EC001530
ETIM 4.0	EC000217
ETIM 5.0	EC001530

UNSPSC

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121410
UNSPSC 11	39121410
UNSPSC 12.01	39121410
UNSPSC 13.2	39121410

Phoenix Contact 2014 @ - all rights reserved http://www.phoenixcontact.com