

Warning label - PML-W400 (58/19XE)R WH-OG - 1016499

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Warning label, can be labeled with: THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, THERMOMARK ROLL X1, THERMOMARK ROLL 2.0, THERMOMARK ROLL, mounting type: adhesive, Number of individual labels: 100

Your advantages

- ✓ Stick-on warning label, color preprinted
- ✓ Highly flexible, soft PVC label that adapts well to uneven surfaces
- ✓ Continuous media which can be cut to the desired length with the cutting unit on the printer or manually with scissors
- ✓ If high-quality ink ribbons are used, the labeling is resistant to solvents and suitable for use even under harsh industrial conditions
- ✓ A temperature range of -50°C to 90°C



Key Commercial Data

Packing unit	1 pc
GTIN	 4 055626 497150
GTIN	4055626497150

Technical data

Dimensions

Length (b)	48 m
Width (a)	77 mm

Ambient conditions

Ambient temperature (operation)	-40 °C ... 90 °C
---------------------------------	------------------

General

Components	Silicone-free
Material	PVC
Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
Number of individual labels	100
Marking mounting type	adhesive

Warning label - PML-W400 (58/19XE)R WH-OG - 1016499

Technical data

Standards and Regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
-----------------	-----------------------------

Classifications

eCl@ss

eCl@ss 10.0.1	40200202
eCl@ss 5.0	40200200
eCl@ss 6.0	40200200
eCl@ss 7.0	40200202
eCl@ss 9.0	40200202

Accessories

Accessories

Ink ribbon

Ink ribbon - THERMOMARK-RIBBON 110-WMTB HF - 5148007



Ink ribbon, for roll printer for printing product groups WMTB HF..., WMS-2 HF..., TMT..., and EMT..., width: 110 mm, color: black

Phoenix Contact 2020 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>