

## Sensor/actuator cable - SAC-8P- 1,5-PUR/M 8FS SH - 1404147

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Sensor/actuator cable, 8-position, PUR halogen-free, black-gray RAL 7021, shielded, free cable end, on Socket straight M8, cable length: 1.5 m

### Your advantages

- ✓ Easy and safe: 100% electrically tested plug-in components
- ✓ Our standard: robust halogen-free PUR cable
- ✓ Save space – with high-pos. connectors
- ✓ Reliable signal transmission – 360° shielding in environments with electromagnetic interference

RoHS

### Key Commercial Data

|              |                                                                                                         |
|--------------|---------------------------------------------------------------------------------------------------------|
| Packing unit | 1 pc                                                                                                    |
| GTIN         | <br>4 046356 680653 |
| GTIN         | 4046356680653                                                                                           |

### Technical data

#### Dimensions

|                 |       |
|-----------------|-------|
| Length of cable | 1.5 m |
|-----------------|-------|

#### Ambient conditions

|                                 |                                  |
|---------------------------------|----------------------------------|
| Ambient temperature (operation) | -25 °C ... 85 °C (Plug / socket) |
| Degree of protection            | IP65                             |
|                                 | IP67                             |

#### General

|                       |          |
|-----------------------|----------|
| Rated current at 40°C | 1.5 A    |
| Rated voltage         | 30 V AC  |
|                       | 30 V DC  |
| Number of positions   | 8        |
| Insulation resistance | ≥ 100 MΩ |

# Sensor/actuator cable - SAC-8P- 1,5-PUR/M 8FS SH - 1404147

## Technical data

### General

|                              |                              |
|------------------------------|------------------------------|
| Coding                       | A - standard                 |
| Standards/regulations        | M8 connector IEC 61076-2-104 |
| Status display               | No                           |
| Protective circuit/component | unwired                      |
| Degree of pollution          | 3                            |
| Insertion/withdrawal cycles  | ≥ 100                        |
| Torque                       | 0.2 Nm (M8 connectors)       |

### Material

|                                        |                                             |
|----------------------------------------|---------------------------------------------|
| Flammability rating according to UL 94 | HB                                          |
| Contact material                       | CuSn                                        |
| Contact surface material               | Ni/Au                                       |
| Contact carrier material               | TPU GF                                      |
| Material of grip body                  | TPU, hardly inflammable, self-extinguishing |
| Material, knurls                       | Zinc die-cast, nickel-plated                |
| Sealing material                       | NBR                                         |

### Standards and Regulations

|                                        |                              |
|----------------------------------------|------------------------------|
| Standards/specifications               | M8 connector IEC 61076-2-104 |
| Flammability rating according to UL 94 | HB                           |

### Cable

|                                               |                                                    |
|-----------------------------------------------|----------------------------------------------------|
| Cable type                                    | PUR halogen-free black                             |
| Cable abbreviation                            | Li9YV1-C-V1-11Y                                    |
| UL AWM style                                  | 20549                                              |
| Conductor cross section                       | 8x 0.14 mm <sup>2</sup> (Signal line)              |
| AWG signal line                               | 26                                                 |
| Conductor structure signal line               | 18x 0.10 mm                                        |
| Core diameter including insulation            | 1 mm ±0.02 mm (Signal line)                        |
| Thickness, insulation                         | ≥ 0.21 mm (Signal line)                            |
|                                               | ≥ 0.38 mm (Outer cable sheath)                     |
| Wire colors                                   | white, brown, green, yellow, gray, pink, blue, red |
| Overall twist                                 | 8 wires around filler to the core                  |
| Length of twist, overall twist                | 58 mm                                              |
| Shielding                                     | Tinned copper braided shield                       |
| Optical shield covering                       | 85 %                                               |
| External sheath, color                        | black-gray RAL 7021                                |
| External cable diameter D                     | 5.9 mm ±0.2 mm                                     |
| Smallest bending radius, fixed installation   | 29.5 mm                                            |
| Smallest bending radius, movable installation | 59 mm                                              |
| Number of bending cycles                      | 2000000                                            |
| Bending radius                                | 59 mm                                              |

## Sensor/actuator cable - SAC-8P- 1,5-PUR/M 8FS SH - 1404147

### Technical data

#### Cable

|                                 |                                                            |
|---------------------------------|------------------------------------------------------------|
| Traversing path                 | 10 m                                                       |
| Traversing rate                 | 3 m/s                                                      |
| Acceleration                    | 10 m/s <sup>2</sup>                                        |
| Outer sheath, material          | PUR                                                        |
| Material, filler                | PE                                                         |
| Material conductor insulation   | PP                                                         |
| Conductor material              | Bare Cu litz wires                                         |
| Insulation resistance           | 1 GΩ*km (at 20 °C)                                         |
| Conductor resistance            | 139 Ω/km (at 20 °C)                                        |
| Nominal voltage, cable          | ≤ 300 V AC                                                 |
| Test voltage, cable             | ≥ 3000 V AC (Spark test)                                   |
| Test voltage Core/Shield        | ≥ 2000 V AC (for 60 s)                                     |
| Flame resistance                | according to UL 758/1581 (horizontal)                      |
|                                 | in accordance with UL 758/1581 FT2                         |
| Halogen-free                    | in accordance with DIN VDE 0472 part 815                   |
|                                 | in accordance with DIN EN 50267-2-1                        |
| Resistance to oil               | According to DIN EN 60811-2-1, 168 h at 100°C              |
| Other resistance                | hydrolysis and microbe resistant                           |
|                                 | Resistant to salt water                                    |
|                                 | Low adhesion                                               |
|                                 | abrasion-resistant                                         |
|                                 | partly UV-resistant in accordance with DIN EN ISO 4892-2-A |
| Ambient temperature (operation) | -40 °C ... 80 °C (cable, fixed installation)               |
|                                 | -25 °C ... 80 °C (cable, flexible installation)            |


#### Environmental Product Compliance

|            |                                                                                                     |
|------------|-----------------------------------------------------------------------------------------------------|
| REACH SVHC | Lead 7439-92-1                                                                                      |
| China RoHS | Environmentally Friendly Use Period = 50 years                                                      |
|            | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

### Drawings

## Sensor/actuator cable - SAC-8P- 1,5-PUR/M 8FS SH - 1404147


Schematic diagram



Connector pin assignment of M8 socket, 8-pos., view of socket side


## Sensor/actuator cable - SAC-8P- 1,5-PUR/M 8FS SH - 1404147

Dimensional drawing



Socket M8 x 1, straight

Circuit diagram



Contact assignment of M8 socket

## Sensor/actuator cable - SAC-8P- 1,5-PUR/M 8FS SH - 1404147

Cable cross section



PUR halogen-free black [PUR]

### Classifications

eCl@ss

|               |          |
|---------------|----------|
| eCl@ss 10.0.1 | 27060311 |
| eCl@ss 4.0    | 27060300 |
| eCl@ss 4.1    | 27060300 |
| eCl@ss 5.0    | 27061800 |
| eCl@ss 5.1    | 27061800 |
| eCl@ss 6.0    | 27279200 |
| eCl@ss 7.0    | 27279218 |
| eCl@ss 8.0    | 27279218 |
| eCl@ss 9.0    | 27060311 |

## Sensor/actuator cable - SAC-8P- 1,5-PUR/M 8FS SH - 1404147

### Classifications

#### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC001855 |
| ETIM 4.0 | EC001855 |
| ETIM 5.0 | EC001855 |
| ETIM 6.0 | EC001855 |
| ETIM 7.0 | EC001855 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 31251501 |
| UNSPSC 7.0901 | 31251501 |
| UNSPSC 11     | 31251501 |
| UNSPSC 12.01  | 31251501 |
| UNSPSC 13.2   | 31251501 |
| UNSPSC 19.0   | 31251501 |
| UNSPSC 20.0   | 31251501 |
| UNSPSC 21.0   | 31251501 |

### Accessories

#### Accessories

#### Conductor marking

Insert label - PABA WH/23 - 1013779



Insert label, Strip, white, unlabeled, can be labeled with: CMS-P1-PLOTTER, mounting type: thread on, cable diameter range: 1.5 ... 35 mm, lettering field size: 23 x 4 mm, Number of individual labels: 20

Insert label - PABA YE/23 - 1013782



Insert label, Strip, yellow, unlabeled, can be labeled with: CMS-P1-PLOTTER, mounting type: thread on, cable diameter range: 1.5 ... 35 mm, lettering field size: 23 x 4 mm, Number of individual labels: 20

#### Corrugated pipe

## Sensor/actuator cable - SAC-8P- 1,5-PUR/M 8FS SH - 1404147

### Accessories

Protective hose - WP-PA HF 13,0 BK - 3240681



Polyamide protective hose, inflammability class V0, UV resistant

---

Protective hose - WP-PA HF-HB 13,0 BK - 3240839



Polyamide protective hose, inflammability class HB, UV resistant

---

### Cutting tools

Diagonal cutter - CUTFOX-S VDE - 1212207



Diagonal cutter for hard (piano wire) and soft wires, VDE 1000 V AC/1500 V DC tested

---

### Marker pen

Marker pen - B-STIFT - 1051993



Marker pen, for manual labeling of unprinted Zack strips, smear-proof and waterproof, line thickness 0.5 mm

---

### Plug for cable screw gland

Screw plug - PROT-M 8 MS-PA-CHAIN - 1430860



M8 sealing cap made of plastic with fixing band for sensor cables, for M8 sockets

---

### Screwdriver tools

## Sensor/actuator cable - SAC-8P- 1,5-PUR/M 8FS SH - 1404147

### Accessories

Tool - SAC BIT M8-D10 - 1208461



Nut for assembling M8 connectors with longitudinal knurl and a knurl diameter of 10 mm, for 4 mm hexagonal drive

---

### Stripping tool

Stripping tool - WIREFOX SAC-1 - 1212757



Stripping pliers, for halogen-free sensor/actuator cables (SAC cables), with PUR and PVC insulation, from Ø of 3.2 to 4.4 mm, any stripping length

Stripping tool - WIREFOX SAC - 1212623



Stripping pliers, for halogen-free sensor/actuator cables (SAC cables), with PUR and PVC insulation, from Ø of 4.4 to 7 mm, any stripping length

Stripping tool - WIREFOX 10 - 1212150



Stripping tool, for cables and conductors from 0.02 - 10 mm², self-adjusting, stripping length of up to 18 mm, cutting capacity of up to 10 mm² stranded/1.5 mm² solid, replaceable stripping blade

---

### Torque tool

Torque screwdriver - TSD 02 SAC - 1208487



Torque screwdriver, with preset torque of 0.2 Nm and 4 mm hexagonal drive for M8 connectors

## Sensor/actuator cable - SAC-8P- 1,5-PUR/M 8FS SH - 1404147

### Accessories

Protective hose adapter - WP-CTA POM 13,0 BK - 1422884



Protective hose adapter, for corrugated hoses with a nominal size of 13 (10 x 13), corrugated in parallel

---

Phoenix Contact 2020 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>