

## Power cable - SAC-4P- 5,0-PUR/M12FST - 1408825

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Power cable, 4-position, PUR halogen-free, black-gray RAL 7021, free cable end, on Socket straight M12, coding: T, cable length: 5 m, For direct current up to 12 A/63 V

### Your advantages

- ✓ Easy and safe: 100% electrically tested plug-in components
- ✓ High-performance: DC connectors for up to 12 A and 63 V DC
- ✓ Protection against incorrect connection using special T-coding
- ✓ Our standard: robust halogen-free PUR cable

RoHS

### Key Commercial Data

|              |                                                                                                         |
|--------------|---------------------------------------------------------------------------------------------------------|
| Packing unit | 1 pc                                                                                                    |
| GTIN         | <br>4 046356 836258 |
| GTIN         | 4046356836258                                                                                           |

### Technical data

#### Dimensions

|                 |     |
|-----------------|-----|
| Length of cable | 5 m |
|-----------------|-----|

#### Ambient conditions

|                                 |                                  |
|---------------------------------|----------------------------------|
| Ambient temperature (operation) | -25 °C ... 85 °C (Plug / socket) |
| Degree of protection            | IP65                             |
|                                 | IP67                             |

#### General

|                       |          |
|-----------------------|----------|
| Rated current at 40°C | 12 A     |
| Rated voltage         | 63 V DC  |
| Number of positions   | 4        |
| Insulation resistance | ≥ 100 MΩ |
| Coding                | T power  |

# Power cable - SAC-4P- 5,0-PUR/M12FST - 1408825

## Technical data

### General

|                              |                               |
|------------------------------|-------------------------------|
| Standards/regulations        | M12 connector IEC 61076-2-111 |
| Status display               | No                            |
| Protective circuit/component | unwired                       |
| Overvoltage category         | III                           |
| Degree of pollution          | 3                             |
| Insertion/withdrawal cycles  | > 100                         |

### Material

|                                        |                              |
|----------------------------------------|------------------------------|
| Flammability rating according to UL 94 | V0                           |
| Contact material                       | CuZn                         |
| Contact surface material               | Ni/Au                        |
| Contact carrier material               | PA                           |
| Material of grip body                  | PP                           |
| Material, knurls                       | Zinc die-cast, nickel-plated |

### Standards and Regulations

|                                        |                               |
|----------------------------------------|-------------------------------|
| Standards/specifications               | M12 connector IEC 61076-2-111 |
| Flammability rating according to UL 94 | V0                            |

### Cable

|                                                 |                            |
|-------------------------------------------------|----------------------------|
| Cable type                                      | PUR halogen-free black     |
| Cable type (abbreviation)                       | PUR                        |
| Cable abbreviation                              | Li9YV1-11Y                 |
| UL AWM style                                    | 20233 / 10493 (80°C/300 V) |
| Conductor cross section                         | 4x 1.5 mm <sup>2</sup>     |
| AWG power supply                                | 16                         |
| Conductor structure, voltage supply             | 78x 0.15 mm                |
| Core diameter including insulation              | 2.35 mm ±0.05 mm           |
| Thickness, insulation                           | ≥ 0.25 mm                  |
| Wire colors                                     | brown, white, blue, black  |
| Overall twist                                   | 4 wires, twisted           |
| Length of twist, overall twist                  | 90 mm                      |
| External sheath, color                          | black-gray RAL 7021        |
| Outer sheath thickness                          | approx. 1.3 mm             |
| External cable diameter D                       | 8.4 mm ±0.25 mm            |
| Minimum bending radius, fixed installation      | 5 x D                      |
| Minimum bending radius, flexible installation   | 10 x D                     |
| Number of bending cycles                        | 4000000                    |
| Minimum bending radius, drag chain applications | 10 x D                     |
| Traversing path                                 | 10 m                       |
| Traversing rate                                 | 3 m/s                      |
| Acceleration                                    | 10 m/s <sup>2</sup>        |

## Power cable - SAC-4P- 5,0-PUR/M12FST - 1408825

### Technical data

#### Cable

|                                 |                                                             |
|---------------------------------|-------------------------------------------------------------|
| Cable weight                    | 109 kg/km                                                   |
| Outer sheath, material          | PUR                                                         |
| Material conductor insulation   | PP                                                          |
| Conductor material              | Bare Cu litz wires                                          |
| Insulation resistance           | $\geq 1 \text{ G}\Omega \cdot \text{km}$ (at 20 °C)         |
| Conductor resistance            | $\leq 13 \text{ }\Omega/\text{km}$ (at 20 °C)               |
| Nominal voltage, cable          | $\leq 300 \text{ V AC}$                                     |
| Test voltage, cable             | $\geq 3000 \text{ V AC}$ (Spark test)                       |
| Flame resistance                | According to UL 758/1581 (Cable Flame)                      |
|                                 | according to UL 758/1581 FT1                                |
|                                 | According to DIN EN 60332-1-2                               |
| Halogen-free                    | in accordance with DIN VDE 0472 part 815                    |
|                                 | in accordance with DIN EN 50267-2-1                         |
| Resistance to oil               | According to DIN EN 60811-2-1, 168 h at 100°C               |
|                                 | According to UL 758, 168 h at 60°C                          |
| Other resistance                | Hydrolysis and microbe resistant as per VDE 0282 section 10 |
|                                 | Low adhesion                                                |
|                                 | abrasion-resistant                                          |
|                                 | Resistant to salt water                                     |
| Ambient temperature (operation) | -50 °C ... 80 °C (cable, fixed installation)                |
|                                 | -30 °C ... 80 °C (cable, flexible installation)             |


#### Environmental Product Compliance

|            |                                                                                                     |
|------------|-----------------------------------------------------------------------------------------------------|
| REACH SVHC | Lead 7439-92-1                                                                                      |
| China RoHS | Environmentally Friendly Use Period = 50 years                                                      |
|            | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

### Drawings


## Power cable - SAC-4P- 5,0-PUR/M12FST - 1408825

Diagram



Current carrying capacity


Dimensional drawing



M12 x 1 socket, straight

## Power cable - SAC-4P- 5,0-PUR/M12FST - 1408825


Circuit diagram



Contact assignment of the M12 socket

## Power cable - SAC-4P- 5,0-PUR/M12FST - 1408825


Schematic diagram



Pin assignment of M12 socket, 4-pos., T-coded, socket side view

## Power cable - SAC-4P- 5,0-PUR/M12FST - 1408825

Cable cross section



PUR halogen-free black [PUR]

### Classifications

eCl@ss

|               |          |
|---------------|----------|
| eCl@ss 10.0.1 | 27060311 |
| eCl@ss 4.0    | 27140800 |
| eCl@ss 4.1    | 27140800 |
| eCl@ss 5.0    | 27143400 |
| eCl@ss 5.1    | 27143400 |
| eCl@ss 6.0    | 27279200 |
| eCl@ss 7.0    | 27279218 |
| eCl@ss 8.0    | 27279218 |
| eCl@ss 9.0    | 27060311 |

## Power cable - SAC-4P- 5,0-PUR/M12FST - 1408825

### Classifications

#### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC002061 |
| ETIM 4.0 | EC001855 |
| ETIM 5.0 | EC001855 |
| ETIM 6.0 | EC001855 |
| ETIM 7.0 | EC001855 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 31251501 |
| UNSPSC 7.0901 | 31251501 |
| UNSPSC 11     | 31251501 |
| UNSPSC 12.01  | 31251501 |
| UNSPSC 13.2   | 31251501 |
| UNSPSC 19.0   | 31251501 |
| UNSPSC 20.0   | 31251501 |
| UNSPSC 21.0   | 31251501 |

### Approvals

#### Approvals

#### Approvals

UL Listed / cUL Listed / cULus Listed

#### Ex Approvals

#### Approval details

|                    |                                                                                     |                                                                                                                                                       |         |
|--------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|---------|
| UL Listed          |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | E468743 |
|                    |                                                                                     |                                                                                                                                                       |         |
| Nominal voltage UN | 63 V                                                                                |                                                                                                                                                       |         |
| Nominal current IN | 12 A                                                                                |                                                                                                                                                       |         |
| mm²/AWG/kcmil      | 16                                                                                  |                                                                                                                                                       |         |

|                    |                                                                                     |                                                                                                                                                       |         |
|--------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|---------|
| cUL Listed         |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | E468743 |
|                    |                                                                                     |                                                                                                                                                       |         |
| Nominal voltage UN | 63 V                                                                                |                                                                                                                                                       |         |



## Power cable - SAC-4P- 5,0-PUR/M12FST - 1408825

### Approvals

|                                |      |
|--------------------------------|------|
|                                |      |
| Nominal current I <sub>N</sub> | 12 A |
| mm <sup>2</sup> /AWG/kcmil     | 16   |

cULus Listed



### Accessories

#### Accessories

#### Screwdriver tools

Tool - SAC BIT M12-D16 - 1200305



Nut for assembling sensor/actuator cables with M12 connector and M12 connectors for assembly, knurl diameter: 16 mm, for 4 mm hexagonal drive

Phoenix Contact 2020 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>