

## Power cable - SAC-4P-M12MSS/ 1,5-PUR PE SH - 1424104

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Power cable, 4-position, PUR halogen-free, orange RAL 2003, shielded (Advanced Shielding Technology), Plug straight M12, coding: S, on free cable end, cable length: 1.5 m, for AC current up to 12 A/690 V

### Your advantages

- ✓ Easy and safe: 100% electrically tested plug-in components
- ✓ High-performance: AC connectors for up to 12 A and 690 V AC
- ✓ Protection against incorrect connection using special S-coding
- ✓ Our standard: robust halogen-free PUR cable
- ✓ Shield power reliably – 360° shielding to reduce electromagnetic loads

RoHS

### Key Commercial Data

|              |                                                                                                         |
|--------------|---------------------------------------------------------------------------------------------------------|
| Packing unit | 1 pc                                                                                                    |
| GTIN         | <br>4 046356 693097 |
| GTIN         | 4046356693097                                                                                           |

### Technical data

#### Dimensions

|                 |       |
|-----------------|-------|
| Length of cable | 1.5 m |
|-----------------|-------|

#### Ambient conditions

|                                 |                                  |
|---------------------------------|----------------------------------|
| Ambient temperature (operation) | -25 °C ... 85 °C (Plug / socket) |
| Degree of protection            | IP65                             |
|                                 | IP67                             |

#### General

|                       |          |
|-----------------------|----------|
| Rated current at 40°C | 12 A     |
| Rated voltage         | 690 V AC |
| Number of positions   | 4        |
| Color handle area     | black    |
| Insulation resistance | ≥ 100 MΩ |

# Power cable - SAC-4P-M12MSS/ 1,5-PUR PE SH - 1424104

## Technical data

### General

|                              |                               |
|------------------------------|-------------------------------|
| Coding                       | S power                       |
| Standards/regulations        | M12 connector IEC 61076-2-111 |
| Status display               | No                            |
| Protective circuit/component | unwired                       |
| Overvoltage category         | III                           |
| Degree of pollution          | 3                             |
| Insertion/withdrawal cycles  | > 100                         |
| Torque                       | 0.4 Nm (M12 connector)        |

### Material

|                                        |                              |
|----------------------------------------|------------------------------|
| Flammability rating according to UL 94 | V0                           |
| Contact material                       | CuZn                         |
| Contact surface material               | Ni/Au                        |
| Contact carrier material               | PA                           |
| Material of grip body                  | PP                           |
| Material, knurls                       | Zinc die-cast, nickel-plated |

### Standards and Regulations

|                                        |                               |
|----------------------------------------|-------------------------------|
| Standards/specifications               | M12 connector IEC 61076-2-111 |
| Flammability rating according to UL 94 | V0                            |

### Cable

|                                                 |                                                    |
|-------------------------------------------------|----------------------------------------------------|
| Cable type                                      | PUR halogen-free orange shielded                   |
| Cable type (abbreviation)                       | PUR                                                |
| Cable abbreviation                              | 9YSLC11Y-JZ                                        |
| UL AWM style                                    | 20234 / 10492 (80°C/1000 V)                        |
| Conductor cross section                         | 4x 1.5 mm <sup>2</sup>                             |
| AWG power supply                                | 16                                                 |
| Conductor structure, voltage supply             | 78x 0.15 mm                                        |
| Core diameter including insulation              | ≤ 2.5 mm                                           |
| Thickness, insulation                           | 0.4 mm                                             |
| Wire colors                                     | Black 1, black 2, black 3, green/yellow            |
| Overall twist                                   | 4 wires optimally twisted                          |
| Shielding                                       | Tinned copper-braided shield, approx. 85% covering |
| External sheath, color                          | orange RAL 2003                                    |
| Outer sheath thickness                          | 1.2 mm                                             |
| External cable diameter D                       | 9.7 mm ±0.3 mm                                     |
| Minimum bending radius, fixed installation      | 5 x D                                              |
| Minimum bending radius, flexible installation   | 7.5 x D                                            |
| Number of bending cycles                        | 4000000                                            |
| Minimum bending radius, drag chain applications | 10 x D                                             |
| Traversing path                                 | 10 m                                               |

## Power cable - SAC-4P-M12MSS/ 1,5-PUR PE SH - 1424104

### Technical data

#### Cable

|                                 |                                                 |
|---------------------------------|-------------------------------------------------|
| Traversing rate                 | 3 m/s                                           |
| Acceleration                    | 10 m/s <sup>2</sup>                             |
| Torsion force                   | ± 25 °/m                                        |
| Outer sheath, material          | PUR                                             |
| Material conductor insulation   | PP                                              |
| Conductor material              | Bare Cu litz wires                              |
| Insulation resistance           | ≥ 10 MΩ*km (at 20 °C)                           |
| Conductor resistance            | ≤ 13.3 Ω/km (at 20 °C)                          |
| Nominal voltage, cable          | 1000 V AC                                       |
| Test voltage, cable             | 4260 V AC (5 min.)                              |
| Flame resistance                | according to EN 60332-1-2                       |
|                                 | in acc. to UL 1581 VW1                          |
|                                 | According to CSA C 22.2 No. 210-05 FT1          |
| Halogen-free                    | according to VDE 0282-13 Appendix C             |
| Resistance to oil               | in accordance with DIN EN 60811-2-1             |
|                                 | According to DIN EN 50363-10-2                  |
| Other resistance                | UV resistant                                    |
|                                 | Low adhesion                                    |
| Ambient temperature (operation) | -40 °C ... 90 °C (cable, fixed installation)    |
|                                 | -30 °C ... 90 °C (cable, flexible installation) |


#### Environmental Product Compliance

|            |                                                                                                     |
|------------|-----------------------------------------------------------------------------------------------------|
| REACH SVHC | Lead 7439-92-1                                                                                      |
| China RoHS | Environmentally Friendly Use Period = 50 years                                                      |
|            | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

### Drawings

## Power cable - SAC-4P-M12MSS/ 1,5-PUR PE SH - 1424104


Schematic diagram



M12 plug pin assignment, 4-pos., S-coded, plug side view


## Power cable - SAC-4P-M12MSS/ 1,5-PUR PE SH - 1424104

Dimensional drawing



Plug, M12 x 1, straight, shielded


Circuit diagram



Contact assignment of the M12 plug

## Power cable - SAC-4P-M12MSS/ 1,5-PUR PE SH - 1424104

Cable cross section



PUR halogen-free orange shielded [PUR]

### Classifications

eCl@ss

|               |          |
|---------------|----------|
| eCl@ss 10.0.1 | 27060311 |
| eCl@ss 4.0    | 27140800 |
| eCl@ss 4.1    | 27140800 |
| eCl@ss 5.0    | 27143400 |
| eCl@ss 5.1    | 27143400 |
| eCl@ss 6.0    | 27279200 |
| eCl@ss 7.0    | 27279218 |
| eCl@ss 8.0    | 27279218 |
| eCl@ss 9.0    | 27060311 |

# Power cable - SAC-4P-M12MSS/ 1,5-PUR PE SH - 1424104

## Classifications

### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC002061 |
| ETIM 4.0 | EC001855 |
| ETIM 5.0 | EC001855 |
| ETIM 6.0 | EC001855 |
| ETIM 7.0 | EC001855 |

### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 31251501 |
| UNSPSC 7.0901 | 31251501 |
| UNSPSC 11     | 31251501 |
| UNSPSC 12.01  | 31251501 |
| UNSPSC 13.2   | 31251501 |
| UNSPSC 19.0   | 31251501 |
| UNSPSC 20.0   | 31251501 |
| UNSPSC 21.0   | 31251501 |

## Approvals

### Approvals

#### Approvals

UL Listed / cUL Listed / cULus Listed

#### Ex Approvals

### Approval details

|                    |                                                                                     |                                                                                                                                                       |               |
|--------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|
| UL Listed          |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | FILE E 468743 |
| Nominal voltage UN | 600 V                                                                               |                                                                                                                                                       |               |
| Nominal current IN | 12 A                                                                                |                                                                                                                                                       |               |
| mm²/AWG/kcmil      | 16                                                                                  |                                                                                                                                                       |               |

|                    |                                                                                     |                                                                                                                                                       |               |
|--------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|
| cUL Listed         |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | FILE E 468743 |
| Nominal voltage UN | 600 V                                                                               |                                                                                                                                                       |               |

## Power cable - SAC-4P-M12MSS/ 1,5-PUR PE SH - 1424104

### Approvals

|                                |      |
|--------------------------------|------|
|                                |      |
| Nominal current I <sub>N</sub> | 12 A |
| mm <sup>2</sup> /AWG/kcmil     | 16   |

cULus Listed



### Accessories

#### Accessories

#### Protective cap

Sealing cap - PROT-M12 FS - 1560251



M12 sealing cap for unoccupied M12 plugs of the sensor/actuator cable, flush-type plugs and I/O devices in the field

---

#### Screwdriver tools

Tool - SAC BIT M12-D16 - 1200305



Nut for assembling sensor/actuator cables with M12 connector and M12 connectors for assembly, knurl diameter: 16 mm, for 4 mm hexagonal drive

---

Phoenix Contact 2020 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>