

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Snap-in locking non-vented enclosure of the ECS Family. IP66/67/69 rated when mated with associated faceplate. Color: Black (9005), Width: 170 mm, Height: 176 mm, Depth: 64 mm

### Your advantages

- ☑ Part of the EnviroCase System
- Suitable for outdoor/indoor applications
- ☑ IP66/IP67 rated with faceplate secured to the base
- Wall, panel, or pole mounting options
- ▼ Tooless assembly



## **Key Commercial Data**

Packing unit	5 pc
Minimum order quantity	5 pc
GTIN	4 055626 381343
GTIN	4055626381343

### Technical data

### Item properties

Туре	ECS-B-122X169-L-UV1-NV
Order No.	2230001
Housing type	outdoor housings
Туре	Snap-in locking
Impact strength	IK08
Mounting type	Wall or panel mount. Pole mount with accessory.
Type of locking	Snap-in locking

#### Measurements

Width [ w ]	170 mm
Height [ h ]	176 mm




## Technical data


## Measurements

Depth [ d ]	64 mm	
Material specifications		
Color (RAL)	black (9005)	
Flammability rating according to UL 94	V0	
Housing material	PC (polycarbonate)	
Ambient conditions		
Ambient temperature (operation)	-40 °C 100 °C	
PCB data		
PCB thickness	1.59 mm 2.36 mm	
Packaging information		
Pieces per package	5	
Denomination packing units	Pcs.	
Standards and regulations		
Flammability rating according to UL 94	V0	
Environmental Product Compliance		
China RoHS	Environmentally friendly use period: unlimited = EFUP-e	
	No hazardous substances above threshold values	

## Drawings







## Classifications

## eCl@ss

eCl@ss 10.0.1	27182702
eCl@ss 4.0	27180401
eCl@ss 4.1	27180401
eCl@ss 5.0	27180505
eCl@ss 5.1	27180505
eCl@ss 6.0	27180800
eCl@ss 7.0	27182702
eCl@ss 8.0	27182702
eCl@ss 9.0	27182702



## Classifications

### **ETIM**

ETIM 3.0	EC001031
ETIM 4.0	EC001031
ETIM 5.0	EC000058
ETIM 6.0	EC001031
ETIM 7.0	EC001031

## **UNSPSC**

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501
UNSPSC 18.0	31261501
UNSPSC 19.0	31261501
UNSPSC 20.0	31261501
UNSPSC 21.0	31261501

#### Accessories

Accessories

Screwdriver tools


Screwdriver - SF-TXH 20X100 - 1200151



Screwdriver, Torx<sup>®</sup> with bore hole, TX 20 x 100, two-component handle

### Additional products

Front plate - ECS-P-122X169-L-UV1-B - 2230004







### Accessories

Front plate - ECS-P-122X169-L-UV1-1M12 - 2230005

Snap-in locking one female M12 faceplate of the ECS Family. IP66/67/69 rated when mated with associated enclosure. Color: Black (9005), Width: 196 mm, Height: 34 mm, Depth: 62



Front plate - ECS-P-122X169-L-UV1-2M12 - 2230006

Snap-in locking two female M12 faceplate of the ECS Family. IP66/67/69 rated when mated with associated enclosure. Color: Black (9005), Width: 196 mm, Height: 34 mm, Depth: 62 mm



Front plate - ECS-P-122X169-L-UV1-CG - 2230007

Snap-in locking cable gland faceplate of the ECS Family. IP66/67/69 rated when mated with associated enclosure. Color: Black (9005), Width: 196 mm, Height: 34 mm, Depth: 62 mm



Safety clip - ECS-BL - 2230012



Clip to prevent PCB from dropping from base when faceplate is removed.

Mounting brackets - ECS-PM - 2230013



Mounting set for mast mounting



Phoenix Contact 2020 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany Tel. +49 5235 300

Fax +49 5235 3 41200

http://www.phoenixcontact.com