

## Wiring bridge - MPB 18/1-57 - 2809238

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Wiring bridge for modules with connecting pitch 17.5 mm, 1-phase, 57-pos.

### Your advantages

- ✓ In combination with other devices in the distribution board, such as residual current devices and miniature circuit breakers
- ✓ Practical wiring of all common applications
- ✓ End covers are used to terminate and insulate individually cut bridges
- ✓ For combinations of lightning and surge arresters

RoHS

### Key Commercial Data

|              |                                                                                                         |
|--------------|---------------------------------------------------------------------------------------------------------|
| Packing unit | 1 pc                                                                                                    |
| GTIN         | <br>4 017918 076306 |
| GTIN         | 4017918076306                                                                                           |

### Technical data

#### General

|                       |             |
|-----------------------|-------------|
| Nominal current $I_N$ | 100 A       |
| Number of positions   | 57          |
| Color                 | gray        |
| Housing material      | Plastic     |
| Type                  | Comb bridge |

#### Environmental Product Compliance

|            |                                                         |
|------------|---------------------------------------------------------|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

## Wiring bridge - MPB 18/1-57 - 2809238

### Classifications

#### eCl@ss

|               |          |
|---------------|----------|
| eCl@ss 10.0.1 | 27371306 |
| eCl@ss 4.0    | 27140200 |
| eCl@ss 4.1    | 27140200 |
| eCl@ss 5.0    | 27140200 |
| eCl@ss 5.1    | 27140200 |
| eCl@ss 6.0    | 27371300 |
| eCl@ss 7.0    | 27371306 |
| eCl@ss 8.0    | 27371306 |
| eCl@ss 9.0    | 27371306 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000489 |
| ETIM 3.0 | EC000489 |
| ETIM 4.0 | EC000489 |
| ETIM 5.0 | EC000215 |
| ETIM 6.0 | EC000215 |
| ETIM 7.0 | EC000215 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30212010 |
| UNSPSC 7.0901 | 39121610 |
| UNSPSC 11     | 39121610 |
| UNSPSC 12.01  | 39121610 |
| UNSPSC 13.2   | 39121620 |
| UNSPSC 18.0   | 39121620 |
| UNSPSC 19.0   | 39121620 |
| UNSPSC 20.0   | 39121620 |
| UNSPSC 21.0   | 39121620 |

### Approvals

#### Approvals

---

Approvals

EAC

---

Ex Approvals

---

#### Approval details

## Wiring bridge - MPB 18/1-57 - 2809238

### Approvals

EAC



RU C-  
DE.A\*30.B.01742

Phoenix Contact 2020 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>