

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Custom circuit module, consisting of housing, MKDS 3 connection terminal blocks and PCB

Your advantages

- ☑ Practical and easy-to-wire conductor connections
- High degree of flexibility due to the wide choice of versions
- Uniform and appropriate housing technology
- ☑ User-friendly and safe mounting on DIN rails according to EN 60715
- Space-saving accommodation of electronic components in finely graded module versions available with 10 to 150 mm pitch
- ☑ Inflammability class V0 insulation material (according to UL 94)
- Shock and contamination-proof accommodation of electronic components
- Universal PCBs for all pitches



Key Commercial Data

Packing unit	5 pc
GTIN	4 017918 082222
GTIN	4017918082222

Technical data

General

Housing type	Component housing
Housing material	Polycarbonate fiber reinforced

Ambient conditions

Ambient temperature (operation)	-40 °C 125 °C

Dimensions

Length	75 mm
Height	47.5 mm



Technical data

Dimensions

Width	90 mm
Pitch	5 mm
Depth	75 mm

Technical data

Power dissipation without gap	4.1 W
Power dissipation with 20 mm gap	4.6 W
Number of positions	34

Standards and Regulations


Flammability rating according to UL 94	V0

Environmental Product Compliance

REACh SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Drawings


Dimensional drawing



^{1 =} Top edge of the PCB B = Housing width



Dimensional drawing



Pitch 5 mm

- a = Area for mounting components, 38 mm in the hood
- b = Area for mounting components, 45 mm in the housing

Classifications

eCl@ss

eCl@ss 10.0.1	27182702
eCl@ss 4.0	27180400
eCl@ss 4.1	27180400
eCl@ss 5.0	27180500
eCl@ss 5.1	27180500
eCl@ss 6.0	27180800
eCl@ss 7.0	27182702
eCl@ss 8.0	27182702
eCl@ss 9.0	27182702

ETIM

ETIM 2.0	EC001031
ETIM 3.0	EC001031
ETIM 4.0	EC001031
ETIM 5.0	EC001031
ETIM 6.0	EC001031
ETIM 7.0	EC001031



Classifications

UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501
UNSPSC 18.0	31261501
UNSPSC 19.0	31261501
UNSPSC 20.0	31261501
UNSPSC 21.0	31261501

UNSPSC 21.0 Approvals Approvals EAC Ex Approvals EAC EAC EAC B.01742

Accessories

Accessories

Component housing center part

Spacer plate - EMG 90-ZE - 2941824

Intermediate element, to enlarge the assembly space

Device marking



Accessories

Marking material - EMG-GKS 22 - 2941594



Device marking label, width: 22 mm, area: 22 x 8 mm, e.g. for EML(20x8) R adhesive marking material

Filler plug

Electronic housing - EMG-KA - 2941510



Terminal block/screw cover, set consisting of 50 strips each for terminal blocks and screw openings, 1 strip covers 12 terminal points.

Marking material - EMG-GKS 12 - 2947035



Device marking label, width: 12 mm, area: 12 x 8 mm, e.g. for EML(10x7) R adhesive marking material

Necessary add-on products

Electronic housing - EMG 90-H 7,5MM KLAR - 2945396



Covering hood, for the contact and dust-protected encapsulation of the components, in transparent design. Height: 7.5 mm

Covering hood - EMG 90-H 15MM KLAR - 2945406



Covering hood, for the contact and dust-protected encapsulation of the components, in transparent design. Height: 15 mm, width: 90 mm



Accessories

Electronic housing - EMG 90-H 52MM GN - 2944300



Covering hood, for the contact and dust-protected encapsulation of the components, in green design. Height: 52 mm, width: 90 mm

Phoenix Contact 2020 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany

Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com