

## Shield connection clamp - SKS 20-SNS35 - 3062809

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Shield connection terminal block, for applying the shield to busbars

### Your advantages

- ✓ The SKS ... spring shield connection clamps are available for cable and conductor diameters of 3 to 20 mm
- ✓ According to the requirements of the directive and standards for electrical equipment in potentially explosive areas, as components, shield connections are not eligible for certification. As such, shield connection clamps can be used in the Ex area even without appropriate approval and marking.
- ✓ Three different mounting types supported: on NS 35 DIN rails, on busbars or directly on conductive mounting plates

RoHS

### Key Commercial Data

|              |                                                                                                         |
|--------------|---------------------------------------------------------------------------------------------------------|
| Packing unit | 10 pc                                                                                                   |
| GTIN         | <br>4 046356 639378 |
| GTIN         | 4046356639378                                                                                           |

### Technical data

#### General

|                       |                |
|-----------------------|----------------|
| Number of levels      | 1              |
| Number of connections | 1              |
| Cable diameter        | 5 mm ... 20 mm |
| Color                 | silver         |
| Open side panel       | No             |

#### Dimensions

|                  |         |
|------------------|---------|
| Length           | 53.2 mm |
| Width            | 24.7 mm |
| Height           | 65.3 mm |
| Height NS 35/7,5 | 48 mm   |

#### Connection data

# Shield connection clamp - SKS 20-SNS35 - 3062809

## Technical data

### Connection data

|                                       |                        |
|---------------------------------------|------------------------|
| Connection method                     | Spring-cage connection |
| Conductor cross section solid min.    | 10 mm <sup>2</sup>     |
| Conductor cross section solid max.    | 20 mm <sup>2</sup>     |
| Conductor cross section flexible min. | 10 mm <sup>2</sup>     |
| Conductor cross section flexible max. | 20 mm <sup>2</sup>     |
| Conductor cross section AWG min.      | 8                      |
| Conductor cross section AWG max.      | 4                      |

### Environmental Product Compliance

|            |                                                         |
|------------|---------------------------------------------------------|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

## Classifications

### eCl@ss

|               |          |
|---------------|----------|
| eCl@ss 10.0.1 | 27141150 |
| eCl@ss 4.0    | 27141100 |
| eCl@ss 4.1    | 27141100 |
| eCl@ss 5.0    | 27141100 |
| eCl@ss 5.1    | 27141100 |
| eCl@ss 6.0    | 27141100 |
| eCl@ss 7.0    | 27141150 |
| eCl@ss 8.0    | 27141150 |
| eCl@ss 9.0    | 27141150 |

### ETIM

|          |          |
|----------|----------|
| ETIM 4.0 | EC002020 |
| ETIM 5.0 | EC002020 |
| ETIM 6.0 | EC002020 |
| ETIM 7.0 | EC002020 |

### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211811 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11     | 39121410 |
| UNSPSC 12.01  | 39121410 |
| UNSPSC 13.2   | 39121432 |
| UNSPSC 18.0   | 39121432 |
| UNSPSC 19.0   | 39121432 |
| UNSPSC 20.0   | 39121432 |
| UNSPSC 21.0   | 39121432 |

Phoenix Contact 2020 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>