

MS-328-6



MS-328-6

Power Reed Sensor Flatpack

Electrical Characteristics

@ 25 °C

Contact form		A
Contact rating max.	W / VA	50
Switching voltage max.	VDC	200
	VAC	250
Switching current max.	A	1.5
Carry current max.	A	2
Breakdown voltage min.	VDC	400
Total resistance max. (initial)	mΩ	150
Insulation resistance min.	Ω	10 ¹⁰

Features

- Sensor with Power Reed Switch
- Adjustable switching point
- Various sensitivity ranges available
- Customized types available

Magnetical Characteristics (of unmodified Reed Switch)

@ 25 °C

Pull in range available	AT	25 - 40
Drop out min.	AT	5
Test coil	TC -	020
Test equipment tolerance	± AT	2

Operating Characteristics (of unmodified Reed Switch)

@ 25 °C

Switching frequency max.	Hz	300
Resonant frequency typ.	Hz	2600
Operate time max. (incl. bounce)	ms	1
Release time max.	ms	0.4

Approvals



Environmental Characteristics

Operating temperature	°C	-20 to + 85
Vibration (50-2000 Hz)	g	20
Shock (1/2 sin 11 ms)	g	50

Ordering Information

Packing Unit	25	pcs
Weight per piece	10.8	g
Weight per package	280	g

Standard AT Ranges

- 4 = 25 to 30 AT
- 5 = 30 to 35 AT
- 6 = 35 to 40 AT


Ordering Example

MS-328-6-4 describes MS-328-6 with 25 to 30 AT.

Remarks

When mounted onto ferromagnetic parts switching distance of MS-328-6 may reduce.
Electromagnetical influences and magnetic fields may change the switching behaviour of the sensor.

Dimensions in mm



Material Information

	Material	Colour
Housing	PA-GF	black
Cable	UL 1007/1569, AWG 20, 4 mm stripped and tinned	black
Potting compound	Epoxy	black