

COMMON MODE CHOKE FOR ADSL AND VDSL



-  Common Mode Chokes for use in ADSL and VDSL applications
-  Ideal for high frequency DSL applications

Electrical Specifications @ 25°C — Operating Temperature -40°C to 85°C



RoHS-5 Compliant Part Number	RoHS-6 Compliant Part Number	Turns Ratio	Inductance (each winding) (mH)	Isolation Voltage (Vrms)
BX8213	BX8213NL	1:1	9.0	500

NOTE: Parts are shipped in trays unless Tape & Reel packaging is specified by adding the suffix “T” to the part number (i.e. BX8213T).


Mechanical

Schematic

BX8213 / BX8213NL




SUGGESTED PAD LAYOUT



Weight 2.0 grams
Tape & Reel 250/reel
Tube 40/tube

Dimensions: Inches
mm
 Unless otherwise specified,
 all tolerances are $\pm .010$
 $0,25$



For More Information:

Pulse Worldwide Headquarters

12220 World Trade Dr.
San Diego, CA 92128
U.S.A.

www.pulseeng.com

TEL: 858 674 8100

FAX: 858 674 8262

Pulse Europe

Einsteinstrasse 1
D-71083 Herrenberg
Germany

Tel: 49 7032 7806 116

Fax: 49 7032 7806 135

Pulse China Headquarters

No. 1
Industrial District
Changan, Dongguan
China

Tel: 86 769 85538070

Fax: 86 769 85538870

Pulse North China

Room 1503
XinYin Building
No. 888 YiShan Rd.
Shanghai 200233
China

Tel: 86 21 54643211/2

Fax: 86 21 54643210

Pulse South Asia

150 Kampong Ampat
#07-01/02
KA Centre
Singapore 368324

Tel: 65 6287 8998

Fax: 65 6280 0080

Pulse North Asia

No. 26
Kao Ching Rd.
Yang Mei Chen
Taoyuan Hsien
Taiwan, R. O. C.

Tel: 886 3 4641811

Fax: 886 3 4641911

Performance warranty of products offered on this data sheet is limited to the parameters specified. Data is subject to change without notice. Other brand and product names mentioned herein may be trademarks or registered trademarks of their respective owners.

© Copyright, 2006. Pulse Engineering, Inc. All rights reserved.

www.pulseeng.com

B830.A (8/06)