



All dimensions are in mm; tolerances according to ISO 2768 m-H

**Application**

Series For DIN 41626 inserts  
 Replacement sleeve 11W102-001

**Material and plating**

**Connector parts**

	<b>Material</b>	<b>Plating</b>
Grip sleeve	Aluminium	N/A
Replacement sleeve	Beryllium copper	Nickel, 2.5-5 µm
Coupling nut	Brass	Nickel, 2.5-5 µm
Ejector	Stainless steel	N/A

**Weight**

Weight 38 g/pce

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
Rong Fang	04/07/05	Sa. Krautenbacher	13.03.14	b00	14-0352	T. Krojer	13.03.14
Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany <a href="http://www.rosenberger.de">www.rosenberger.de</a>					Tel.: +49 8684 18-0 Fax: +49 8684 18-499 email: <a href="mailto:info@rosenberger.de">info@rosenberger.de</a>		Page 1 / 1