REVISION S ANY REV MADE TO THIS PRINT MUST HAVE AN UPDATED MKT PRINT 1. ITEMS -1, -2, & -3 NOT AVAILABLE AS STANDARD, CUTOM FOR **VARIATION OF VITA 42 XMC STANDARDS.** 2. © REPRESENTS A CRITICAL DIMENSION. 3. MAXIMUM BURR ALLOWANCE: .0015[0.038] **DO NOT** 4. MAXIMUM CUT FLASH: .010[0.25]
5. MINIMUM PUSHOUT FORCE: .5 LB [2.22N]
6. MAXIMUM ALLOWABLE BOW; TOP/BOTTOM: .006[0.15], SIDE/SIDE: .003[0.08].
7. PARTS TO BE PACKAGED IN TAPE & REEL. FOR QTY'S LESS THAN 125 PCS, NO TRAILER SCALE FROM THIS PRINT OR LEADER WILL BE SUPPLIED. 8. LEAD FREE SOLDER BALLS 1.050 [26.67] REF .980 [24.89] REF .900 [22.86] (19 POS - 1) X .0500[1.270] .020±.010[0.51±0.25] .420 [10.67] С .105 [2.67] .350 [8.89] .008±.002 [0.20±0.05] .250 [6.35] REF DETAIL 'G' **SCALE 10: 1** SOLDER BALL REMOVED FOR CLARITY $\emptyset.460[11.68]$ 6 — 2° MAX SWAY ((EITHER DIRECTION) **REF** .295±.020[7.49±0.51] .900 [22.86] [TOL NON-ACCUM] (1) .016[0.41] "A" REF (TYP) .100 [2.54] .155 [3.94] .084[2.13] REF REF .339 [8.61 .363 [9.22] .278 7.05 .0060[0.152] .073 [1.85] ·'G' SECTION "A"-"A"

ITEM NO.	PART NUMBER	QUANTITY	MATERIAL
1	ASP-144052-01-B	1.0000	UL 94 VO, COLOR: BLACK
2	ASP-136535-01-B	1.0000	UL 94 VO, COLOR: BLACK
3	ASP-104554-02-P-H	114.00	BRASS ALLOY 260, 3/4 HARD
4	CT-ASP1134MS	.00571	CONDUCTIVE POLYMER
5	SDB-030-9653	114.00	96.5% TIN / 3% SILVER/ 0.5% COPPER
6	K-850-650	1.0000	POLYIMIDE FILM

UNLESS OTHERWISE SPECIFIED. DIMENSIONS ARE IN INCHES. TOLERANCES ARE:

DECIMALS ANGLES .XX: ±.01

.XXX: ±.005 .XXXX: ±.0020

PROPRIETARY NOTE THIS DOCUMENT CONTAINS INFORMATION CONFIDENTIAL AND PROPRIETARY TO SAMTEC, INC. AND SHALL NOT BE REPRODUCED OR TRANSFERRED TO OTHER DOCUMENTS OR DISCLOSED TO OTHERS OR USED FOR ANY PURPOSE OTHER THAN THAT WHICH IT WAS OBTAINED WITHOUT THE EXPRESSED WRITTEN CONSENT OF SAMTEC, INC

DO NOT SCALE DRAWING SHEET SCALE: 3:1 PLATING: .000030 GOLD OVER .000050 NICKEL

520 PARK EAST BLVD, NEW ALBANY, IN 47150 PHONE: 812-944-6733 FAX: 812-948-5047 e-Mail info@SAMTEC.com code 55322

VITA 42 (LEAD FREE) SOCKET ASSEMBLY

DWG. NO. ASP-103614-04

c:\enterprisevault\DWG\MISC\MKTG\ASP-103614-04-MKT.SLDDRW

BY: TAMMY W 09/11/06

SHEET 1 OF 2

REVISION S RECOMMENDED BOARD LAYOUT .900 [22.86] 01 .250 [6.35] SEE DETAIL 'B' .025 [0.64] .0100 [.254] TRACE $\emptyset.0310 \ [\emptyset.787]$ FREE OD SOLDER MASK


DETAIL 'B'


 \emptyset .0250 [\emptyset .635] PAD


 $\emptyset.0100 \ [\ \emptyset.305]$

VIA (PLATED)

RECOMMENDED STENCIL LAYOUT STENCIL TO BE .0060[0.152] THICK







PROPRIETARY NOTE THIS DOCUMENT CONTAINS INFORMATION CONFIDENTIAL AND PROPRIETARY TO SAMTEC, INC. AND SHALL NOT BE REPRODUCED OR TRANSFERRED TO OTHER DOCUMENTS OR DISCLOSED TO OTHERS OR USED FOR ANY PURPOSE OTHER THAN THAT WHICH IT WAS OBTAINED WITHOUT THE EXPRESSED WRITTEN CONSENT OF SAMTEC, INC.

520 PARK EAST BLVD, NEW ALBANY, IN 47150 PHONE: 812-944-6733 FAX: 812-948-5047 e-Mail info@SAMTEC.com code 55322

SHEET SCALE: 3:1

VITA 42 (LEAD FREE) SOCKET ASSEMBLY

ASP-103614-04

c:\enterprisevault\DWG\MISC\MKTG\ASP-103614-04-MRYS:DDRWAMMY W 09/11/06

SHEET 2 OF 2