





ICA-640-SGG



ICA-320-STT

DIP SOCKETS ICA SERIES


Mates with:
AP, APS, APO,
APA, APE

ICA

ROW SPACING &
NO. OF CONTACTSSTYLE
OPTIONPLATING
OPTIONOPTION
(Leave Blank for
Standard Version)

Specify from chart below

- Side & end stackable
- Great for auto insertion
- Open body design



*-322 has no cross bar on one end.

	Row Space	No. of Contacts
-308	.300 (7,62)	08
-314		14
-316		16
-318		18
-320		20
-322 *		22
-324		24
-328	.400 (10,16)	28
-422		22
-624	.600 (15,24)	24
-628		28
-632		32
-640		40
-648		48

GG

= 30μ" (0,76μm)
Gold contact,
10μ" (0,25μm)
Gold Shell

GT

= 30μ" (0,76μm)
Gold contact,
Tin Shell

TT

=Tin contact
and shell
(-S, -ZS, -W,
-ZW only)

ST

= 10μ" (0,25μm)
Gold contact,
Tin shell (Styles -S
& -ZS only)

-2
= .360 (9,14)
TailWire-Wrap
Option

Requires Style
-W or -ZW
Specify desired
suffix for shorter
Wire-Wrap tail.

-3
= .260 (6,60)
Tail-L
= Locking
SocketRequires Style
-S or -ZS

Requires GT
Plating Option

ALSO AVAILABLE

RoHS compliant
options.
Call Samtec.
DIP Adaptors.
Request ICA
Fact Sheet.



SPECIFICATIONS

For complete specifications
see www.samtec.com/ICA


Insulator Material:
Black Glass Filled
Polyester
except -328 is LCP
Contact: BeCu
Shell: Brass except style K
Phosphor Bronze
Plating: Au or Sn over 50μ" Ni
Flammability Rating:
UL 94V-O
Insulation Resistance:
5000 MΩ min
Temperature Range:
-55°C to +105°C with Tin
-55°C to +125°C with Gold.
Withstanding Voltage:
1000 VRMS
Current Rating: 1A
Contact Resistance:
10mΩ max
Lead Size Range:
.015" (0,38mm) to .022"
(0,56mm) DIA and most IC leads
Insertion Force:
(Single contact only)
Standard = 9 oz avg, 16 oz max;
Low Insertion Force =
2.5 oz avg, 5.5 oz max
Withdrawal Force:
(Single contact only)
Standard = 2.5 oz avg, 1.5 oz
min; Low Insertion Force =
2.0 oz avg, 0.35 oz min
Lead-Free Solderable:
Wave only
RoHS Compliant: No



Note: Some sizes, styles and
options are non-standard,
non-returnable.


-S, -ZS, -ZA, -J, or -K

= Printed Circuit
-ZS & -ZA = Low Insertion Force



LEAD STYLE	X DIA	Y TAIL	Z
-S or -ZS	(0,51) .020	(3,18) .125	(7,62) .300
-ZA	(0,51) .020	(4,57) .180	(8,89) .350
-J	(0,64) .025	(10,41) .410	(15,24) .600
-K	(0,89) .035	(12,95) .510	(17,86) .703


Locking lead
available with -S
and -ZS.
See OPTION.



Insertion Depth = .095" (2,41) to .145" (3,68):
Style S Component Part No. = SC-1P1
Style ZS Component Part No. = EZ-1P1
Style ZA Component Part No. = EZ-6P1
Option L Component Part No. = SC-1L1 or EZ-1L1
Insertion Depth = .095" (2,41) to .138" (3,51)
Style J Component Part No. = SC-1P3
Insertion Depth = .125" (3,18) to .157" (3,99)
Style K Component Part No. = SC-2P1

-W, -ZW

= Wire-Wrap
ZW = Low Insertion Force




Shorter wire-wrap tail
lengths available.
See OPTION.

Insertion Depth = .125" (3,18) to .157" (3,99)
Style W Component Part No. = SC-1W1(1)
Style ZW Component Part No. = EZ-1W1(1)
Style W-2 Component Part No. = SC-1W1(2)
Style W-3 Component Part No. = EZ-1W1(2)
Style W-3 Component Part No. = SC-1W1(3)
Style ZW-3 Component Part No. = EZ-1W1(3)

-ZE or -ZH

= Elevated
Low Insertion Force



LEAD STYLE	X DIA	W TAIL	Y	Z
-ZE	(0,51) .020	(4,32) .170	(8,86) .349	(13,77) .542
-ZH	(0,46) .018	(3,81) .150	(12,95) .510	(17,86) .703

Insertion Depth = .125" (3,18) to .170" (4,32)
Style ZE Component Part No. = EZ-2P3
Insertion Depth = .125" (3,18) to .145" (3,68)
Style ZH Component Part No. = EZ-2P2

Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM

SAMTEC USA • Tel: 1-800-SAMTEC-9 or 812-944-6733 • Fax: 812-948-5047

SAMTEC GERMANY • Tel: +49 (0) 89 / 89460-0 • Fax: +49 (0) 89 / 89460-299

SAMTEC NORDIC/BALTIC • Tel: +46-84477280 • Fax: +46-84420413

SAMTEC JAPAN • Tel: 045-475-1385 • Fax: 045-475-1340

SAMTEC KOREA • Tel: 82-31-717-5685 • Fax: 82-31-717-5681

SAMTEC SILICON VALLEY • Tel: 408-395-5900 • Fax: 408-395-1520

SAMTEC FRANCE • Tel: 01 60 95 06 60 • Fax: 01 60 95 06 61

SAMTEC ITALY • Tel: 39 039 6890337 • Fax: 39 039 6890315

SAMTEC INDIA • Tel: +91-80-3272 1612 • Fax: +91-80-4152 8187

SAMTEC CHINA • Tel: 86-21-61103766 • Fax: 86-21-5423 4575

SAMTEC SOUTH AFRICA • Tel: 27 11 454 4317 • Fax: 27 86 6714432

SAMTEC UK • Tel: 01236 739292 • Fax: 01236 727113

SAMTEC TAIWAN • Tel: 886-2-2735-6109 • Fax: 886-2-2735-5036

SAMTEC ANZ • Tel: 613 9512 7747 • Fax: 613 9512 7745

SAMTEC ASIA PACIFIC • Tel: 65 6745-5955 • Fax: 65 6841-1502

SAMTEC SOUTH AFRICA • Tel: 27 11 454 4317 • Fax: 27 86 6714432