

Conductive Carbon Infused Nylon® For Static Protection And Shielding

FLEXO ANTI-STAT (CNN) is braided from 11 mil carbonized Nylon[®] monofilament yarn. Flexo Anti-Stat is designed to protect sensitive wiring from abrasion while shielding it from high frequency noise. Many successful applications have utilized this sleeving for maintaining clean video signals, interference filtering in pro sound environments, and RF filtering on power cables and outputs. CNN is also useful in static sensitive environments.

Flexo Anti-Stat utilizes a patented carbonization process which infuses our braided sleeving with a microscopic carbon compound that is virtually indistinguishable from the base material. The result is a strong, long lasting jacket that is ready for the most sensitive applications.

- ESD Management Solution
- EMI, RFI Protection
- Economical and Easy to Install
- Cut & Abrasion
 Resistant
- Expands up to 150%
- Halogen Free
- Resists Gasoline and Engine Chemicals



Clean signals without excessive noise can be achieved with properly isolated cables and wires.

"Techflex assures maximum protection for delicate video and data lines."

Tim Daly - Emmy Award Winning Engineer InterTest - www.intertestinc.com

Nominal Size	Part #	Expansion Range		Standard Spool Put-Ups		Available	Lbs/
		Min.	Max.	Bulk Spool	Shop Spool	Colors	100′
1/8″	CNN0.13BK	3/32″	1/4″	1,000′	225′	Black (BK)	0.35
1/4″	CNN0.25BK	1/8″	7/16″	1,000′	200′	Black (BK)	0.40
3/8″	CNN0.38BK	3/16″	5/8″	500′	125′	Black (BK)	0.60
1/2″	CNN0.50BK	1/4″	3/4″	500′	100′	Black (BK)	0.68
5/8″	CNN0.63BK	3/8″	1″	500′	100′	Black (BK)	0.96
3/4″	CNN0.75BK	1/2″	1 1/4″	250′	75′	Black (BK)	1.00
1″	CNN1.00BK	5/8″	1 5/8″	250′	65′	Black (BK)	1.20
1 1/4″	CNN1.25BK	3/4″	1 3/4″	250′	50′	Black (BK)	1.65
1 1/2″	CNN1.50BK	1″	2 1/2″	200′	40′	Black (BK)	2.20

 $\mathsf{Nylon}^{\circledast}$ is a registered trademark of DuPont Corporation.



