


Adapter Plates for SUB-D Inserts



for Housing	Style	for Bottom Parts	for Top Parts
HA 10	1 x 9	0-1107196-1	0-1107197-1
HA 10	1 x 15	0-1107196-2	0-1107197-2
HA 10	1 x 25	0-1107196-3	0-1107197-3
HA 16	1 x 37	0-1107202-1	0-1107203-1
HA 16	1 x 50	0-1107202-2	0-1107203-2
HB 06	2 x 9	0-1107198-1	0-1107199-1
HB 06	2 x 15	0-1107198-2	0-1107199-2
HB 18	1 x 15 + 25	0-1107200-2	0-1107201-2
HB 10	2 x 25	0-1107200-1	0-1107201-1
HB 16	1 x 25 + 37	0-1107204-2	0-1167205-2
HB 16	2 x 37	0-1107204-3	0-1107205-3
HB 16	2 x 50	0-1107204-4	0-1107205-4
HB 16	1 × 9 + 15 + 25	0-1107204-1	0-1107205-1



1 + 2 - 100 A/1000 V 2 + 2 - 63 A/1000 V 3 1 4 46 A/1000 V 8 - 16 A/ 400 V

Signal 15 - 10 A/ 250 V 18 - 10 A/ 250 V

Twinax/Koax

4-pole screened 1-pole RG 58/59 6-pole RG 58/59

LWL/Pneumatic

18 x Optical transmission

2 x Pneumatic 10 bar/NW4




for Housing HB 10 2 x MDL

for Housing HB 16 3 x MDL

for Housing HB 24 4 x MDL

for Housing HB 32 6 x MDL

for Housing HB 48 8 x MDL



Screen Termination and Grips



Application in surface mounted housings or in high construction housings only.

for contact insert size HB 06 1-1106305-9

for contact insert size HB 10 1-1106306-9

for contact insert size HB 16 1-1106307-9

for contact insert size HR 24 1-1106308-9



HIP/EMV Housing IP 68



HIP/EMV

- Pressure tight up to 5 bar
- Aluminum die-cast alloy
- Integrated all-around protective metal collar at the hood
- Internal 0-seal or all-around flange seal at the surface mounted
- Screw locking system
- Tightening screws with sealing ring

Series HIP-K

- Corrosion protection guaranteed, even in extremly adverse
- environmental influences
- No contact corrosion

Series EMV/EMV-K

- · Protection against electro-magnetic influence
- · Adequate interference resistance

for contact insert size HB 16 1-1106300-9

for contact insert size HB 24 1-1106301-9



Assembly without housing