

Search by part # or keyword 

Products

Industries &
Solutions

Resources

Shop TE

Sign In



Reliable Switching Devices > Switches > Slide Switches

MSSA211NG

Slide Switches, Double Pole - Double Throw Configuration (Pole-Throw), Vertical, Copper Alloy
Contact Base Material, Actuators Single, 2 Positions

Alcoswitch

TE Internal #: **4-1437580-9**TE Internal Description: **MSSA211NG=SLIDE
W/PC TERMINALS**Configuration (Pole-Throw) : **Double Pole -
Double Throw**Mounting Angle : **Vertical**Contact Base Material : **Copper Alloy**Number of Actuators : **Single**Number of Positions : **2** [Digital Datasheet](#)

ORDER SAMPLES

[Compatible Parts & Tooling](#)[Purchase items directly
from TE.com](#)

We are here to help!

Get in touch with our product experts.



CHAT WITH US



EMAIL US



CALL US

Documents

Features

Product Compliance

Product Drawings

MSSA211NG=SLIDE W/PC TERMINALS

 [MSSA211NG=SLIDE W/PC TERMINALS](#)

English

CAD Files

PCB Design

[Download symbol & footprint \(Ultra Librarian\)](#)

3D PDF

 [3D_CVM_CVM_4-1437580-9_C1.pdf](#)

3D

Customer View Model

 [ENG_CVM_CVM_4-1437580-9_C1.2d_dxf.zip](#)

English

 [ENG_CVM_CVM_4-1437580-9_C1.3d_igs.zip](#)

English

 [ENG_CVM_CVM_4-1437580-9_C1.3d_stp.zip](#)

English

Datasheets &
Catalog Pages

SWITCHES_CORE_PROGRAM_CATALOG

 [ENG_CS_1308111-
1_SWITCHES_CORE_PROGRAM_CATALOG_0308.pdf](#)

English



Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Terminal Configuration : Standard Actuator Style : Top Product Type : Switch Switch Type : Slide Grade : Instrumentation Threaded Case : Without
Configuration Features	Configuration (Pole-Throw) : Double Pole - Double Throw Number of Actuators : Single Number of Positions : 2 Operating Function : On None On Terminals Connected : 2-1, 5-4
Electrical Characteristics	Voltage Rating (VDC): 20
Body Features	Actuator Material : PPS Actuator Color : Black Actuator Travel : 3.05 mm [.12 in]
Contact Features	Contact Base Material : Copper Alloy Contact Current Rating (A): .4 Switch Contact Plating Material : Gold
Termination Features	Termination Type : PC
Mechanical Attachment	PCB Mount Retention Type : Extended PCB Mount Retention : Without Mounting Angle : Vertical Mounting Type : Through Hole
Dimensions	Length : 11.94 mm [.4701 in] Width : 11.43 mm [.45 in] Actuator Length : 2.79 mm [.11 in] PCB Tail Length : 3.18 mm [.125 in]
Identification Marking	Stamped Marking : With
Industry Standards	UL Flammability Rating : UL 94-HB
Packaging Features	Packaging Method : Tray

Statement of
Compliance

[Statement of Compliance](#) pdf

[ABOUT TE CONNECTIVITY](#)

[FOR PARTNERS](#)

[SUPPORT](#)

[CALL US](#)

[LIVE CHAT](#)

[UNITED STATES \(EN\)](#)