



+ RELAYS, CONTACTORS & SWITCHES
DIP & SIP SWITCHES



✓ Active

TE CONNECTIVITY (TE)
ADF04T04=DIP SWT,FLUSH,THRU/HL
[Alcoswitch](#) | [Alcoswitch DIP](#) , [Alcoswitch DIP ADF](#)

1825002-6
TE Internal Number: 1825002-6
Alias ID: ADF04T04

[EU RoHS Compliant](#)
[EU ELV Compliant](#)

Product Type Switch
Contact Mating Area Plating Material Gold Flash
Housing Color Black
Housing Material Polyphenylene Sulfide (PPS)
Auto-Insertable Yes

↓ **PRODUCT DRAWING**
English

DOCUMENTATION

Product Drawings
DIP SWITCH, ADF THRU HOLE
PDF
English

Catalog Pages/Data Sheets
SWITCHES_CORE_PROGRAM_CATALOG
PDF
English

Product Environmental Compliance
TE Material Declaration
MD_1825002-6_101720161559_dmtec

FEATURES



Please review product documents or [contact us](#) for the latest agency approval information.

Please Note: Use the Product Drawing for all design activity.

Product Type Features

Product Type Switch
Sealed Yes
Switch Type DIP
Actuator Style Flush, Slide

Configuration Features

Number of Switches 4
Configuration (Pole-Throw) Single Pole - Single Throw
Number of Positions 4

Electrical Characteristics

Voltage Rating (VDC) 5

Body Features

Actuator Color White
Seal Type Tape

Contact Features

Contact Mating Area Plating Material Gold Flash
Auto-Insertable Yes
Contact Current Rating (A) 1
Contact Base Material Copper Alloy
Contact Mating Area Plating Thickness (µin) 1.2
Solder Tail Contact Plating Gold over Nickel

Termination Features

Termination Post Length 4 mm [.157 in]

Mechanical Attachment

Mounting Type Through Hole
Mounting Angle Vertical

Housing Features

Housing Color Black
Housing Material Polyphenylene Sulfide (PPS)
Centerline 2.54 mm [.1 in]

Dimensions

Length 12.14 mm [.477 in]

Height 4 mm [.138 in]

Usage Conditions

Operating Temperature Range (°C) -30 – 85

Industry Standards

UL Flammability Rating UL 94V-0

Packaging Features

Packaging Quantity 35

Packaging Method Tube

PRODUCT COMPLIANCE



Statement of Compliance

Statement of Compliance

PDF