



+ RELAYS, CONTACTORS & SWITCHES
SLIDE SWITCHES



✓ Active

TE CONNECTIVITY (TE)
ASE22RGL04=DPDT AUTOSLIDE

[Alcoswitch](#) | ASE/F

1825010-9
TE Internal Number: 1825010-9
Alias ID: ASE22RGL04

[EU RoHS Compliant](#)
[EU ELV Compliant](#)

Configuration (Pole-Throw) Double Pole - Double Throw
Mounting Angle Right Angle
Contact Base Material Copper Alloy
Number of Actuators Single
Number of Positions 2

[↓](#) **PRODUCT DRAWING**
English

[↓](#) **3D PDF**

DOCUMENTATION

Product Drawings

SLIDE SWITCH ASE/ASF, AUTO-INSERTABLE, THRU-HOLE AND SURFACE MOUNT
PDF
English

CAD Files

Customer View Model
2D_DXF.ZIP
English

3D PDF
PDF
3D

Customer View Model

3D_IGS.ZIP

English

Customer View Model

3D_STP.ZIP

English

Catalog Pages/Data Sheets

SWITCHES_CORE_PROGRAM_CATALOG

PDF

English

FEATURES



Please review product documents or [contact us](#) for the latest agency approval information.

Please Note: Use the Product Drawing for all design activity.

Product Type Features

- Terminal Configuration** Standard
- Switch Style** Auto-Insertable
- Actuator Style** Extended, Side
- Product Type** Switch
- Switch Type** Slide
- Grade** Telecom
- Threaded Case** Without

Configuration Features

- Configuration (Pole-Throw)** Double Pole - Double Throw
- Number of Actuators** Single
- Number of Positions** 2

Body Features

- Actuator Color** Natural
- Actuator Material** Nylon
- Actuator Travel** 2.79 mm [.11 in]

Contact Features

- Contact Base Material** Copper Alloy
- Contact Plating** Gold

Termination Features

- Termination Type** SMT, Gull Wing

Mechanical Attachment

- Mounting Angle** Right Angle
- Mounting Type** Surface Mount
- PCB Mount Retention** Without

Dimensions

Length 10.16 mm [.4 in]
Width 7.37 mm [.2902 in]
Actuator Length 2.79 mm [.1098 in]

Identification Marking

Stamped Marking With

Industry Standards

UL Flammability Rating UL 94V-0

Packaging Features

Packaging Method Tube

PRODUCT COMPLIANCE



Statement of Compliance

Statement of Compliance
PDF