



+ RELAYS, CONTACTORS & SWITCHES
SLIDE SWITCHES



✓ Active

TE CONNECTIVITY (TE)
MHS233K04=DP3T SL SW VERT AG

[Alcoswitch](#) | [MHS](#)

1-1825289-0
TE Internal Number: 1-1825289-0
Alias ID: MHS233K04

[EU RoHS Compliant](#)
[EU ELV Compliant](#)

Configuration (Pole-Throw) Double Pole - Three Throw

Mounting Angle Vertical

Contact Base Material Copper Alloy

Number of Actuators Single

Number of Positions 3

 **PRODUCT DRAWING**
[English](#)

 **3D PDF**

DOCUMENTATION

Product Drawings

SLIDE SWITCH, MHS SERIES, DOUBLE POLE, VERTICAL

PDF
English

CAD Files

3D PDF
PDF
3D

Customer View Model

2D_DXF.ZIP
English

Customer View Model

3D_IGS.ZIP

English

Customer View Model

3D_STP.ZIP

English

Catalog Pages/Data Sheets

SWITCHES_CORE_PROGRAM_CATALOG

PDF

English

Product Environmental Compliance

TE Material Declaration

MD_1-1825289-0_11292016852_dmtec

PDF

English

FEATURES



Please review product documents or [contact us](#) for the latest agency approval information.

Please Note: Use the Product Drawing for all design activity.

Product Type Features

Terminal Configuration Standard

Switch Style Low Profile

Actuator Style Lever

Product Type Switch

Switch Type Slide

Grade Instrumentation

Threaded Case Without

Configuration Features

Configuration (Pole-Throw) Double Pole - Three Throw

Number of Actuators Single

Number of Positions 3

Operating Function On On On

Terminals Connected 1-2, 5-6

Body Features

Actuator Color Black

Actuator Material Thermoplastic

Actuator Travel 2 mm [.079 in]

Contact Features

Contact Base Material Copper Alloy

Contact Current Rating (A) .3

Contact Plating Silver

Termination Features

Termination Type PC

Mechanical Attachment

Mounting Angle Vertical

Mounting Type Through Hole

PCB Mount Retention Type Guide Posts

PCB Mount Retention With

Dimensions

Length 15 mm [.5906 in]

Width 6.2 mm [.2441 in]

Actuator Length 4.5 mm [.18 in]

PCB Tail Length 3.51 mm [.138 in]

Identification Marking

Stamped Marking With

Industry Standards

UL Flammability Rating UL 94-HB

Packaging Features

Packaging Method Tray

PRODUCT COMPLIANCE



Statement of Compliance

Statement of Compliance

PDF