



1825261-1

TE Internal Number: 1825261-1



Active

## Slide Switches

[Always EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

### Product Highlights:

- 2 Positions
- Double Pole - Double Throw Configuration (Pole-Throw)
- Actuator Style = Top
- Actuator Color = Black
- MSS Series

[View all Features](#)

## Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)



[Add to My Part List](#)



[Request Sample](#)



[Find Similar Products](#)



[Buy Product](#)

## Documentation & Additional Information

### Product Drawings:

- [SLIDE SWITCH, MSS 2200 SERIES, VERTICAL](#) (PDF, English)

### Catalog Pages/Data Sheets:

- None Available

### Product Specifications:

- None Available

### Application Specifications:

- None Available

### Instruction Sheets:

- None Available

### CAD Files:

- None Available

### Additional Information:

- [Product Line Information](#)

### Related Products:

- [Tooling](#)

[List all Documents](#)

## Product Features (Please use the Product Drawing for all design activity)

### Product Type Features:

- Configuration (Pole-Throw) = Double Pole - Double Throw
- Actuator Style = Top
- Mount Angle = Vertical
- Terminal Configuration = Standard
- Grade = Instrumentation
- Termination Type = PC
- PCB Mount Retention = With

### Electrical Characteristics:

- Contact Rating = 0.4 VA max @ 20 VDC or peak AC

### Body Related Features:

- [Number of Positions](#) = 2
- Actuator Color = Black
- Series = MSS
- Mount Style = Through-Hole
- PCB Tail Length (mm [in]) = 5.33 [0.210]
- PCB Mount Retention Type = Guide Posts
- Actuator Length (mm [in]) = 2.30 [0.090]
- Actuator Material = Polyester
- Actuator Travel = 2.00 [.079]

### Contact Related Features:

- Contact Plating = Silver

### Housing Related Features:

- UL Flammability Rating = UL 94V-0

### Configuration Related Features:

- Threaded Case = Without
- Number of Actuators = Single

### Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C, solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant

### Identification Marking:

- Stamped Marking = With

### Other:

- Brand = Alcoswitch



BOOKMARK



## Corporate Information

[Who We Are](#)

[Investors](#)

[News Room](#)

[Supplier Portal](#)

[Careers](#)

## Quick Links

[Check Distributor Inventory](#)

[Cross Reference](#)

[Find Documents & Drawings](#)

[Product Compliance Support Center](#)

[Site Map](#)

## Customer Support

[Email or Chat with Us](#)

[Find a Phone Number](#)

[Search Knowledge Base](#)

[Manage Your Account](#)

## Sign up for our eNewsletter

Enter your email address

## Follow Us On:



Visit Us On:

