

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

[List all Documents](#)**Product Features** (Please use the Product Drawing for all design activity)**Product Type Features:**

- Configuration (Pole-Throw) = Four Pole - Double Throw
- Actuator Style = Extended, Top
- Series = MSS
- Mount Angle = Vertical
- Terminal Configuration = Standard
- Grade = Instrumentation
- Termination Type = PC
- PCB Mount Retention = With

Electrical Characteristics:

- Contact Rating = 300mA @ 125 VAC

Body Features:

- [Number of Positions](#) = 2
- Actuator Color = Black
- Mount Style = Through-Hole
- PCB Tail Length (mm [in]) = 3.40 [0.134]
- PCB Mount Retention Type = Guide Posts
- Actuator Length (mm [in]) = 12.00 [0.472]
- Actuator Material = POM
- Actuator Travel = 2.00 [.079]

Contact Features:

- Contact Plating
- Contact Base

Housing Features:

- UL Flammability

Configuration Features:

- Threaded Connector
- Number of Positions

Industry Standards:

- [RoHS/ELV Compliance](#)
- [Lead Free Solder](#)
solder capability
- RoHS/ELV Compliance

Identification Markings:

- Stamped Markings

Other:

- Brand = Alcon

Corporate Information[Who We Are](#)[Investors](#)[News Room](#)[Supplier Portal](#)[Careers](#)**Quick Links**[Check Distributor Inventory](#)[Cross Reference](#)[Find Documents & Drawings](#)[Product Compliance Support Center](#)[Site Map](#)**Customer Support**[Email or Chat With Us](#)[Find a Phone Number](#)[Search Knowledge Base](#)[Manage your Account](#)