

Instruction Sheets:

- None Available

CAD Files:

- None Available

[List all Documents](#)**Product Features** (Please use the Product Drawing for all design activity)**Product Type Features:**

- Termination Type = Solder/Plug-In Terminals

Electrical Characteristics:

- Actuating System = DC
- Input Voltage (VDC) = 48
- Contact Current Rating (Amps.) = 2
- [Coil Resistance \(\$\Omega\$ \)](#) = 1400
- Coil Power, Nominal (mW) = 1650
- Dielectric Between Coil and Contacts (V rms) = 500

Body Related Features:

- [Series](#) = V23003/Cradle Relay P
- Polarized = Yes

Contact Related Features:

- Number of Bistable Coils = Double
- Mounting Options = Socket
- Enclosure = Dust Protected
- [FCC Part 68 Isolation](#) = No
- Approved Standards = None
- Contact Material = Silver, Gold Overlay
- Approx. Dimensions (L x W x H) (mm [in]) = 30.00 x 19.00 x 30.00 [1.181 x .748 x 1.181]
- Compatible Socket = With
- Contact Type = Bifurcated
- Pin Configuration = Industry Standard

Configuration Related Features:

- [Contact Arrangement](#)
- [Coil Magnetic System](#)
- Coil Suppression Diode

Industry Standards:

- [RoHS/ELV Compliance](#) compliant
- [Lead Free Solder Process](#) capable to 240°C, Wave solder capable to 260°C, Wave solder capable
- RoHS/ELV Compliance comply with RoHS directive

Other:

- Brand = Axicom

[Provide Website Feedback](#) | [Need Help?](#)[Home](#) | [Customer Support](#) | [Suppliers](#) | [Site Map](#) | [Privacy Policy](#) | [Browser Support](#)

© 2008 Tyco Electronics Corporation All Rights Reserved