

6-1393806-7 (V23154C 717B104) TE Internal Number: 6-1393806-7

Active

Converted to EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- V23154/Cradle Relay N Series
- DC Actuating System
- Input Voltage = 12 VDC Contact Arrangement = 2 Form C, DPDT, 2 C/O

communications, signal PC Doard Relays

Contact - Rated Current = 2 A

View all Features







Documentation & Additional Information

Product Drawings:

None Available

Catalog Pages/Data Sheets:

None Available

Product Specifications:

Cradle N Relay Datasheet (PDF, English)

Application Specifications:

· None Available

Instruction Sheets:

None Available

CAD Files:

None Available

Additional Information:

Product Line Information

Check Pricing & Availability

Contact Us About This Pro-

Search for Tooling Product Feature Selector

Related Products:

Tooling

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Series = V23154/Cradle Relay N
- Termination Type = Solder/Plug-In Terminals

Electrical Characteristics:

- Actuating System = DC
- Input Voltage (VDC) = 12
- Contact Rated Current (A) = 2
- Coil Resistance (Ω) = 220
- Coil Rated Power (mW) = 650
- <u>Insulation Special Features</u> = None
- Insulation Initial Dielectric Between Contacts and Coil (V rms) = 500

Body Features:

Polarized = No

Contact Features:

- Mounting Options = Socket
- Enclosure Type = Dust Protected
- · Contact Base Material = Silver, Gold Overlay
- Approx. Dimensions (L \times W \times H) (mm [in]) = 24.00 \times 19.00 \times 30.00 [.945 x .748 x 1.181]
- Compatible Socket = With
- Contact Configuration = Single
- Pin Configuration = Industry Standard

Configuration Features:

- Contact Arrangement = 2 Form C, DPDT, 2 C/O
- <u>Coil Magnetic System</u> = Non Polarized, Monostable
- Coil Suppression Diode = Without

Industry Standards:

- Approved Standards = None
- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Wave solder capable to 240°C, solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Converted to comply with Roll directive

Other:

Brand = Axicom

Corporate Information

Who We Are Investors News Room Supplier Portal

Careers

Quick Links

Check Distributor Inventory Cross Reference

Find Documents & Drawings Product Compliance Support Center

Site Map

Customer Support

Email or Chat With Us Find a Phone Number Search Knowledge Base Manage your Account

Keep Me Informed

Receive TE News, Events & Technology Updates

Enter your email address











