

Molded Parts Specification Control Drawing

inches

 All dimensions are in inches [millimeters]
Dimensions appearing in table are as follows:

- a As Supplied
- b After Unrestricted Recovery
- 3. Part shall have injection and vent ports, located as shown.





222D2XX-X-32

Part Number :

TABLE OF DIMENSIONS														
PART NUMBER	Н			J		Р	R	Т	U	JO	PP	RR	HW	JW
NOWDER	Min	Max	Min	Min	Max	±10%	±10%	±10%	±10%	±10%	±10%	±10%	±20%	±20%
	a	b	-3,-4,-25 a	-12 a	b	b	b	b	b	b	b	b	b	ь
222D211-X-32	.88	.45	.88	.55	.25	2.75	.73	.12	.04	2.06	.27	.49	.06	.045
	[22,4]	[11,4]	[22,4]	[14,0]	[6,4]	[69,9]	[18,5]	[3,05]	[1,02]	[52,3]	[6,9]	[12,4]	[1,52]	[1,14]
222D221-X-32	1.01	.59	1.01	.63	.29	3.10	.78	.12	.04	2.12	.33	.59	.06	.045
	[25,7]	[15,0]	[25,7]	[16,0]	[7,4]	[78,7]	[19,8]	[3,05]	[1,02]	[53,8]	[8,4]	[15,0]	[1,52]	[1,14]
222D232-X-32	1.16	.74	1.16	.72	.33	3.50	.82	.12	<u>.04</u>	2.24	.41	<u>.61</u>	.07	.045
	[29,5]	[18,8]	[29,5]	[18,3]	[8,4]	[88,9]	[20,8]	[3,05]	[1,02]	[56,9]	[10,4]	[15,5]	[1,78]	[1,14]
222D242-X-32	1.34	.90	1.34	.84	. <u>38</u>	4.00	.86	.12	<u>.04</u>	2.44	.48	<u>.62</u>	<u>.07</u>	.045
	[34,0]	[22,9]	[34,0]	[21,3]	[9,7]	[101,6]	[21,8]	[3,05]	[1,02]	[62,0]	[12,2]	[15,7]	[1,78]	[1,14]
222D253-X-32	1.47	1.16	1.47	.91	.41	4.25	.96	.12	.065	2.62	.61	.70	.08	.045
	[37,3]	[29,5]	[37,3]	[23,1]	[10,4]	[108,0]	[24,4]	[3,05]	[1,65]	[66,5]	[15,5]	[17,8]	[2,03]	[1,14]
222D263-X-32	1.72	1.34	1.72	1.07	.48	4.75	1,08	.12	.065	3.00	.72	.78	.08	.045
	[43,7]	[34,0]	[43,7]	[27,2]	[12,2]	[120,7]	[27,4]	[3,05]	[1,65]	[76,2]	[18,3]	[19,8]	[2.03]	[1,14]
222D274-X-32	1.97	1.62	1.97	1.24	. <u>56</u>	5.20	1,16	.12	.065	3.18	.83	.82	.09	.055
	[50,0]	[41,1]	[50,0]	[31,5]	[14,2]	[132,1]	[29,5]	[3,05]	[1,65]	[80,8]	[21,1]	[20,8]	[2.29]	[1,40]
222D285-X-32	2.47	1.85	2.47	1.54	<u>.69</u>	5.25	1.31	.12	.08	2.92	.95	.92	.10	.055
	[62,7]	[47,0]	[62,7]	[39,1]	[17,5]	[133,4]	[33,3]	[3,05]	[2,03]	[74,2]	[24,1]	[23,4]	[2,54]	[1,40]
222D296-X-32	2.73	2.35	2.73	1.70	<u>.77</u>	5.40	1.38	.12	.08	2.40	1.18	.93	<u>.10</u>	.055
	[69,3]	[59,7]	[69,3]	[43,2]	[19,6]	[137,2]	[35,1]	[3,05]	[2,03]	[61,0]	[30,0]	[23,6]	[2.54]	[1,40]
222D299-X-32	3.22	2.64	3.22	2.01	<u>.90</u>	5.50	1.75	.12	.08	2.12	1.31	1.23	.10	.055
	[81,8]	[67,1]	[81,8]	[51,1]	[22,9]	[139,7]	[44,5]	[3,05]	[2,03]	[53,8]	[33,3]	[31,2]	[2,54]	[1,40]

tyco

Electronics 300 CONSTITUTION DRIVE MENLO PARK, CALIFORNIA 94025

Revision: B Date: 5/22/03 Part Number :

222D2XX-X-32

Description: Boot, 90°, With Lip


Molded Parts Specification Control Drawing

Part Number : 222D2XX-X-32 Description: Boot, 90°, With Lip

COMPATABILITY CHART								
MATERIAL DASH NO.	MATERIAL DESCRIPTION	RT SPEC	COATING SLASH NO.	COATING S NO.	COATING DESCRIPTION			
-3	Polyolefin, Semi-rigid	RT-301	N/A					
-4	Polyolefin, Flexible	RT-1304	N/A					
-12	*VITON, Flexible	RT-1312	N/A					
-25	Elastomer, Fluid Resistant	RT-1325	N/A					
-100	Polyolefin, Semi-flexible ZEROHAL™	RT-1323	N/A					

*VITON is a Registered Trademark of Dupont

If this document is printed it becomes uncontrolled. Check for the latest revision.



THIS DRAWING IS SUBJECT TO CHANGE WITHOUT NOTICE; CONSULT YOUR NEAREST FIELD REPRESENTATIVE FOR CURRENT REVISION

tyco Electronics

TYCO ELECTRONICS 300 CONSTITUTION DRIVE MENLO PARK, CALIFORNIA 94025

Revision: B Date: 5/22/03

Part Number : 222D2XX-X-32 Description : Boot, 90°, With Lip

CAD FILE MP03125