

Tyco Electronics

Our commitment. Your advantage.

Search

Products

Documentation

Resources

My Account

Customer Support

Home > Products > By Type > Pin & Socket Connectors > Product Feature Selector > Product Details

212491-5 Product Details

212491-5

Active

Subminiature D Pin/Socket Connectors for MIL-C-24308 and MIL-C-39029

Not EU RoHS or ELV Compliant (Find RoHS Compliant Alternates)

Product Highlights:

Connector

Product Series = 109

Density = Standard

Terminate To Coaxial Cable, Terminate To Printed Circuit Board, Terminate To Wire

Insert Arrangement = 5C5

View all Features

Find Similar Products

Live Product Chat

US Only

8:30am - 5pm ET, Mon - Fri

Quick Links

Check Pricing & Availability

Search for Tooling

Product Feature Selector

Contact Us About This Product

Documentation & Additional Information

Product Drawings:

PLUG ASSEMBLY AMPLIMITE 5C5 SIZE 3, SERIES 109, COAX MIX

(PDF, English)

Catalog Pages/Data Sheets:

None Available

Product Specifications:

None Available

Application Specifications:

None Available

Instruction Sheets:

None Available

CAD Files:

None Available

Additional Information:

Product Line Information

Additional Product Images:

PCB Layout

Related Products:

Tooling

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

Product Type = Connector

Product Series = 109

Gender = Plug

Shell Size = 3

Shell Material = Steel

Comment = Cable clamp/strain relief hardware cannot be used with these arrangements.; With grounding indents.; P/N is supplied with 4-40 UNC-28 clinch nuts in the mounting hole positions

Body Related Features:

Insert Arrangement = 5C5

Blindmate = No

Non-Magnetic = No

Pins = Without

Rear Grommet = No

Power/Signal/Coax Combination = Yes

Shell Plating = Tin-lead over Copper

Mount Style = Mounting Holes

Retention Clip Material = Stainless Steel

Contact Related Features:

Contact Size = 20

Configuration Related Features:

Density = Standard

Industry Standards:

Government/Industry Qualification = No

RoHS/ELV Compliance = Not ELV/RoHS compliant

Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260° C, Wave solder capable to 265°C

NASA Qualification = No

Conditions for Usage:

Terminate To = Coaxial Cable, Printed Circuit Board, Wire

Other:

Brand = AMP

Provide Website Feedback | Contact Customer Support

Home | Customer Support | Suppliers | Site Map | Privacy Policy | Browser Support

© 2008 Tyco Electronics Corporation All Rights Reserved