


 Live Product Chat US Only
8:30am - 5pm ET, Mon - Fri



 Active

Always EU RoHS/ELV Compliant (Statement of Compliance)

- ? Connector
- ? Plug
- ? Number of Positions = 60
- ? Not Shielded
- ? Without Mating Connector Lock

[View all Features](#) | [Find Similar Products](#)

[Check Pricing & Availability](#)
[Search for Tooling](#)
[Product Feature Selector](#)
[Contact Us About This Product](#)

[CAP ASSY \(HORIZONTAL / W/LEG\) AMPLIMITE .050 SERIES...](#)
(PDF, English)

? None Available

[AMPLIMITE*.050 SERIES I BTB CONNECTOR](#) (PDF, English)

? None Available

? None Available

? None Available

? Product Line Information

? Tooling

List all Documents

? Product Type = Connector
 ? Gender = Plug
 ? Number of Positions = 60
 ? Shielded = No
 ? Mating Connector Lock = Without
 ? Mount Angle = Right Angle
 ? PCB Polarization = Without
 ? PCB Retention Feature = Yes
 ? Rails = Without
 ? Shell Type = All Plastic
 ? Product Series = Series I
 ? Comment = Connectors are secured by soldering to contact posts. For connector with retention legs, connector is temporarily secured onto pc board prior to soldering.

? Termination (Solder) Post Length (mm [in]) = 3.10 [0.122]

? PCB Retention Method = Boardlock(s)
 ? Post Plating = Tin over Nickel

? Contact Mating Area Plating = Gold (8)
? Contact Material = Phosphor Bronze

?	Housing Material = Thermoplastic	
?	Housing Flammability Rating = UL 94V	-0
?	Housing Color = Black	

- ? RoHS/ELV Compliance = RoHS compliant, ELV compliant
- ? Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- ? RoHS/ELV Compliance History = Always was RoHS compliant

? Brand = AMP