

 [Live Product Chat](#)



✓ Active

 [Add to Part List](#)

 Always EU RoHS/ELV Compliant (Statement of Compliance)

- Number of Positions = 15
- Receptacle
- PCB Mount Angle = Vertical
- Product Series = HDP-20
- Without Mating Connector Lock

[View all Features](#) | [Find Similar Products](#)

- ▶ [Check Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [View Mating Products \(7\)](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)
- ▶ [Request Samples](#)

NEW!

- [15 pol hd-20 stiftstecker mit pfofen 0,63 x 0.63](#) (PDF, English)

- None Available

- None Available

- None Available

- None Available

- None Available

- Product Line Information

- PC Board Mount Specifications

- Tooling
- Mating Products (7)

List all Documents

- Number of Positions = 15
- Gender = Receptacle
- PCB Mount Angle = Vertical
- Product Series = HDP-20
- Mating Connector Lock = Without
- PCB Retention Feature = No
- Shell Type = Full Metal
- Shell Size = 2
- PCB Thickness (in [mm]) = 0.062 [1.57]
- Grounding Indents = Without
- Grounding Straps = Without
- PCB Mount Style = Thru Hole
- Color Code = None
- Sealed = No
- Post Size (mm [in]) = 0.64 [.025]
- Shell Material = Steel
- Comment = All Assemblies are pre-loaded with size 20 posted contacts. 1.2 mm pc board holes are recommended.

- Panel Attachment = Without

- Grounding Clips = Without
- Termination (Solder) Post Length (mm [in]) = 3.20 [0.126]
- Solder Tail Contact Plating = Tin

- Insert Flammability Rating = UL 94V-0
- Insert Material = Brass
- Shell Plating = Tin

- Contact Mating Area Plating Material = Gold (30)
- Contact Shape = Square
- Contact Material = Phosphor Bronze

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Wave solder capable to 240°C
- RoHS/ELV Compliance History = Always was RoHS compliant

- Application = Standard

- Brand = AMP