

• <u>Terminal Shape</u> = Ring Tongue

• Wire Range (mm [AWG]) = 3.00-6.00<sup>2</sup> [12-10]

- <u>Receptacle Style</u> = Straight
- <u>Body Style</u> = PIDG
- <u>Barrel Type</u> = Closed Barrel
- <u>Wire/Cable Type</u> = Regular Wire
- <u>Insulation</u> = Yes
- <u>Insulation Support</u> = Insulation Support
- Insulation Diameter (mm [in]) = 3.81-5.84 [.150-.230]
- Stud Size = 6 [M3.5]
- <u>Stud Diameter (mm [in])</u> = 3.68 [0.145]
- Shape = RING-041
- Heavy Duty = No
- <u>Material</u> = Copper
- <u>Finish</u> = Tin
- Tongue Material Thickness (mm [in]) = 1.02 [0.040]
- Color = Yellow
- Insulation Material = Nylon

# Electrical Characteristics:

• Voltage (VAC) = 300

## • Wire Range (CMA) = 5,180 - 13,100

- Length (mm [in]) = 27.51 [1.083]
- Insulation Sleeve Material = Copper

## Industry Standards:

- Government/Industry Qualification = No
- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

#### Packaging Related Features:

- <u>Packaging Method</u> = Loose Piece
- Packaging Quantity = 50/Box

#### Other:

• Brand = AMP

# Provide Website Feedback | Contact Customer Support

Home | Customer Support | Suppliers | Site Map | Privacy Policy | Browser Support © 2008 Tyco Electronics Corporation All Rights Reserved