Materials

- 1. Shell, steel, nickel plated
- 2. Pins, brass, 5 μ " gold and tin plating
- 3. Insulator, PBT, white

Electrical

Rated voltage: 30 Vdc Rated current: 3 A

Dielectric strength: 1 min @ 500 Vac Insulation resistance: 500 M Ω @ 500 Vdc Contact resistance: 50 m Ω or less

Mechanical

Insertion force: 3.5 kgf maximum Withdrawal force: 1.0 kgf minimum

Durability: 1500 cycle minimum life; less than 100 m Ω contact resistance, minimum 100 M Ω insulation

resistance

Terminal strength: 0.3 kgf in any direction without

damage or looseness

Soldering

Solderability: 75% minimum coverage when terminals dipped 2 mm in 245 ±5 °C solder bath for 3 ±0.5 seconds

Solder bath durability: no deformation when immersed in 255 ± 5 °C up to surface of the board for 5 seconds or less

Solder iron durability: no deformation when exposed to 350 ± 10 °C for 3 ± 0.5 seconds


Environmental

Cold test: -40 ±3 °C for 48 hours without deformation Heat test: 85 ±2 °C for 48 hours without deformation Humidity test: 40 ±2 °C and humidity between 90 and 98 % for 48 hours without deformation

Operating range

-40 ~ 85°C

USB A 2.0 plug molding style



Revision:	Date:	Description:	Prepared:	Notes:					
Α	12/15/2015	Initial release	GL Digitally signed by GL Date: 2018.08.06 09:15:34 -07'00'	RoHS compliant		E	NSIL	ITY	
A1	07/27/201/	Corrected operating temp range	Verified: RS Digitally signed by RS Date: 2018.08.09 08:57:01-0700'	Function test: no open, no short circuit, no intermittent	l	1.541.323.3228 800 877.670.7118 ax 1.541.323.4202 web tensility.com			
			Dimensions are in			10.2 1.3 T1.323. T202 Web terisinty.com			
			millimeters. Tolerances: X: ± 0.5 mm	Description:	Size:	Size: Part number:			
				Connector, USB A plug, molding style, nickel shell, shielded, white insulator	Α	А 50-00467			
			X.X: ± 0.3 mm X.XX: ± 0.05 mm		Scale:	2:1		Sheet 1 of 1	