


CMOS Digital Integrated Circuit Silicon Monolithic

TC358767AXBG

Mobile Peripheral Devices

Overview

TC358767AXBG is a bridge device that enables video streaming from a Host (application or baseband processor) over MIPI DSI or DPI link to drive DisplayPort display panels. TC358767AXBG also supports audio streaming from the host via I2S interface to the Display panels. TC358767AXBG provides a low power bridge solution to efficiently translate MIPI DSI or DPI transfers to DisplayPort transfers. As the DisplayPort uses fewer wires compared to other existing display panel standards, it simplifies the LCD connectivity. The effect of using TC358767AXBG is to enable existing baseband devices supporting DSI or DPI streaming to connect to new panels supporting DisplayPort interface and also to connect to existing panels over longer distance using DisplayPort adaptors at far-end. TC358767AXBG can interface to up to two independent devices.



Features

- Translates MIPI DSI/DPI Link video stream from Host to DisplayPort Link data to external display devices.
- The inputs are driven by a DSI Host with 4-Data Lanes, upto1 Gbps/lane or DPI Host with 16/18/24 bit interface upto154 MHz parallel clock.
- Supports HDCP Digital Content Protection version 1.3 (DisplayPort amendment Rev1.1).
- Embeds audio information from the I2S port into the DisplayPort data stream.
- The output Interface consists of a DisplayPort Tx with a 2-lane Main Link and AUX-Ch.
- Register Configuration: From DSI link or I²C interface.
- Interrupt to host to inform any error status or status needing attention from Host.
- Internal test pattern (color bar) generator for DP o/p testing without any video (DSI/DPI) i/p.
- Debug/Test Port: I²C Slave
- **DSI Receiver**
 - ✧ MIPI DSI: v1.01 / MIPI D-PHY: v0.90 Compliant.
 - ✧ Up to four (4) Data Lanes with Bi-direction support on Data Lane 0.
 - ✧ Maximum speed at 1 Gbps/lane.
 - ✧ Supports Burst as well as Non-Burst Mode Video Data.
 - Video data packets are limited to one row per Hsync period.
 - ✧ Supports video stream packets for video data transmission.
 - ✧ Supports generic long packets for accessing the chip's register set.
- ✧ Video input data formats:
 - RGB-565, RGB-666 and RGB-888.
 - New DSI V1.02 Data Type Support: 16-bit YCbCr 422
- ✧ Interlaced video mode is not supported.
- **DPI Receiver**
 - ✧ Up to 16 / 18 / 24 bit parallel data interface.
 - ✧ Maximum speed at 154 MP/s (MPixel per sec).
 - ✧ Video input data formats: RGB-565, RGB-666 and RGB-888.
 - ✧ Only Progressive mode supported.
 - ✧ Shutdown support (can be used in non-DPI mode also).
- **I2S Audio Interface:** Supports one I2S port for audio streaming from the host to TC358767AXBG.
 - ✧ Supports slave mode (BCLK, LRCLK & over-sampling clock input from Host).
 - ✧ Supports sampling frequencies of 32, 44.1, 48, 88.2, 96, 176.4 & 192 kHz.
 - ✧ Supports up to 2 audio channels.
 - ✧ Supports 16, 18, 20 or 24bits per sample.
 - ✧ Optionally inserts IEC60958 status bits and preamble bits per channel.
- **DisplayPort Interface:** Supports a DisplayPort link from TC358767AXBG to display panels.
 - ✧ High speed serial bridge chip using VESA DisplayPort 1.1a Standard.
 - ✧ Supports one dual-lane DisplayPort port for high bandwidth applications
 - ✧ Support 1.62 or 2.7 Gbps/lane data rate with voltage swings @0.4, 0.6, 0.8 or 1.2 V
 - ✧ Support of pre-emphasis levels of 0, 3.5dB and

6dB.

- ✧ Supports Audio related Secondary Data Packets.
- ✧ AUX channel supported at 1 Mbps.
- ✧ HPD support through GPIO[0] based interrupts
- ✧ Enhanced mode supported for content protection.
- ✧ Support HDCP encryption Version 1.3 with DisplayPort amendment Revision 1.1.
- ✧ Secure ASSR (Alternate Scrambler Seed Reset) support for eDP panels
 - System designer connects ASSR_DisablePad to VSS to enable eDP panels and ASSR
 - Drive ASSR_DisablePad with an inner ring VDDS for using DP panels and disable ASSR
 - System software read Revision ID field, 0x0500[7:0]:
 - 0x01 indicates eDP panels are used, DPCD register bit 0x0010A[0] of eDP panel should be set
 - 0x03 assumes DP panels are connected, DPCD register bit 0x0010A[0] of DP panel should Not be set
- ✧ Stream Policy Maker is assumed handled by the Host (software/firmware).
 - Start Link training in response to HPD & read final Link training status
 - Configure DP link for actual video streaming & start video streaming
- ✧ Link Policy maker is assumed shared between the Host and TC358767AXBG chip.
 - In auto_correction = 0 mode, control link training
 - Initiate Display device capabilities read and configure TC358767AXBG accordingly.
- ✧ Video timing generation as per panel requirement.
- ✧ SSCG with to 30 kHz modulation to reduce EMI.
- ✧ Toshiba Magic Square algorithm – RGB666 18b produces RGB888 24b like quality (with up to 16-million colors).
- ✧ Built in PRBS7 Generator to test DisplayPort Link.

● I²C Interface:

- ✧ I²C slave interface for chip register set access enabled using a boot-strap option.
- ✧ I²C compliant slave interface support for normal (100 kHz) and fast mode (400 kHz).

● GPIO Interface:

- ✧ 2 bits of GPIO (shared with other digital logic).
- ✧ Direction controllable by Host I²C accesses.

● Clock Source:

- ✧ DisplayPort clock source is from an external clock input or clock from DSI interface (13, 26, 19.2 or 38.4 MHz) – generates all internal & output clocks to interfacing display devices.
- ✧ Built-in PLLs generate high-speed DisplayPort link clock requiring no external components. These

PLLs are part of the DisplayPort PHY.

- Clock and power management support to achieve low power states.

● Possible modes of Operation:

- ✧ MODE S21: TC358767AXBG uses DisplayPort Tx as single 2-lane DisplayPort link to interface to single DisplayPort display device. Video stream source is from MIPI DSI Host.
- ✧ MODE P21: TC358767AXBG uses DisplayPort Tx as single 2-lane DisplayPort link to interface to single DisplayPort display device. Video stream source is from MIPI DPI Host.

● Power supply inputs

- ✧ Core and MIPI D-PHY: 1.2 V ± 0.06 V
- ✧ Digital I/O: 1.8 V ± 0.09 V
- ✧ DisplayPort: 1.8 V ± 0.09 V
- ✧ DisplayPort: 1.2 V ± 0.06 V

● Power Consumptions (based on estimations)

- ✧ Power-down mode (DSI-Rx in ULPS, DP PHY & PLLs disabled, clocks stopped):
 - DSI Rx: 0.01 mW
 - DP PHY: 2.34 mW
 - PLL9: 0.01 mW
 - Core: 0.96 mW
 - Rest: 0.01 mW
- ✧ Normal operation (1920 × 1080 resolution with DSI-Rx in 4-lane @925 Mbps per lane, DP PHY in dual lane link @2.7 Gbps per lane):
 - DSI Rx: 21.79 mW
 - DP PHY: 142.70 mW
 - PLL9: 2.42 mW
 - Core: 87.64 mW
 - IOs: 1.68 mW

● Package

- 0.5mm ball pitch, 81 balls, 5 × 5 mm BGA package

Table of content

REFERENCES.....	6
1. Overview	7
2. Features	9
3. External Pins	13
3.1. TC358767AXBG External Pins	13
3.2. TC358767AXBG Pin Mapping.....	14
4. Package	15
5. Electrical Characteristics.....	17
5.1. Absolute Maximum Ratings.....	17
5.2. Operating Condition.....	17
5.3. DC Electrical Specification	18
5.4. Power Consumption	19
6. Revision History	20
RESTRICTIONS ON PRODUCT USE.....	21

Table of Figures

Figure 1.1 System Overview with TC358767AXBG in MODE_S21 Configuration	8
Figure 1.2 System Overview with TC358767AXBG in MODE_P21 Configuration	8
Figure 3.1 TC358767AXBG 81-Pin Layout.....	14
Figure 4.1 81 pin TC358767AXBG package	15

List of Tables

Table 2.1 TC358767AXBG operational modes summary with panel size support information	11
Table 2.2 Panel Size v/s Data link required by TC358767AXBG in DSI input case	11
Table 2.3 Panel Size v/s Data link required by TC358767AXBG in DPI input case	12
Table 3.1 TC358767AXBG Functional Signal List for 81-pin Package	13
Table 3.2 Mechanical Dimension of TC358767AXBG BGA.....	14
Table 4.1 Mechanical Dimension of P-VFBGA81-0505-0.50	16
Table 6.1 Revision History	20

- MIPI is registered trademarks of MIPI Alliance, Inc.
- VESA, VESA logo and the DisplayPort Icon are trademarks of the Video Electronics Standards Association.

1 NOTICE OF DISCLAIMER

2 The material contained herein is not a license, either expressly or impliedly, to any IPR owned or controlled
3 by any of the authors or developers of this material or MIPI. The material contained herein is provided on
4 an "AS IS" basis and to the maximum extent permitted by applicable law, this material is provided AS IS
5 AND WITH ALL FAULTS, and the authors and developers of this material and MIPI hereby disclaim all
6 other warranties and conditions, either express, implied or statutory, including, but not limited to, any (if
7 any) implied warranties, duties or conditions of merchantability, of fitness for a particular purpose, of
8 accuracy or completeness of responses, of results, of workmanlike effort, of lack of viruses, and of lack of
9 negligence.

10 All materials contained herein are protected by copyright laws, and may not be reproduced, republished,
11 distributed, transmitted, displayed, broadcast or otherwise exploited in any manner without the express
12 prior written permission of MIPI Alliance. MIPI, MIPI Alliance and the dotted rainbow arch and all related
13 trademarks, tradenames, and other intellectual property are the exclusive property of MIPI Alliance and
14 cannot be used without its express prior written permission.

15 ALSO, THERE IS NO WARRANTY OF CONDITION OF TITLE, QUIET ENJOYMENT, QUIET
16 POSSESSION, CORRESPONDENCE TO DESCRIPTION OR NON-INFRINGEMENT WITH REGARD
17 TO THIS MATERIAL OR THE CONTENTS OF THIS DOCUMENT. IN NO EVENT WILL ANY
18 AUTHOR OR DEVELOPER OF THIS MATERIAL OR THE CONTENTS OF THIS DOCUMENT OR
19 MIPI BE LIABLE TO ANY OTHER PARTY FOR THE COST OF PROCURING SUBSTITUTE
20 GOODS OR SERVICES, LOST PROFITS, LOSS OF USE, LOSS OF DATA, OR ANY INCIDENTAL,
21 CONSEQUENTIAL, DIRECT, INDIRECT, OR SPECIAL DAMAGES WHETHER UNDER
22 CONTRACT, TORT, WARRANTY, OR OTHERWISE, ARISING IN ANY WAY OUT OF THIS OR
23 ANY OTHER AGREEMENT, SPECIFICATION OR DOCUMENT RELATING TO THIS MATERIAL,
24 WHETHER OR NOT SUCH PARTY HAD ADVANCE NOTICE OF THE POSSIBILITY OF SUCH
25 DAMAGES.

26 Without limiting the generality of this Disclaimer stated above, the user of the contents of this Document is
27 further notified that MIPI: (a) does not evaluate, test or verify the accuracy, soundness or credibility of the
28 contents of this Document; (b) does not monitor or enforce compliance with the contents of this Document;
29 and (c) does not certify, test, or in any manner investigate products or services or any claims of compliance
30 with the contents of this Document. The use or implementation of the contents of this Document may
31 involve or require the use of intellectual property rights ("IPR") including (but not limited to) patents,
32 patent applications, or copyrights owned by one or more parties, whether or not Members of MIPI. MIPI
33 does not make any search or investigation for IPR, nor does MIPI require or request the disclosure of any
34 IPR or claims of IPR as respects the contents of this Document or otherwise.

35 Questions pertaining to this document, or the terms or conditions of its provision, should be addressed to:

36 MIPI Alliance, Inc.
37 c/o IEEE-ISTO
38 445 Hoes Lane
39 Piscataway, NJ 08854
40 Attn: Board Secretary

This Notice of Disclaimer applies to all DSI input and processing paths related descriptions throughout this document.

REFERENCES

1. MIPI DSI, "MIPI Alliance Specification for DSI Version 1.01.00 - 21 February 2008"
2. MIPI DPI, "MIPI Alliance Standard for Display Pixel Interface (DPI-2) Version 2.00 – 15 September 2005"
3. MIPI D-PHY, "DRAFT MIPI Alliance Specification for D-PHY Version 0.91.00 – r0.01 14-March-2008"
4. VESA DisplayPort Standard (Version 1, Revision 1A January 11, 2008)
5. VESA Embedded DisplayPort (eDP) Standard (Version 1.1 October 23, 2009)
6. Digital Content Protection LLC, HDCP (Version 1.3 with DisplayPort amendment Revision 1.1, Jan. 15 2010)
7. I²C bus specification, version 2.1, January 2000, Philips Semiconductor
8. Draft CEA-861-C, A DTV Profile for Uncompressed High Speed Digital Interfaces (Doc. Number: CEA-861rCv9.pdf (PNXXX)) Date: 05/04/2005
9. Display Port PHY DFT Strategy Specification Rev 1.3

1. Overview

The DSI/DPI to Display Port converter (TC358767AXBG) is a bridge device that enables video streaming from a Host (application or baseband processor) over MIPI DSI or DPI link to drive DisplayPort display panels.

TC358767AXBG also supports audio streaming from the host via I2S interface to the Display panels.

TC358767AXBG provides a low power bridge solution to efficiently translate MIPI DSI or DPI transfers to DisplayPort transfers. As the DisplayPort uses fewer wires compared to other existing display panel standards, it simplifies the LCD connectivity. The effect of using TC358767AXBG is to enable existing baseband devices supporting DSI or DPI streaming to connect to new panels supporting DisplayPort interface and also to connect to existing panels over longer distance using DisplayPort adaptors at far-end. TC358767AXBG can interface to up to two independent devices.

The chip can be configured through the DSI link by sending write/read register commands through DSI Generic Long Write packets. It can also be configured through the I²C Slave interface.

The DSI-RX receiver supports from 1 to 4-Lane configurations at bit rate up to 1 Gbps per lane. Host can transmit video in continuous video streaming mode. Host controls video timing by sending video frame and line sync events together with video pixel data; video data transmission can be burst or non-burst. Since the chip integrates only a small video buffer, Host still has to take care of transmitting pixel data at appropriate video line time in order to avoid buffer overflow (or underflow).

The DPI-Rx receiver supports 16, 18 or 24 bits parallel interface along with the required control signals for the Pixel clock and HSync/VSync/DE.

The TC358767AXBG also supports content protection using HDCP copy protection.

The DisplayPort transmitter supports data throughput at 1.62 Gbps or 2.7 Gbps per lane of main link.

TC358767AXBG supports two configuration modes, MODE S21 and MODE P21. These modes mainly differ based on the source of input stream and number of display devices that TC358767AXBG can be connected to.

- Mode_S21: A system configuration where TC358767AXBG may typically be used is shown in
- Figure 1.1. In this configuration, the TC358767AXBG can support displays with resolution up to WUXGA (1920×1200) at 24bit, 60 fps or WUXGA (1920×1200) at 18bit, 60 fps. Video stream source is from DSI Host.
- Mode_P21: A system configuration where TC358767AXBG may typically be used is shown in Figure 1.2. This is similar to the Mode_S21 except that the video stream source is from DPI Host. In this configuration, the TC358767AXBG can support displays with resolution up to WUXGA (1920×1200) at 24bit, 60 fps.

The chip supports power management to conserve power when its functions are not in use. Host manages the chip's power consumption modes by using ULPS messages over DSI link or the shutdown pin (SD) during DPI input mode.

The following figures show all these modes, where TC358767AXBG, display panels and a Host are connected in target Reference system for mobile large display panel applications.




Figure 1.1 System Overview with TC358767AXBG in MODE_S21 Configuration




Figure 1.2 System Overview with TC358767AXBG in MODE_P21 Configuration

2. Features

Below are the main features supported by TC358767AXBG.

- Translates MIPI DSI/DPI Link video stream from Host to DisplayPort Link data to external display devices.
- The inputs are driven by a DSI Host with 4-Data Lanes, upto1 Gbps/lane or DPI Host with 16/18/24 bit interface upto154 MHz parallel clock.
- Supports HDCP Digital Content Protection version 1.3 (DisplayPort amendment Rev1.1).
- Embeds audio information from the I2S port into the DisplayPort data stream.
- The output Interface consists of a DisplayPort Tx with a 2-lane Main Link and AUX-Ch.
- Register Configuration: From DSI link or I²C interface.
- Interrupt to host to inform any error status or status needing attention from Host.
- Internal test pattern (color bar) generator for DP o/p testing without any video (DSI/DPI) i/p.
- Debug/Test Port: I²C Slave
- **DSI Receiver**
 - ✧ MIPI DSI: v1.01 / MIPI D-PHY: v0.90 Compliant.
 - ✧ Up to four (4) Data Lanes with Bi-direction support on Data Lane 0.
 - ✧ Maximum speed at 1 Gbps/lane.
 - ✧ Supports Burst as well as Non-Burst Mode Video Data.
 - Video data packets are limited to one row per Hsync period.
 - ✧ Supports video stream packets for video data transmission.
 - ✧ Supports generic long packets for accessing the chip's register set.
 - ✧ Video input data formats:
 - RGB-565, RGB-666 and RGB-888.
 - New DSI V1.02 Data Type Support: 16-bit YCbCr 422
 - ✧ Interlaced video mode is not supported.
- **DPI Receiver**
 - ✧ Up to 16 / 18 / 24 bit parallel data interface.
 - ✧ Maximum speed at 154 MPs (MPixel per sec).
 - ✧ Video input data formats: RGB-565, RGB-666 and RGB-888.
 - ✧ Only Progressive mode supported.
 - ✧ Shutdown support (can be used in non-DPI mode also).
- **I2S Audio Interface:** Supports one I2S port for audio streaming from the host to TC358767AXBG.
 - ✧ Supports slave mode (BCLK, LRCLK & over-sampling clock input from Host).
 - ✧ Supports sampling frequencies of 32, 44.1, 48, 88.2, 96, 176.4 & 192 kHz.
 - ✧ Supports up to 2 audio channels.
 - ✧ Supports 16, 18, 20 or 24 bits per sample.
 - ✧ Optionally inserts IEC60958 status bits and preamble bits per channel.
- **DisplayPort Interface:** Supports a DisplayPort link from TC358767AXBG to display panels.
 - ✧ High speed serial bridge chip using VESA DisplayPort 1.1a Standard.
 - ✧ Supports one dual-lane DisplayPort port for high bandwidth applications
 - ✧ Support 1.62 or 2.7 Gbps/lane data rate with voltage swings @0.4, 0.6, 0.8 or 1.2 V
 - ✧ Support of pre-emphasis levels of 0, 3.5 dB and 6 dB.
 - ✧ Supports Audio related Secondary Data Packets.
 - ✧ AUX channel supported at 1 Mbps.
 - ✧ HPD support through GPIO[0] based interrupts
 - ✧ Enhanced mode supported for content protection.
 - ✧ Support HDCP encryption Version 1.3 with DisplayPort amendment Revision 1.1.
 - ✧ Secure ASSR (Alternate Scrambler Seed Reset) support for eDP panels
 - System designer connects ASSR_DisablePad to VSS to enable eDP panels and ASSR
 - Drive ASSR_DisablePad with an inner ring VDDS for using DP panels and disable ASSR
 - System software read Revision ID field, 0x0500[7:0]:
 - 0x01 indicates eDP panels are used, DPCD register bit 0x0010A[0] of eDP panel should be set

- 0x03 assumes DP panels are connected, DPCD register bit 0x0010A[0] of DP panel should Not be set
 - ✧ Stream Policy Maker is assumed handled by the Host (software/firmware).
 - Start Link training in response to HPD & read final Link training status
 - Configure DP link for actual video streaming & start video streaming
 - ✧ Link Policy maker is assumed shared between the Host and TC358767AXBG chip.
 - In auto_correction = 0 mode, control link training
 - Initiate Display device capabilities read and configure TC358767AXBG accordingly.
 - ✧ Video timing generation as per panel requirement.
 - ✧ SSCG with to 30 kHz modulation to reduce EMI.
 - ✧ Toshiba Magic Square algorithm – RGB666 18b produces RGB888 24b like quality (with up to 16-million colors).
 - ✧ Built in PRBS7 Generator to test DisplayPort Link.
- **I²C Interface:**
 - ✧ I²C slave interface for chip register set access enabled using a boot-strap option.
 - ✧ I²C compliant slave interface support for normal (100 kHz) and fast mode (400 kHz).
 - **GPIO Interface:**
 - ✧ 2 bits of GPIO (shared with other digital logic).
 - ✧ Direction controllable by Host I²C accesses.
 - **Clock Source:**
 - ✧ DisplayPort clock source is from an external clock input or clock from DSI interface (13, 26, 19.2 or 38.4 MHz) – generates all internal & output clocks to interfacing display devices.
 - ✧ Built-in PLLs generate high-speed DisplayPort link clock requiring no external components. These PLLs are part of the DisplayPort PHY.
 - Clock and power management support to achieve low power states.
 - **Possible modes of Operation:**
 - ✧ MODE S21: TC358767AXBG uses DisplayPort Tx as single 2-lane DisplayPort link to interface to single DisplayPort display device. Video stream source is from MIPI DSI Host.
 - ✧ MODE P21: TC358767AXBG uses DisplayPort Tx as single 2-lane DisplayPort link to interface to single DisplayPort display device. Video stream source is from MIPI DPI Host.
 - **Power supply inputs**
 - ✧ Core and MIPI D-PHY: 1.2 V ± 0.06 V
 - ✧ Digital I/O: 1.8 V ± 0.09 V
 - ✧ DisplayPort: 1.8 V ± 0.09 V
 - ✧ DisplayPort: 1.2 V ± 0.06 V

● **Power Consumptions (based on estimations)**

- ✧ Power-down mode (DSI-Rx in ULPS, DP PHY & PLLs disabled, clocks stopped):
 - DSI Rx: 0.01 mW
 - DP PHY: 2.34 mW
 - PLL9: 0.01 mW
 - Core: 0.96 mW
 - Rest: 0.01 mW
- ✧ Normal operation (1920×1080 resolution with DSI-Rx in 4-lane @925 Mbps per lane, DP PHY in dual lane link @2.7 Gbps per lane):
 - DSI Rx: 21.79 mW
 - DP PHY: 142.70 mW
 - PLL9: 2.42 mW
 - Core: 87.64 mW
 - IOs: 1.68 mW

● **Package**

- 0.5mm ball pitch, 81 balls, 5 × 5 mm BGA package

Note: Attention about ESD. This product is weak against ESD. Please handle it carefully.

Table 2.1 TC358767AXBG operational modes summary with panel size support information

Mode	Input Configuration		Register Access Method	Max Panel size example
	DSI input	DPI input		
S21	Active	X	DSI or I ² C	WUXGA 18bpp @ 60fps WUXGA 24bpp @ 60fps
P21	X	Active	I ² C	WUXGA 24bpp @ 60fps

Tables below provide an idea of different panel sizes that can be supported by using different data link lane configurations.

Table 2.2 Panel Size v/s Data link required by TC358767AXBG in DSI input case

Frame Size		With OverHead	FPS	Pixel Clock (MHz)	RGB666			RGB888				
					Bit Rate (Gbps)	# DSI Data lanes	# DP Main links		Bit Rate (Gbps)	# DSI Data lanes	# DP Main links	
							1.62G	2.7G			1.62G	2.7G
XGA	1024×768	1184×790	60	56	1.01	2	1	1	1.34	2	2	1
WXGA+	1366×768	1526×790	60	72	1.30	2	2	1	1.74	2	2	1
WXGA+ / WSXGA	1440×900	1600×926	60	89	1.60	2	2	1	2.13	3	2	1
SXGA+	1400×1050	1560×1080	60	89	1.82	2	2	1	2.43	3	2	2
WSXGA+	1680×1050	1840×1080	60	119	2.15	3	2	1	2.86	3	-	2
UXGA	1600×1200	1760×1235	60	130	2.35	3	2	2	3.13	4	-	2
WUXGA	1920×1200	2080×1235	60	154	2.77	3	-	2	3.70	4	-	2

Table 2.3 Panel Size v/s Data link required by TC358767AXBG in DPI input case

Frame Size			FPS	Pixel Clock (MHz)	DPI Support 154 MHz PCLK	RGB666			RGB888		
		With OverHead				Bit Rate (Gbps)	# DP Main links		Bit Rate (Gbps)	# DP Main links	
							1.62G	2.7G		1.62G	2.7G
XGA	1024×768	1184×790	60	56	Yes	1.01	1	1	1.34	2	1
WXGA+	1366×768	1526×790	60	72	Yes	1.30	2	1	1.74	2	1
WXGA+ / WSXGA	1440×900	1600×926	60	89	Yes	1.60	2	1	2.13	2	1
SXGA+	1400×1050	1560×1080	60	89	Yes	1.82	2	1	2.43	2	2
WSXGA+	1680×1050	1840×1080	60	119	Yes	2.15	2	1	2.86	–	2
UXGA	1600×1200	1760×1235	60	130	Yes	2.35	2	2	3.13	–	2
WUXGA	1920×1200	2080×1235	60	154	Yes	2.77	–	2	3.70	–	2

Note: These are the formats commonly used by displays. Support for other sizes is possible as long as they satisfy the maximum data rate constraints on the DSI and DisplayPort link interfaces.

NOTE: Throughout the rest of the document, “DP” is used to denote “DisplayPort”. Both these words have been used interchangeably and refer to the VESA DisplayPort specification as mentioned in the references.

3. External Pins

3.1. TC358767AXBG External Pins

TC358767*AXBG uses an 81pin package. Following table gives the signals of TC358767AXBG and their function.

Table 3.1 TC358767AXBG Functional Signal List for 81-pin Package

Group	Pin Name	I/O	Type	Function	Note
System: Reset & Clock (9)	RESX	I	Sch	System Reset – active Low	
	REFCLK	I	Sch	13, 26, 19.2 or 38.4 MHz 50ps phase jitter p2p/ WC duty cycle 40-60%	
	TEST	I	N	Test Pin, active high	
	TEST[3]	O	N	Test Pin, Open	
	INT	O	N	Interrupt to Host	4mA
	SD	I	N	Shutdown Input	
	DISABLE_ASSR	I	N	1: Disable ASSR, set when connecting to DP panels 0: Enable ASSR for eDP panel application	
DSI Rx (10)	MODE[1:0]	I	N	Mode Selection pins	
	DSICP	I	MIPI-PHY	MIPI-DSI Rx Clock Lane Pos	
	DSICM	I	MIPI-PHY	MIPI-DSI Rx Clock Lane Neg	
	DSIDP[3:0]	I/O	MIPI-PHY	MIPI-DSI Rx Data Lane Pos	
DP Out (8)	DSIDM[3:0]	I/O	MIPI-PHY	MIPI-DSI Rx Data Lane Neg	
	DPLNP[1:0]	O	DP-PHY	eDP Output Main Link Pos	
	DPLNM[1:0]	O	DP-PHY	eDP Output Main Link Neg	
	DPAUXP[0]	I/O	DP-PHY	eDP Output AUX Channel Pos	
DPI Rx (28)	DPAUXM[0]	I/O	DP-PHY	eDP Output AUX Channel Neg	
	PREC_RES[1:0]	I	DP-PHY	Precision Resistance (3K @ 1%) connection	
	DPI_PCLK	I/O	N	DPI Pixel Clock (max 154 MHz) (default: Input)	4mA
	DPI_VSYNC	I/O	N	DPI Vertical Sync (default: Input)	4mA
	DPI_HSYNC	I/O	N	DPI Horizontal Sync (default: Input)	4mA
I2C (3)	DPI_DE	I/O	N	DPI Data Enable (default: Input)	4mA
	DPI_D [23:0]	I/O	N	DPI Parallel Data (default: Input)	4mA
	I2C_SCL	OD	FS/Sch	I ² C Clock	
I2S (3)	I2C_SDA	OD	FS/Sch	I ² C Data	4mA
	I2C_ADR_SEL	I	N	I ² C Slave Address Select	
GPIO (2)	I2S_BCLK	I	N	I2S Bit Clock (max 12.5 MHz)	
	I2S_LRCLK	I	N	I2S sample clock (max 192 kHz)	
	I2S_DATA	I	N	I2S Data	
POWER (11)	GPIO[1:0]	OD	5T-OD	GPIO or Test Control ^{*Note1} GPIO[1:0] can be used for HPD support	4mA
	VDDC (VDD12)	NA		VDD for Internal Core (2)	
	VDDS (1.8V)	NA		VDDS for IO Ring power supply (1)	
	VDD_PLL18 (1.8V)	NA		VDD for DP PHY PLLs (1)	
	VDD_PLL12 (1.2V)	NA		VDD for DP PHY PLLs(1)	
	VDD_DP18 (1.8V)	NA		VDD for DP PHY Main Channels (2)	
	VDD_PLL912(1.2V)	NA		VDD for PLL9 (1)	
	VDD_DP12 (1.2V)	NA		VDD for DP PHY (1)	
VDD_DSI12 (1.2V)	NA		VDD for the MIPI DSI PHY (1)		
GROUND (7)	VPGM	NA		eFUSE programming voltage (1)	
	VSS	NA		Ground (including VSSC (core), VSS_IO (IO), VSS_DSI (MIPI), VSS_DP (DP))	

Total 81 pins TC358767AXBG BGA package.

Note 1: Pins with multiplexed Functional mode functions

- N: Normal IO
- PHY: Either DP analog front end or MIPI D-PHY
- OD: Open drain
- Pd: Pull Down
- FS: Fail safe IO – gated
- Sch: Schmitt trigger input
- 5T-OD: 5 V tolerant bi-direction buffer with Open drain

3.2. TC358767AXBG Pin Mapping

The mapping of TC358767AXBG signals to the external pins is given in the following figure. (BGA array)

Top View (through the die)

A1 DSIDM_0	A2 DSIDP_0	A3 I2S_LRCLK	A4 VDDC	A5 VDDC	A6 INT	A7 VDDS	A8 I2C_SDA	A9 I2C_SCL
B1 DSIDM_1	B2 DSIDP_1	B3 GPIO_0	B4 I2S_BCLK	B5 I2S_DATA	B6 MODE_0	B7 MODE_1	B8 GPIO_1	B9 I2C_ADR_SEL
C1 DSICM	C2 DSICP	C3 DPI_DE	C4 DPI_VSYNC	C5 DPI_D_5	C6 DPI_D_7	C7 DPI_D_10	C8 TEST_3	C9 SD
D1 VDD_DSI12	D2 VSS_DSI	D3 DPI_HSYNC	D4 DPI_D_0	D5 VSS	D6 DPI_D_9	D7 DPI_D_12	D8 DPI_D_13	D9 DSI_D_14
E1 DSIDM_2	E2 DSIDP_2	E3 DPI_D_1	E4 DPI_D_3	E5 VSS	E6 VSS	E7 DPI_D_16	E8 VPGM	E9 DPI_D_11
F1 DSIDM_3	F2 DSIDP_3	F3 DPI_D_2	F4 DPI_D_6	F5 DPI_D_8	F6 DPI_D_15	F7 DPI_D_18	F8 DPI_D_17	F9 DPI_D_20
G1 PREC_RES_0	G2 Disable_ASSR	G3 DPI_D_4	G4 TEST	G5 DPI_D_19	G6 DPI_PCLK	G7 DPI_D_21	G8 DPI_D_23	G9 DPI_D_22
H1 PREC_RES_1	H2 VSS_DP	H3 DPLNP_0	H4 VDD_DP12	H5 VSS_DP	H6 DPLNP_1	H7 VSS_DP	H8 DPAUXP_0	H9 VDD_PLL912
J1 REFCLK	J2 VDD_DP18	J3 DPLNM_0	J4 VDD_PLL12	J5 VDD_PLL18	J6 DPLNM_1	J7 VDD_DP18	J8 DPAUXM_0	J9 RESX

Figure 3.1 TC358767AXBG 81-Pin Layout

Table 3.2 Mechanical Dimension of TC358767AXBG BGA

Package	Solder Ball Pitch	Solder Ball Height	Package Dimension	Package Height	Note
81-Pin	0.5 mm	0.25 mm	5.0 × 5.0 mm ²	1.0 mm	

4. Package

The package for TC358767AXBG is described in the figure below.

P-VFBGA81-0505-0.50-001

"Unit:mm"




Figure 4.1 81 pin TC358767AXBG package

Weight: 44.0 mg (Typ.)

The mechanical dimension of BGA81 package is listed below.

Table 4.1 Mechanical Dimension of P-VFBGA81-0505-0.50-001

Package	Solder Ball Pitch	Solder Ball Height	Package Dimension	Package Height	Note
81-Pin	0.50 mm	0.25 mm	5.0 × 5.0 mm ²	1.0 mm	

5. Electrical Characteristics

5.1. Absolute Maximum Ratings

VSS= 0 V reference

VDD18 used for VDDS as well as VDD-DP18; VDD12 used for VDDC as well as VDD-DSI12

Parameter	Symbol	Rating	Unit
Supply voltage (1.8 V)	VDD18	-0.3 to +3.5	V
Supply voltage (1.2 V)	VDD12	-0.3 to +2.0	V
Supply voltage (IO)	VDD18	-0.3 to +3.5	V
	VREF	-0.3 to +3.5	V
Input voltage	VIN	-0.3 to VDDS+0.3	V
Output voltage	VOUT	-0.3 to VDDS+0.3	V
Storage temperature	Tstg	-40 to +125	°C

5.2. Operating Condition

VSS= 0 V reference

VDD18 used for VDDS as well as VDD-DP18; VDD12 used for VDDC as well as VDD-DSI12

Parameter	Symbol	Min	Typ.	Max	Unit
Supply voltage (1.8 V)	VDD18	1.71	1.8	1.89	V
Supply voltage (1.2 V)	VDD12	1.14	1.2	1.26	V
Operating frequency (internal)	Fopr	-	-	200	MHz
Operating temperature	Ta	-20	-	+85	°C

5.3. DC Electrical Specification

VSS=VSS_C=VSS_IO=VSS_DSI=VSS_DP=VSS_PLL=VSS_REG=0V reference

Parameter	Symbol	Min	Typ.	Max	Unit
Input voltage High level CMOS input ^{Note1}	VIH	0.7 VDD5		VDD5	V
Input voltage Low level CMOS input ^{Note1}	VIL	0		0.3 VDD5	V
Input voltage High level CMOS Schmitt Trigger ^{Note1}	VIHS	0.7 VDD5		VDD5	V
Input voltage Low level CMOS Schmitt Trigger ^{Note1}	VILS	0		0.3 VDD5	V
Output voltage High level ^{Note1, Note2}	VOH	0.8 VDD5		VDD5	V
Output voltage Low level ^{Note1, Note2}	VOL	0		0.2 VDD5	V
Input leak current High level	I _{IH1} ^(Note3)	-10	-	10	μA
Input leak current Low level	I _{IL1} ^(Note4)	-10	-	10	μA
	I _{IL2} ^(Note5)	-200	-	-10	μA

Note1: VDD5 within recommended operating condition.

Note2: Output current value is according to each IO buffer specification. Output voltage changes with output current value.

Note3: Normal pin, or Pull-up I/O pin applied VDD18_IO supply voltage to input pin

Note4: Normal pin applied VSS (0 V) to input pin

Note5: Pull-up I/O pin applied VSS (0 V) to input pin

5.4. Power Consumption

Power consumption as measured for the power-down modes and for normal operation are provided below:

- Power-down mode (DSI-Rx in ULPS, DP PHY & PLLs disabled, clocks stopped):
 - ✧ DSI Rx: 0.01 mW
 - ✧ DP PHY: 2.34 mW
 - ✧ PLL9: 0.01 mW
 - ✧ Core: 0.96 mW
 - ✧ Rest: 0.01 mW

- Normal operation (1920×1080 resolution with DSI-Rx in 4-lane @925 Mbps per lane, DP PHY in dual lane link @2.7 Gbps per lane):
 - ✧ DSI Rx: 21.79 mW
 - ✧ DP PHY: 142.70 mW
 - ✧ PLL9: 2.42 mW
 - ✧ Core: 87.64 mW
 - ✧ IOs: 1.68 mW

6. Revision History

Table 6.1 Revision History

Revision	Date	Description
0.97	2014-04-10	Newly released

RESTRICTIONS ON PRODUCT USE

- Toshiba Corporation, and its subsidiaries and affiliates (collectively "TOSHIBA"), reserve the right to make changes to the information in this document, and related hardware, software and systems (collectively "Product") without notice.
- This document and any information herein may not be reproduced without prior written permission from TOSHIBA. Even with TOSHIBA's written permission, reproduction is permissible only if reproduction is without alteration/omission.
- Though TOSHIBA works continually to improve Product's quality and reliability, Product can malfunction or fail. Customers are responsible for complying with safety standards and for providing adequate designs and safeguards for their hardware, software and systems which minimize risk and avoid situations in which a malfunction or failure of Product could cause loss of human life, bodily injury or damage to property, including data loss or corruption. Before customers use the Product, create designs including the Product, or incorporate the Product into their own applications, customers must also refer to and comply with (a) the latest versions of all relevant TOSHIBA information, including without limitation, this document, the specifications, the data sheets and application notes for Product and the precautions and conditions set forth in the "TOSHIBA Semiconductor Reliability Handbook" and (b) the instructions for the application with which the Product will be used with or for. Customers are solely responsible for all aspects of their own product design or applications, including but not limited to (a) determining the appropriateness of the use of this Product in such design or applications; (b) evaluating and determining the applicability of any information contained in this document, or in charts, diagrams, programs, algorithms, sample application circuits, or any other referenced documents; and (c) validating all operating parameters for such designs and applications. **TOSHIBA ASSUMES NO LIABILITY FOR CUSTOMERS' PRODUCT DESIGN OR APPLICATIONS.**
- **PRODUCT IS NEITHER INTENDED NOR WARRANTED FOR USE IN EQUIPMENTS OR SYSTEMS THAT REQUIRE EXTRAORDINARILY HIGH LEVELS OF QUALITY AND/OR RELIABILITY, AND/OR A MALFUNCTION OR FAILURE OF WHICH MAY CAUSE LOSS OF HUMAN LIFE, BODILY INJURY, SERIOUS PROPERTY DAMAGE AND/OR SERIOUS PUBLIC IMPACT ("UNINTENDED USE").** Except for specific applications as expressly stated in this document, Unintended Use includes, without limitation, equipment used in nuclear facilities, equipment used in the aerospace industry, medical equipment, equipment used for automobiles, trains, ships and other transportation, traffic signaling equipment, equipment used to control combustions or explosions, safety devices, elevators and escalators, devices related to electric power, and equipment used in finance-related fields. **IF YOU USE PRODUCT FOR UNINTENDED USE, TOSHIBA ASSUMES NO LIABILITY FOR PRODUCT.** For details, please contact your TOSHIBA sales representative.
- Do not disassemble, analyze, reverse-engineer, alter, modify, translate or copy Product, whether in whole or in part.
- Product shall not be used for or incorporated into any products or systems whose manufacture, use, or sale is prohibited under any applicable laws or regulations.
- The information contained herein is presented only as guidance for Product use. No responsibility is assumed by TOSHIBA for any infringement of patents or any other intellectual property rights of third parties that may result from the use of Product. No license to any intellectual property right is granted by this document, whether express or implied, by estoppel or otherwise.
- **ABSENT A WRITTEN SIGNED AGREEMENT, EXCEPT AS PROVIDED IN THE RELEVANT TERMS AND CONDITIONS OF SALE FOR PRODUCT, AND TO THE MAXIMUM EXTENT ALLOWABLE BY LAW, TOSHIBA (1) ASSUMES NO LIABILITY WHATSOEVER, INCLUDING WITHOUT LIMITATION, INDIRECT, CONSEQUENTIAL, SPECIAL, OR INCIDENTAL DAMAGES OR LOSS, INCLUDING WITHOUT LIMITATION, LOSS OF PROFITS, LOSS OF OPPORTUNITIES, BUSINESS INTERRUPTION AND LOSS OF DATA, AND (2) DISCLAIMS ANY AND ALL EXPRESS OR IMPLIED WARRANTIES AND CONDITIONS RELATED TO SALE, USE OF PRODUCT, OR INFORMATION, INCLUDING WARRANTIES OR CONDITIONS OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, ACCURACY OF INFORMATION, OR NONINFRINGEMENT.**
- Do not use or otherwise make available Product or related software or technology for any military purposes, including without limitation, for the design, development, use, stockpiling or manufacturing of nuclear, chemical, or biological weapons or missile technology products (mass destruction weapons). Product and related software and technology may be controlled under the applicable export laws and regulations including, without limitation, the Japanese Foreign Exchange and Foreign Trade Law and the U.S. Export Administration Regulations. Export and re-export of Product or related software or technology are strictly prohibited except in compliance with all applicable export laws and regulations.
- Please contact your TOSHIBA sales representative for details as to environmental matters such as the RoHS compatibility of Product. Please use Product in compliance with all applicable laws and regulations that regulate the inclusion or use of controlled substances, including without limitation, the EU RoHS Directive. **TOSHIBA ASSUMES NO LIABILITY FOR DAMAGES OR LOSSES OCCURRING AS A RESULT OF NONCOMPLIANCE WITH APPLICABLE LAWS AND REGULATIONS.**