

1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com



NetDirector 16-Port Cat5 Matrix KVM Switch 1U Rack-Mount 2-User

MODEL NUMBER: B060-016-2





Description

Tripp Lite's 2-User 16-port NetDirector® 1U Rackmount Matrix KVM Switch is the optimal solution for controlling multiple computers (combination of PS/2, USB or Sun) by two independent, simultaneous users. A single unit occupies a mere 1U of rack space, yet can control up to 16 directly connected computers. A maximum of 1,024 computers can be connected through a combination of daisy-chaining and cascading. RJ45 connections allow signals to travel up to 150 meters away (500 ft.) using ordinary Cat5 cable, while maintaining video resolution. Use either PS/2 or USB console equipment to connect to PS/2, USB or SUN Servers.

For Government purchasers, B060-016-2 is Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases. Constructed of heavy-duty steel housing.

Features

- Three Level password security: Super Administrator, Administrator, and Users
- Superior video quality up to 1024 x 768 @ 60Hz at 500ft.
- Auto Signal Compensation (ASC) assures optimum video resolution for distances up to 500ft between the switch and the consoles or computers - no dip switch setting required
- PS/2 keyboard and mouse emulation computers boot even when the console focus is elsewhere.
 Keep Alive feature ensures that the keyboard and mouse work properly even if the switch temporarily loses power
- Daisy chain up to 7 additional B060-016 KVM Switches
- No software required; convenient computer selection via intuitive hotkey combinations or On Screen Display (OSD) menus
- OSD port list automatically expands when stations are added port names are automatically reconfigured when the station sequence is changed

Highlights

- Two consoles independently and simultaneously control up to 16 directly connected computers, or over 1,000 when additional KVMs are connected
- Multi-platform support: PC, Sun or Mac
- Rackmountable in a 1U design...Rackmount Hardware Included
- Inexpensive Cat5 cabling makes cable management a breeze; up to 500 ft. distance from console to switch and up to 500 ft. from switch to servers
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

System Requirements

- Console: The Tripp Lite B062-002-PS2 or B062-002-USB
 Console Interface Module must be used to connect a console (Keyboard, Monitor and Mouse) to the KVM switch
- Computers: The Tripp Lite
 B054-001-SUN Server Interface
 Module must be used to connect a computer/server to the KVM
 switch

Package Includes

- 1 B060-016-2 KVM Switch
- 1 Power Cord
- 1 Daisy Chain Cable
- 1 CD with Owner's Manual
- 1 set Rackmount Hardware



- OSD screen automatically adjusts to resolution changes
- Hot pluggable; add or remove components without having to power off the switch
- USB and PS/2 Consoles can control any combination of USB, PS/2, or SUN computers
- LCD, VGA, SVGA, XGA, and MultiSync support; DDC2B
- Rackmount Hardware Included
- Lifetime firmware upgrading via flash ROM
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases
- Constructed of heavy-duty steel housing

Specifications

OVERVIEW		
UPC Code	037332138750	
Console	No	
Max CPU	1024	
PHYSICAL		
Color	Black	
LCD Monitor (cm)	Not Applicable	
LCD Monitor (in.)	Not Applicable	
Shipping Dimensions (hwd / cm)	4.44 x 43.18 x 27.94	
Shipping Dimensions (hwd / in.)	1.75 x 17.00 x 11.00	
Shipping Weight (kg)	5.35	
Shipping Weight (lbs.)	11.80	
ENVIRONMENTAL		
BTUs	38.6 to 41.7	
COMMUNICATIONS		
Port Control	Hotkeys, OSD	
IP Remote Access	Yes	
CONNECTIONS		
Ports	16	
PC/Server Connections	VGA; USB; PS/2	
FEATURES & SPECIFICATIONS		



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234

Number of Users	2
NIAP-Certified Secure	No
Cat5 KVM Switch	Yes
Technology	Cat5/5e; PS/2; USB; VGA/SVGA
WARRANTY	
Product Warranty Period (Worldwide)	1-year limited warranty

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies