

2-Port HDMI Splitter - HDMI 2.0, HDCP 2.2, 4K @ 60 Hz, HDR, TAA

MODEL NUMBER: B118-002-UHD-2







Transmits Ultra High Definition (UHD) 4K x 2K audio/video (A/V) from an HDMI source to two HDMI displays at the same time. Recommended for digital signage in classrooms, churches, office buildings, restaurants/bars, etc.

Description

The B118-002-UHD-2 2-Port 4K 3D HDMI Splitter transmits a UHD 4K x 2K (@ 60 Hz) audio/video signal from an HDMI source, such as a Blu-ray[™] player or computer, to two HDMI monitors, projectors or televisions at the same time. Ideal for classrooms, churches, offices, restaurants, bars, trade shows and anywhere else featuring 4K x 2K digital signage, the B118-002-UHD-2 is quick and simple to install with no software or drivers necessary.

Using standard 28 AWG HDMI cabling, this splitter can transmit a 4K x 2K (3840 x 2160) signal up to 15 feet (4 meters). It supports a wide range of audio formats, including DTS-HD, Dolby TrueHD, Dolby Digital Plus, and LPCM 7.1-channel surround sound, as well as 36-bit Deep Color (12 bits per channel). The Full 3D-compliant B118-002-UHD-2 also supports HDMI 2.0 and HDCP 2.2 to ensure its compatibility with the latest audio/video hardware.

Features

Transmits a 4K HDMI A/V Signal to 2 HDMI Displays Simultaneously

- Recommended for 4K x 2K digital signage in classrooms, churches, offices, restaurants, bars, trade shows, etc.
- Distributes A/V signals up to 15 ft. (4 m) when used with standard 28 AWG HDMI cable
- Maintains UHD video resolutions up to 3840 x 2160 @ 60 Hz
- HDCP 2.2, EDID and HDMI 2.0 compliant to ensure compatibility with latest A/V hardware
- Cascade up to 3 levels of splitters together to increase the number of connected monitors up to 32. Supports the Most Up-To-Date Features and Formats
- Supports High Dynamic Range (HDR) for richer contrast and expanded color accuracy

Highlights

- Transmits UHD video resolutions up to 4K x 2K @ 60 Hz
- Distributes A/V up to 15 ft. when used with 28 AWG HDMI cable
- Supports DTS-HD, Dolby® TrueHD and Dolby Digital Plus™
- Compatible with HDCP 2.2, 3D, EDID and HDMI 2.0
- Supports High Dynamic Range (HDR) for richer contrast and expanded color accuracy
- Expand the number of connected displays, up to 32, by cascading up to 3 levels of splitters together
- Plug and play—no software or drivers required

Package Includes

- B118-002-UHD-2 2-Port 4K 3D
 HDMI Splitter
- External power supply (Input: 100–240V, 50/60 Hz, 0.35A; Output: 5V 2A)
- International plug adapters (North America, Europe, U.K. and Australia)
- Mounting hardware
- Owner's manual



- Full 3D
- DTS-HD, Dolby TrueHD, Dolby Digital Plus and LPCM 7.1-channel surround sound audio
- 36-bit Deep Color (12 bits per channel)
- Video amplifier bandwidth of 600 MHz/6 Gbps per channel (18 Gbps total)
- Lip sync pass-through, xvYCC and x.vColor Easy to Use Almost Anywhere
- Plug and play—no software or drivers required
- Supports desktop use or wall-mounting using included hardware
- Power supply includes international plug adapters (North America, Europe, U.K. and Australia) **TAA-Compliant**
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Specifications

OVERVIEW		
UPC Code	037332200648	
AC Adapter	Input: 100-240V, 50/60Hz, 0.35A; Output: 5V, 2A, 4 ft	
	input. 100-240V, 50/60HZ, 0.35A, Oulput. 5V, 2A, 4 it	
INPUT		
Voltage Compatibility (VAC)	100; 110; 120; 125; 127; 200; 208; 220; 230; 240	
External Power Supply Input Specs (V / Hz / A)	100-240V, 50/60HZ, 0.35A	
External Power Supply Output Specs (V / A)	5V / 2A	
External Power Supply Cord Length (ft.)	4.0	
External Power Supply Cord Length (m.)	1.2	
External Power Supply Plug(s)	NEMA 5-15P North America; CEE 7/16 Schuko; BS 1363 UK; AS/NZS 3112 Australia	
External Power Supply Certifications	CE; FCC; UL; cUL; TUV; CCC; PSE; C-Tick; GS; RoHS	
Bus Powered	No	
Product Length (in.)	3.61	
Product Length (ft.)	0.300	
USER INTERFACE, ALERTS & CONTROLS		
LED Indicators	(x1) Green (Power), (x2) Orange (Signal)	
PHYSICAL		
Color	Black	
Material of Construction	Metal	



Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

[
Rackmountable	Yes
Shipping Dimensions (hwd / cm)	5.51 x 18.39 x 16.41
Shipping Dimensions (hwd / in.)	2.17 x 7.24 x 6.46
Shipping Weight (kg)	0.45
Shipping Weight (lbs.)	0.99
Unit Dimensions (hwd / in.)	2.16 x 6.45 x 7.24
Unit Packaging Type	Box
Unit Weight (kg)	0.08
Unit Weight (Ibs.)	0.187
ENVIRONMENTAL	
Operating Temperature Range	32 to 104 F (0 to 40 C)
Storage Temperature Range	5 to 122 F (-15 to 50 C)
Relative Humidity	0% to 85% RH, Non-Condensing
CONNECTIONS	
Ports	2
Side A - Connector 1	HDMI (FEMALE)
Side B - Connector 1	(2) HDMI (FEMALE)
Connector Plating	Nickel
FEATURES & SPECIFICATIONS	
Max Supported Video Resolution	3840 x 2160 @ 60Hz
HDMI Specification	2.0
HDCP Specification	2.2
Audio Specification	DTS-HD, Dolby TrueHD, Dolby Digital Plus and LPCM 7.1 Channel Surround Sound
Driver Required	No
Max Supported Color Depth	36-bit Deep Color
EDID Compatible	Yes
3D Video Supported	Yes
Technology	HDMI
SPECIAL FEATURES	
HDR Support	Yes
STANDARDS & COMPLIANCE	
Certifications	FCC, CE, ROHS



WARRANTY	
Product Warranty Period (Worldwide)	3-year limited warranty

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies