



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

External 240V Rackmount Battery Pack for select Tripp Lite UPS Systems (BP240V5RT2U)

MODEL NUMBER: **BP240V5RT2U**



Highlights

- BP240V5RT2U is a replacement external battery pack intended to replace the original battery pack bundled with Tripp Lite SmartOnline SU5000RT3UHV UPS Systems
- 240VDC battery pack with convenient DC input connector

Description

Tripp Lite's BP240V5RT2U is a 2U external battery pack that serves as a replacement for the original battery pack bundled with Tripp Lite SmartOnline SU5000RT3UHV UPS Systems. Includes a simple DC input connection for fast installation.

NOTE - A maximum of ONE BP240V5RT2U can be connected to each SU5000RT3UHV installation (see specification table).

Features

- 2U external battery pack that serves as a replacement for the original battery pack bundled with Tripp Lite SmartOnline SU5000RT3UHV UPS Systems
- Includes a simple DC input connection for fast installation

Specifications

| OVERVIEW | |
|-----------------------------|-----------------------------|
| UPC Code | 037332122537 |
| INPUT | |
| UPS Input Cord Length (ft.) | 3 |
| UPS Input Cord Length (m) | 0.9 |
| Input Connection Type | Modular 3-wire DC connector |
| Input Phase | Single-Phase |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

| BATTERY | |
|---|---|
| Expandable Battery Runtime | This battery pack has no DC jack to connect more battery packs - and can only be used in a multiple battery installation as the final battery pack in the chain of connected battery packs. For additional battery packs beyond the single BP240V5RT2U provided with your SU5000RT3UHV UPS, use BP240V10RT3U which does include a DC jack to support the connection of multiple battery packs. |
| DC System Voltage (VDC) | 240 |
| UPS Connection | Black 3-point DC connector |
| PHYSICAL | |
| External Battery Pack Form Factor | Rack |
| Installation Form Factor Notes | Upright vertical tower configuration is not recommended for this model |
| Installation Form Factors Supported with Included Accessories | 4 post 19 inch rackmount |
| Installation Form Factors Supported with Optional Accessories | Wallmount (2POSTRMKITWM) |
| Material of Construction | Steel |
| Minimum Required Rack Depth (cm) | 73.02 |
| Minimum Required Rack Depth (inches) | 28.75 |
| Rack Height | 2U |
| Shipping Dimensions (hwd / cm) | 24.13 x 67.31 x 72.39 |
| Shipping Dimensions (hwd / in.) | 9.50 x 26.50 x 28.50 |
| Shipping Weight (kg) | 59.87 |
| Shipping Weight (lbs.) | 132.00 |
| Unit Dimensions (hwd / cm) | 8.9 x 44.5 x 52.7 |
| Unit Dimensions (hwd / in.) | 3.5 x 17.5 x 20.75 |
| Unit Weight (kg) | 41.00 |
| Unit Weight (lbs.) | 90.4 |
| WARRANTY | |
| Product Warranty Period (U.S. & Canada) | 2-year limited warranty |
| Product Warranty Period (International) | 1-year limited warranty |
| Product Warranty Period (Mexico) | 1-year limited warranty |
| Product Warranty Period (Puerto Rico) | 1-year limited warranty |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>