

# 72V External Battery Pack for Select Tripp Lite UPS Systems, 2U Rack/Tower, TAA

# MODEL NUMBER: BP72V18-2USTAA







TAA-compliant external battery pack provides extended runtime for compatible 72V Tripp Lite UPS systems.

### Features

**Gives Your Compatible Tripp Lite UPS System Extended Runtime**The BP72V18-2USTAA is compatible only with Tripp Lite's SU3000RTXLCDTAA and other UPS systems that specify the use of this battery pack. Not only does it provide extended runtime, but it can also be daisy-chained using its rear connector to additional external battery packs for even longer extended-run operation. Heavy-gauge cabling with high-current DC connectors is included for simple installation.

**Mounts in 2U of Space in 19 in. 4-Post Racks**This battery pack's multi-use form factor supports mounting in 2U of space in EIA-standard 19-inch racks using the included 4-post rack-mounting brackets. The BP72V18-2USTAA is also compatible with Tripp Lite's 2-9USTAND for upright tower configuration, 2POSTRMKITWM for 2-post racks or wall installation and UPDHDEARKIT for 2-point front-rail rack installation without rear supports (all accessories sold separately).

**TAA-Compliant for GSA Schedule Purchases**The BP72V18-2USTAA is compliant with the Federal Trade Agreements Act for GSA Schedule purchases.

2-Year Warranty and Environmentally Responsible DesignThe BP72V18-2USTAA comes with a 2year warranty. It's manufactured in compliance with strict RoHS specifications, reflecting Tripp Lite's commitment to environmental responsibility.

## Highlights

- Connects to expandable 72V
  DC Tripp Lite UPS systems for extended runtime
- Daisy-chain connector supports additional battery packs for even longer runtime
- Mounts in 2U of space in 19 in. rack using included 4-post installation hardware
- Supports 2-post rack, wall or tower installation with optional accessories
- Complies with Federal Trade
  Agreements Act (TAA) for GSA
  Schedule purchases

### Applications

- Extends the runtime of your compatible Tripp Lite UPS system
- Daisy-chains to additional battery packs to provide even longer extended-run operation

### **Package Includes**

- BP72V18-2USTAA 72V External Battery Pack, 2U Rack/Tower, TAA
- Rack-mounting hardware
- Owner's manual

# **Specifications**

| OVERVIEW |              |
|----------|--------------|
| UPC Code | 037332223678 |
| INPUT    |              |



|   | Circle Direct   |  |
|---|---|--|
| Input Phase   | Single-Phase  |  |
| BATTERY   |   |  |
| DC System Voltage (VDC)                                       | 72  |  |
| UPS Connection  | Attached cable with black 3-point DC connector  |  |
| Typical Battery Lifespan                                      | 4-6 years typical (North America)   |  |
| PHYSICAL  |   |  |
| External Battery Pack Form Factor                             | Rack/Tower  |  |
| Installation Form Factors Supported with Included Accessories | 4 post 19 inch rackmount  |  |
| Installation Form Factors Supported with Optional Accessories | 2 post rackmount ( <a class="productLink" href="//www.tripplite.com/2-Post-Rack-Mount-Wall-Mount-Adapter-&lt;br&gt;Kit-select-Rack-Mount-UPS-Systems~2POSTRMKITWM">2POSTRMKITWM</a> ); Wallmount ( <a<br>class="productLink" href="//www.tripplite.com/2-Post-Rack-Mount-Wall-Mount-Adapter-Kit-select-Rack-Mount-UPS-<br/>Systems~2POSTRMKITWM"&gt;2POSTRMKITWM ); Tower ( <a <br="" class="productLink">href="//www.tripplite.com/2U-9U-Tower-Stand-Kit-select-Rack-Mount-UPS-Systems~2-9USTAND"&gt;2-<br/>9USTAND</a> ); 2-4 post front rail rackmount ( <a <br="" class="productLink">href="//www.tripplite.com/Heavy-Duty-2-post-Front-Mounting-Ear-Kit-UPSHDEARKIT"&gt;UPSHDEARKIT</a> )</a<br> |  |
| Material of Construction                                      | Steel   |  |
| Minimum Required Rack Depth (cm)                              | 68.07   |  |
| Minimum Required Rack Depth (inches)                          | 26.8  |  |
| Rack Height   | 2U  |  |
| Shipping Dimensions (hwd / cm)                                | 22.86 x 71.12 x 66.04   |  |
| Shipping Dimensions (hwd / in.)                               | 9.00 x 28.00 x 26.00  |  |
| Shipping Weight (kg)  | 58.51   |  |
| Shipping Weight (lbs.)  | 129.00  |  |
| Unit Dimensions (hwd / cm)                                    | 8.6 x 44 x 52.8   |  |
| Unit Dimensions (hwd / in.)                                   | 3.4 x 17.3 x 20.8   |  |
| Unit Weight (kg)  | 40.01   |  |
| Unit Weight (Ibs.)  | 88.20   |  |
| STANDARDS & COMPLIANCE  |   |  |
| Certifications  | Tested to CE; TAA Compliant   |  |
| WARRANTY  |   |  |
| Product Warranty Period (U.S. & Canada)                       | 2-year limited warranty   |  |
| Product Warranty Period<br>(International)                    | 1-year limited warranty   |  |
| Product Warranty Period (Mexico)                              | 1-year limited warranty   |  |
| Product Warranty Period (Puerto<br>Rico)                      | 1-year limited warranty   |  |



|  | Optional Coverage | 3 year, 5 year, next day and on-site warranty coverage available |
|--|-------------------|--|
|--|-------------------|--|

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies