

Network Surge Suppressor - Essential protection for TV/VCR coaxial lines

MODEL NUMBER: DCATV



Highlights

- Complete dataline (F coaxial) surge protection
- Protects against the effects of electrostatic discharge, faulty wiring and lightning
- Lifetime product warranty
- Heavy duty grounding lead

Description

Tripp Lite's DCATV offers type F coax line surge suppression for satellite receivers and broadcast antennas. Convenient coax input and output connections accept standard type F coax wiring. Surge suppression is handled with balanced arrays of high-speed avalanche diodes that divert excess energies created by electrostatic discharges, faulty wiring or lightning. Tripp Lite network surge suppressors reduce blown interface connections by safely shunting dataline surges to ground. Six inch heavy gauge grounding lead connects to designated grounding lugs. Lifetime warranty. **Not for use with cable modems.** SUPPRESSION: 1 set type F coax jacks, protects center and shield, 7.5V clamping

Features

- DCATV offers type F coax line surge suppression satellite receivers and broadcast antennas. Not for use with cable modems.
- Type F coax input and output connections
- Surge suppression utilizing high speed avalanche diodes divert excess energies on the network to ground
- 6 inch heavy gauge grounding lead connects to designated grounding lugs on protected equipment
- Lifetime product warranty

Specifications

OVERVIEW		
UPC Code	037332010889	
INPUT		
Recommended Electrical Service	120V, 230V	





Input Plug Type	F-Type Coax	
Input Cord Length (ft.)	0	
Right-Angle Plug	No	
Input Cord Length (m)	0.00	
Integrated Cord Clip	No	
ОИТРИТ		
Circuit Breaker (amps)	750	
USER INTERFACE, ALERTS & CONTROLS		
Diagnostic LED(s)	No	
SURGE / NOISE SUPPRESSION		
Clamping Voltage (RMS)	7.5	
Automatic Shut-Off	No	
DATALINE SURGE SUPPRESSION		
Telephone/DSL Protection	No	
Cable (Coax) Protection	Yes	
Network (Ethernet) Protection	No	
Additional Dataline Protection	Center & Shield	
PHYSICAL		
Anti-Microbial Protective Coating	No	
Integrated Keyhole Mounting Slots	No	
Shipping Dimensions (hwd / cm)	23.37 x 10.80 x 25.91	
Shipping Dimensions (hwd / in.)	9.20 x 4.25 x 10.20	
Shipping Weight (kg)	0.80	
Shipping Weight (lbs.)	1.76	
SPECIAL FEATURES		
Rotatable Outlets	No	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

https://www.tripplite.com/products/product-certification-agencies