



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

USB Sync/Charge Cable with Lightning Connector, Black, 10 ft. (3 m)

MODEL NUMBER: **M100-010-BK**



Charge and sync your latest-generation Apple iPhone, iPad or iPod over long distances with this 10-ft. lightning cable.

Features

The M100-010-BK USB Sync/Charge Cable connects your latest generation iPhone, iPad or iPod to the USB port on any computer, so you can charge your Apple device and transfer data over long distances. The 10-foot cable is MFi-certified for use with the latest generation of iPhone, iPad and iPod devices. Reversible 8-pin Lightning connector plugs into your Apple device in either direction.

Highlights

- Features a reversible 8-pin Lightning plug and a USB-A plug
- Works with any computer
- MFi-certified for broad compatibility with your Apple iPhone, iPad or iPod
- Compatible with all devices with 8-pin connectors
- Plugs into Apple device in either direction

System Requirements

- Device or charger with USB-A port
- iPhone, iPad, iPad mini, iPad mini 2, iPad mini 3, iPad mini 4, iPad Air, iPad Air 2, iPad Pro 12.9 inch, iPad Pro 10.5 inch, iPad Pro 9.7 inch and iPod Touch devices with Lightning port

Package Includes

- M100-010-BK USB Sync/Charge Cable with Apple Lightning Connector

Specifications

| OVERVIEW | |
|--------------------|--------------|
| UPC Code | 037332189776 |
| INPUT | |
| Cable Length (ft.) | 10 |
| Cable Length (m) | 3 |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

| PHYSICAL | |
|-------------------------------------|------------------------------|
| Cable Jacket Rating | VW-1 |
| Cable Outer Diameter (OD) | 3.7mm |
| Color | Black |
| Material of Construction | PVC |
| Shipping Dimensions (hwd / cm) | 14.48 x 3.30 x 7.11 |
| Shipping Dimensions (hwd / in.) | 5.70 x 1.30 x 2.80 |
| Shipping Weight (kg) | 0.14 |
| Shipping Weight (lbs.) | 0.30 |
| Unit Packaging Type | Box |
| Wire Gauge (AWG) | 28/21 |
| ENVIRONMENTAL | |
| Operating Temperature Range | -4 to 140 F (-20 to 60 C) |
| Storage Temperature Range | -4 to 176 F (-20 to 80 C) |
| Relative Humidity | 0% to 90% RH, Non-Condensing |
| CONNECTIONS | |
| Side A - Connector 1 | USB A (MALE) |
| Side B - Connector 1 | LIGHTNING (MALE) |
| Connector Plating | Nickel |
| Contact Plating | Gold |
| FEATURES & SPECIFICATIONS | |
| USB Specification | USB 2.0 (up to 480 Mbps) |
| Technology | Lightning; USB |
| STANDARDS & COMPLIANCE | |
| Certifications | RoHS, CA65, REACH, MFi |
| WARRANTY | |
| Product Warranty Period (Worldwide) | 2-year limited warranty |

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>