

Serial ATA (SATA) Latching Signal Cable 7Pin (M/M), 8-in.

MODEL NUMBER: **P940-08I**



Description

Tripp Lite expands its line of hard drive cables with the introduction of our new line of serial ATA cables. This 8inch signal cable connects any high speed Serial ATA device to a Serial ATA controller. Serial ATA delivers two significant benefits: it supports much higher data transfer rates (up to 6.0 Gbps) and the narrow cable design helps improve internal air flow. Perfect for the desktop or server that has multiple drives. These cables feature 7-pin female latching connectors and offer easy, secure installation.

Features

- Connect your high-speed Serial ATA device to a Serial ATA controller
- Compatible with Serial ATA Hard Drives, Blu-ray/DVD/CD Drives and other Serial ATA devices
- Metal latches ensure secure connections
- Support data transfer rates of up to 6.0 Gbps
- Narrow cables design simplifies cable routing and installation and improves air flow within CPU (no more big ribbons blocking air movement)
- Meets Serial ATA 1.0 standards, including Errata 029
- Cable is shielded to protect against EMI/RFI

Specifications

OVERVIEW	
UPC Code	037332140999
INPUT	

Highlights

- Connect your high-speed Serial ATA device to a Serial ATA controller
- Support data transfer rates of up to 6.0 Gbps (SATA II)
- Cable is shielded to protect against EMI/RFI

Applications

- Connect your high-speed Serial ATA device to a Serial ATA controller
- Compatible with Serial ATA Hard Drives, Blu-ray/DVD/CD Drives and other Serial ATA devices

System Requirements

- Serial ATA device
- Serial ATA controller

Package Includes

- P940-08I Latching Serial ATA Signal Cable - 8 in.



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Cable Length (ft.)	0.7
Cable Length (m)	0.2
Cable Length (in.)	8
Cable Length (cm)	20.32
PHYSICAL	
Cable Outer Diameter (OD)	2.4/8.0mm
Color	Red
Shipping Dimensions (hwd / cm)	13.46 x 9.91 x 1.27
Shipping Dimensions (hwd / in.)	5.30 x 3.90 x 0.50
Shipping Weight (kg)	0.06
Shipping Weight (lbs.)	0.14
Wire Gauge (AWG)	26
CONNECTIONS	
Side A - Connector 1	7 PIN SATA (MALE)
Side B - Connector 1	7 PIN SATA (MALE)
FEATURES & SPECIFICATIONS	
Technology	SATA/eSATA
STANDARDS & COMPLIANCE	
Certifications	ROHS
WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice.

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>