

Serial ATA (SATA) Latching Signal Cable (7Pin/7Pin), 19-in.

MODEL NUMBER: P940-19I



Description

Tripp Lite expands its line of hard drive cables with the introduction of our new line of serial ATA cables. The signal cables connect any high speed Serial ATA device to a Serial ATA controller. Serial ATA delivers two significant benefits: it support much higher data transfer rates (up to 6.0 Gbps...backward compatible to 1.5Gbps) and the narrow cable design helps improve internal air flow. Perfect for the desktop or server that has multiple drives. These cables feature 7-pin straight/7-pin straight latching connectors and offer easy, secure installation.

Features

- · Connect your high-speed Serial ATA device to a Serial ATA controller
- Compatible with Serial ATA Hard Drives, Blu-ray/DVD/CD Drives and other Serial ATA devices
- Metal latches ensure secure connections
- Support data transfer rates of up to 6.0 Gbps
- Narrow cables design simplifies cable routing and installation and improves air flow within CPU (no more big ribbons blocking air movement)
- Meets Serial ATA 1.0 standards, including Errata 029
- · Cable is shielded to protect against EMI/RFI

Highlights

- Connect your high-speed Serial ATA device to a Serial ATA controller
- Support data transfer rates of up to 6.0 Gbps
- Cable is shielded to protect against EMI/RFI

Applications

- Connect your high-speed Serial ATA device to a Serial ATA controller
- Compatible with Serial ATA
 Hard Drives, Blu-ray/DVD/CD
 Drives and other Serial ATA
 devices

System Requirements

- Serial ATA device
- Serial ATA controller

Package Includes

19-in. Serial ATA (SATA)
 Latching Signal Cable
 7Pin/7Pin, Straight/Straight

Specifications

OVERVIEW	
UPC Code	037332118134
INPUT	





	-	
Cable Length (ft.)	1.6	
Cable Length (m)	0.5	
Cable Length (in.)	18	
Cable Length (cm)	45.72	
PHYSICAL		
Cable Outer Diameter (OD)	2.4/8.0mm	
Color	Red	
Shipping Dimensions (hwd / cm)	13.46 x 9.91 x 1.27	
Shipping Dimensions (hwd / in.)	5.30 x 3.90 x 0.50	
Shipping Weight (kg)	0.06	
Shipping Weight (lbs.)	0.14	
Wire Gauge (AWG)	26	
CONNECTIONS		
Side A - Connector 1	7 PIN SATA (MALE)	
Side B - Connector 1	7 PIN SATA (MALE)	
FEATURES & SPECIFICATIONS		
Technology	SATA/eSATA	
STANDARDS & COMPLIANCE		
Certifications	ROHS	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies