

Management Interface

The management interface for this PDU model is transitioning to a new technology platform. The new interface can be distinguished by a USB-A port (for EnviroSense2 modules) in place of the round ENVIROSENSE port. For managing the units containing the round port, Tripp Lite recommends using the [PowerAlert Console Launcher](#) rather than a web browser. This application enables local access of the PDU using a self-contained, compatible Java Runtime Environment version. The Console Launcher can be downloaded for free; click the above link or go to the Management Solutions / Utilities page. Units with the new interface work with most current web browsers.

3.2-3.8kW Single-Phase Monitored PDU, 208/220/230/240V Outlets (8-C13), C20/L6-20P Adapter, 8ft Cord, 1U Rack-Mount; TAA Compliant

MODEL NUMBER: PDUMNH20HV



Description

Tripp Lite single phase Monitored PDU / Power Distribution Unit offers real-time remote monitoring of voltage, frequency and load levels via built-in network connection. LX Platform interface supports custom notification of user-specified remote conditions via email, secure web, SNMP, Telnet or SSH interface. PDU lighted digital display enables visual monitoring of PDU output current to prevent circuit overloads as additional equipment is added. Offers reliable rackmount multi-outlet power distribution from any protected UPS, generator or mains input power source. High quality design includes rugged all-metal housing and secure rackmount installation with included mounting accessories.

Features

- 20A single phase 208/230/240V Monitored Power Distribution Unit / PDU (agency derated to 16A continuous)
- C20 inlet; 8ft / 2.4m C20 cable and NEMA L6-20P plug adapter included
- 1U horizontal rackmount installation
- 8 C13 outlets
- Lighted display reports output power consumption in amps
- Built-in network interface reports voltage, frequency and PDU loading via network or secure web browser interface with options for user specified alarm and notification thresholds
- LX Platform interface allows full remote access for power monitoring with email notifications via secure

Highlights

- Monitored 16/20A 208/220/230/240V PDU, 1U horizontal rackmount
- Reports voltage, frequency & load level via ethernet interface
- Visual current meter, Reversible housing
- C20 inlet; 8ft / 2.4m C20 cable with L6-20P plug adapter
- 8 C13 outlets with included plug-lock retention sleeves
- Temperature, humidity and contact-closure monitoring options
- TAA Compliant for GSA Schedule purchases

Package Includes

- Rackmount PDU
- Rack mounting brackets
- Plug retention inserts
- 2.6m C19-to-C20 power cord
- C19-to-L6-20P plug adapter
- Mounting hardware
- Owner's manual



web browser, SNMP, telnet or SSH

- Optional EnviroSense2 modules (sold separately) provide a variety of environmental monitoring capabilities
- 10/100 Mbps auto-sensing allows optimal communication with 10/100 Base-T networks
- Real-time clock backup maintains the time of day and date even if the PDU is unpowered
- Tiered access privileges allow an administrator and a guest to login via web browser for monitoring
- Alert notifications via email or SNMP traps offer immediate event notification
- Firmware upgrade ability supports future product enhancements.
- Mounting flanges support installation in 2 and 4 post racks, with additional support for wall-mount and under-counter installation formats
- Mounting ears are reversible for front or rear facing rackmount installation
- Included cord retention brackets keep vital network equipment plugged in and continuously powered
- TAA Compliant for GSA Schedule purchases

Specifications

| OVERVIEW | |
|-----------------------------------|--|
| UPC Code | 037332160928 |
| PDU Type | Monitored |
| INPUT | |
| PDU Input Voltage | 208; 220; 230; 240 |
| Recommended Electrical Service | 20A 208/240V; 16A 230V |
| Maximum Input Amps | 16 |
| PDU Plug Type | NEMA L6-20P; IEC-320 C20 |
| Input Phase | Single-Phase |
| Input Cord Length (ft.) | 8.5 |
| Input Cord Length (m) | 2.59 |
| OUTPUT | |
| Frequency Compatibility | 50 / 60 Hz |
| Output Capacity Details | 3.84kW (240V), 3.68kW (230V), 3.52kW (220V), 3.33kW (208V) / 16A total capacity; 12A (10A CE) max per C13 outlet |
| Output Receptacles | (8) C13 |
| Output Nominal Voltage | 208; 220; 230; 240 |
| Overload Protection | n/a |
| USER INTERFACE, ALERTS & CONTROLS | |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

| | |
|--------------------------------------|---|
| Front Panel LCD Display | Digital meter reports PDU output current in amps |
| Switches | n/a |
| LED Indicators | n/a |
| PHYSICAL | |
| Form Factors Supported | 1U horizontal rackmount in 2 or 4 post racks |
| Material of Construction | Metal |
| Minimum Required Rack Depth (cm) | 43.43 |
| Minimum Required Rack Depth (inches) | 17.1 |
| PDU Form Factor | Horizontal (1U) |
| Shipping Dimensions (hwd / cm) | 15.24 x 52.70 x 58.42 |
| Shipping Dimensions (hwd / in.) | 6.00 x 20.75 x 23.00 |
| Shipping Weight (kg) | 6.12 |
| Shipping Weight (lbs.) | 13.50 |
| Unit Dimensions (hwd / cm) | 4,4 x 44,4 x 37,6 |
| Unit Dimensions (hwd / in.) | 1.75 x 17.5 x 14.8 |
| Unit Weight (kg) | 4.08 |
| Unit Weight (lbs.) | 9.00 |
| ENVIRONMENTAL | |
| Storage Temperature Range | -30°C to +50°C (-22°F to +122°F) |
| Relative Humidity | 5 to 95% non-condensing |
| COMMUNICATIONS | |
| SNMP Compatibility | Pre-installed LX platform interface provides remote monitoring via Java-free HTML5 web interface, telnet, SSH and SNMP management systems |
| SPECIAL FEATURES | |
| High Availability PDU Features | Auto Probe Monitoring (included) |
| STANDARDS & COMPLIANCE | |
| Certifications | Tested to UL 60950-1 (USA, Canada), CE (EEA), Class A (Emissions), NOM (Mexico), RoHS compliant, TAA Compliant |
| WARRANTY | |
| Product Warranty Period (Worldwide) | 2-year limited warranty |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>