

## SmartOnline SV Series 20kVA Large-Frame Modular Scalable 3-Phase On-Line Double-Conversion 208/120V 50/60 Hz UPS System

MODEL NUMBER: **SV20KL**



3-phase 20kVA UPS system offers network-grade power protection in a highly configurable, modular and scalable large-chassis rack-width frame. Pre-installed WEBCARDLX network interface allows full remote access 24/7.

### Description

The SV20KL SmartOnline® SV Series 20kVA 3-Phase On-Line Double-Conversion UPS System delivers true scalability and offers the highest level of secure, uninterrupted power protection. Featuring a modular, scalable design with high-efficiency voltage and frequency independent (VFI) operation, this on-line UPS system is ideal for protecting a variety of critical IT systems.

The SV20KL includes pre-installed input, bypass and output breakers, as well as a static transfer switch (STS) and one included 20kVA SV20PM power module. Space is included for up to seven additional user-installable SV20PM power modules to accommodate increased capacity up to 140kVA with N+1 fault tolerance. Each power module is rated at 0.9 power factor for maximum power to the connected load.

The Java-free HTML5-based WEBCARDLX interface enables full remote access for site power and UPS status monitoring, configuration, control and email notifications via secure web browser, SNMP, telnet or SSH. It supports 10/100 Mbps auto-sensing for optimum communication with an Ethernet network.

With up to 92% efficiency in standard mode and up to 99% efficiency in optional economy mode, this 20kVA UPS system helps you reduce operating and cooling costs. Automatic and manual bypass options keep connected equipment operational during routine maintenance or critical power module failure. Batteries are not included. External  $\pm 120\text{VDC}$  battery cabinets, such as Tripp Lite's BP240V370, are sold separately.

### Features

#### Highlights

- Scalable capacity up to 140kVA with N+1 redundancy
- Economy mode option helps reduce operating and cooling costs
- Pre-installed WEBCARDLX network interface for 24/7 remote access
- DSP/IGBT technology and 1% output voltage regulation
- Batteries not included; external battery cabinets sold separately

#### Package Includes

- SV20KL SmartOnline SV Series 20kVA 3-Phase On-Line Double-Conversion UPS System
- Pre-installed WEBCARDLX network interface
- (1) SV20PM 20kVA power module (shipped separately)
- Owner's manual



#### **20kVA 18kW 3-Phase Large-Chassis UPS System**

- Supports 208/120V or 220/127V AC 50/60Hz Wye 4-wire plus Earth hardwire input and output wiring
- Dual hardwire input design enables operation from up to 2 power sources
- Network-grade sine-wave AC output with 1% output voltage regulation and less than 1.5% output total harmonic distortion
- Tested to UL 1778 (U.S.), CSA (Canada) and NOM (Mexico) standards
- High 0.9 power factor for maximum power to the connected load
- Batteries not included—external  $\pm 120$ VDC battery cabinets, such as Tripp Lite's BP240V370, sold separately

#### **Pre-Installed WEBCARDLX Network Interface**

- Allows full remote access for power monitoring, configuration, control and email notifications via secure web browser, SNMP, telnet or SSH
- Supports 10/100 Mbps auto-sensing for communication with an Ethernet network
- Optional EnviroSense2 sensors (sold separately) enable site monitoring of temperature, humidity and contact-closure status
- No Java required

#### **Modular, Scalable Design for Maximum Flexibility**

- Modular configuration with hot-swappable power modules enables easy and fast maintenance with zero downtime
- Open slots for up to 7 additional 20kVA SV20PM power modules accommodate increased capacity up to 140kVA with N+1 fault tolerance

#### **Optional Economy Mode**

- Up to 99% efficient in optional economy mode to lower operating and cooling costs

#### **Wide Input/Narrow Output Voltage Operating Range**

- Enables full continuous online operation during brownouts as low as 156V and overvoltages up to 253V
- Regulates output voltage within 1% of the selected nominal output voltage in on-line double-conversion mode

#### **Advanced IGBT Inverter with Digital Signal Processor (DSP) Technology**

- Provides for less than 3% input total harmonic distortion (THDi) to support 1:1 generator sizing and prevent the need to oversize generator systems relative to UPS capacity

#### **Automatic and Manual Bypass Options**

- Keep connected equipment operational during routine maintenance or critical power module failure

## **Specifications**



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

| OVERVIEW                            |   |
|-------------------------------------|---|
| UPC Code                            | 037332196248  |
| UPS Type                            | On-Line   |
| INPUT                               |   |
| Rated input current (Maximum Load)  | SV20KL 20kVA Configuration: 60A; Maximum 140kVA Large Chassis Configuration: 420A; 330A maximum inrush current  |
| Nominal Input Voltage(s) Supported  | 120/208V 3-PH Wye; 127/220V 3-PH Wye  |
| Nominal Input Voltage Description   | Set of two hardwire input connections enables 3-Phase Wye, 4 wire (3P, N, G) inputs from two separate power sources   |
| UPS Input Connection Type           | Hardwire  |
| Input Circuit Breakers              | MAIN and ALTERNATE AC inputs are each protected by 400A 3 pole magnetic breakers  |
| Input Phase                         | 3-Phase   |
| Input Frequency                     | 40 to 70Hz (online mode); 50/60Hz Auto-selectable   |
| Power Factor (Input)                | Greater than 0.99 (full load)   |
| THDi                                | Less than 3% (full linear load)   |
| OUTPUT                              |   |
| Output Volt Amp Capacity (VA)       | 20000   |
| Output kVA Capacity (kVA)           | 20  |
| Output Watt Capacity (Watts)        | 18000   |
| Output kW Capacity (kW)             | 18  |
| Power Factor                        | 0.9   |
| Crest Factor                        | 3:1   |
| Nominal Voltage Details             | Output THD full resistive load: <1.5%; Output THD non-linear load: <4%; Max DC offset: $\pm 50\text{mV}$ ; Max Phase angle deviation: 2°; Max Voltage unbalance deviation: 1%; Output short-circuit protection included       |
| Frequency Compatibility             | 50 / 60 Hz; Supports 50 to 60 Hz and 60 to 50 Hz conversion   |
| Frequency Compatibility Details     | Auto-selectable, user adjustable  |
| Output Receptacle Details           | Output wiring: 3P, N, E   |
| Output Circuit Breakers             | 630A 3 pole magnetic breaker  |
| Output AC Waveform (AC Mode)        | Pure Sine wave  |
| Output AC Waveform (Battery Mode)   | Pure Sine wave  |
| Output Capacity Details             | OVERLOAD CAPABILITY: Supports 105-110% load for 1 hour, 111-125% load for 10 minutes, 126-150% for 1 minute and Over 150% for 200ms before switching to Bypass; Online operation resumes when load is reduced to 100% or less |
| Nominal Output Voltage(s) Supported | 120/208V 3-PH Wye; 127/220V 3-PH Wye  |
| Output Receptacles                  | Hardwire  |

4 / 7



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
www.tripplite.com

| VOLTAGE REGULATION  |  |
|---|--|
| Voltage Regulation Description                                | Online, double-conversion power conditioning   |
| Overvoltage Correction  | Maintains continuous output in online mode, without using battery power, during overvoltages to 253V (Ph-Ph), reducing output to within 1% of selected 208/120V, 220/127V nominal output voltage   |
| Undervoltage Correction                                       | Maintains continuous output in online mode, without using battery power, during brownout/undervoltage conditions to 156V (Ph-Ph) at full load and to 121V (Ph-Ph) at 70% output load or less, increasing output to within 1% of selected 208/120V or 220/127V nominal output voltage |
| USER INTERFACE, ALERTS & CONTROLS                             |  |
| Front Panel LCD Display                                       | 145mm front panel LCD display with directional scroll and select buttons offers complete operating status display, plus setting and selection options for all UPS functions  |
| Switches  | Front panel buttons include ESC (menu escape), UP/LEFT (menu up / left), DOWN/RIGHT (menu down / right), ENTER (confirm selection), HOME (return to home screen) and POWER (on/off power control); Also includes Manual Bypass switch  |
| Alarm Cancel Operation  | Audible alarms can be muted using on-screen prompts  |
| Audible Alarm   | Unique audible alarms for POWER ON / POWER OFF (alarm sounds for 2 seconds), BATTERY MODE (alarm sounds every 2 seconds), LOW BATTERY (alarm sounds every 0.5 seconds), UPS ALARM (alarm sounds every 1 second), UPS FAULT (continuous alarm)  |
| LED Indicators  | Front panel LED indicators represent INPUT (green), BYPASS (amber), INVERTER (green), BATTERY (red) and ALARM (red)  |
| SURGE / NOISE SUPPRESSION                                     |  |
| EMI / RFI AC Noise Suppression                                | Yes  |
| AC Suppression Joule Rating                                   | 2496   |
| AC Suppression Joule Rating Details                           | 2496 joules (Ph-Ph), 2496 joules (Ph-N), 1872 joules (N-E)   |
| AC Suppression Response Time                                  | Instantaneous  |
| PHYSICAL  |  |
| Cooling Method  | Fans   |
| Installation Form Factors Supported with Included Accessories | Tower  |
| Primary Form Factor   | Tower  |
| Primary UPS Depth (mm)  | 1,100  |
| Primary UPS Height (mm)                                       | 2,010  |
| Primary UPS Width (mm)  | 600  |
| Shipping Dimensions (hwd / cm)                                | 138.43 x 72.39 x 107.95  |
| Shipping Dimensions (hwd / in.)                               | 54.50 x 28.50 x 42.50  |
| Shipping Weight (kg)  | 479.90   |
| Shipping Weight (lbs.)  | 1058.00  |
| UPS Housing Material  | Steel  |





**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
www.tripplite.com

|   |  |
|---|--|
| UPS Power Module Dimensions (hwd, cm)                       | 200.99 x 59.99 x 109.98  |
| UPS Power Module Dimensions (hwd, in.)                      | 79.13 x 23.62 x 43.3   |
| UPS Power Module Weight (kg)                                | 307.54   |
| UPS Power Module Weight (lbs.)                              | 678  |
| <b>ENVIRONMENTAL</b>  |  |
| Operating Temperature Range                                 | 0° to +40°C (+32° to +104°F); De-rates to 90% capacity at 35°C / 95°F and 80% capacity at 40°C / 104°F   |
| Storage Temperature Range                                   | -15° to +60°C (+5° to +140°F)  |
| Relative Humidity   | 0 to 95%, non-condensing   |
| AC Mode BTU / Hr. (Full Load)                               | 5912   |
| AC Economy Mode BTU / Hr. (Full Load)                       | 570  |
| AC Economy Mode Efficiency Rating (100% Load)               | 99%  |
| Audible Noise   | Less than 73 DBA front-side, 1m  |
| Operating Elevation (m)                                     | Up to 1000m (At elevations over 1000m, output de-rates by 1% per 100m)   |
| <b>COMMUNICATIONS</b>                                       |  |
| Network Management Cards                                    | <a href="#">WEBCARDLX</a> & <a href="#">MODBUSCARDSV</a> & <a href="#">RELAYCARDSV</a>   |
| Network Monitoring Port Description                         | Includes pre-installed Tripp Lite WEBCARDLX network interface  |
| PowerAlert Software   | For local monitoring via the UPS's built-in communication ports, download PowerAlert Local software at <a href="http://www.tripplite.com/poweralert">http://www.tripplite.com/poweralert</a>   |
| Communications Cable  | DB9 cabling included   |
| SNMP Compatibility  | Includes pre-installed <a href="#">WEBCARDLX</a> network interface card  |
| Communications Interface                                    | DB9 Serial; EPO (emergency power off); Pre-installed network card; Slot for SNMP/Web interface   |
| <b>LINE / BATTERY TRANSFER</b>                              |  |
| Transfer Time   | No transfer time (0 ms.) in online, double-conversion mode; Less than 20 ms. transfer time in economy mode   |
| Low Voltage Transfer to Battery Power (Setpoint)            | Maintains continuous operation without using battery power during brownout/undervoltage conditions to to 156V (Ph-Ph) Full load or 121V (Ph-Ph) 70% load or less; Below the low transfer voltage point, output is maintained utilizing reserve battery power |
| High Voltage Transfer to Battery Power (Setpoint)           | Maintains continuous operation without using battery power during overvoltages to 253V (Ph-Ph), reducing output within 1% of nominal; Above this point, output is maintained utilizing reserve battery power   |
| <b>SPECIAL FEATURES</b>                                     |  |
| Cold Start (Startup in Battery Mode During a Power Failure) | Cold-start operation supported   |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

|   |   |
|---|---|
| High Availability UPS Features          | Automatic inverter bypass; Hot swappable batteries; Hot swappable UPS power module; Auto Probe Monitoring (included); Zero transfer time; On-Line/Double-Conversion |
| Green Energy-Saving Features            | Greater than 95% efficiency - GREEN UPS; High efficiency economy mode operation; Schedulable daily hours of economy mode operation                                  |
| <b>STANDARDS &amp; COMPLIANCE</b>       |   |
| UPS Certifications                      | ROHS (Restriction of Hazardous Substances); Tested to CSA (Canada); Tested to NOM (Mexico); Tested to UL1778 (USA)  |
| UPS Certification Details               | UL1778: 2014 5th Edition; CSA C22.2 No. 107.3.14; FCC Part 15 Class A   |
| <b>WARRANTY</b>                         |   |
| Product Warranty Period (U.S. & Canada) | 1-year limited warranty   |
| Product Warranty Period (International) | 2-year limited warranty   |
| Product Warranty Period (Mexico)        | 1-year limited warranty   |
| Product Warranty Period (Puerto Rico)   | 2-year limited warranty   |
| 3-Phase Warranty Statement              | <u><a href="#">Tripp Lite 3-Phase UPS Factory Warranty</a></u>  |

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:  
<https://www.tripplite.com/products/product-certification-agencies>